USE THE BLUE SEAL A RATED ISO-BLOCO WIN2WALL



THE SOLUTION FOR THE PERFECT INSTALLATION **ISO-BLOCO WIN2WALL**

Why install A energy rated products with a gap around equivalent to something like D (U-value of 2.3)?

When you can have an installation equivalent that can achieve higher than A energy and sound ratings (U-value of 1.2 to 0.7 and reduction of 40 to 63 dB)?

Use the simple to apply sealing tape that will guarantee the windows are installed correctly: A energy and sound rate installation (U-value of 1.2 to match the product installed).

PRODUCT ADVANTAGES:

- thermally suitable for UK energy rated windows

- more energy saving
 more sound reduction
 longer working life expectancy
 cleaner and better performance than silicone

SAY GOODBYE TO UNSIGHTLY & NON ENERGY EFFICIENT WINDOW INSTALLATION. SAY HELLO TO THE NEW, MODERN METHOD!

SAY GOODBYE TO:



Unsightly & non energy efficient window installation





Perfect sealing with ISO-BLOCO WIN2WALL

WEATHER, THERMAL & ACOUSTIC SEAL:



Fit seal to window, fit window to wall

ISO-Chemie GmbH \ 268 Bath Road \ Slough, Berkshire \ SL1 4DX \ UK \ Tel.: +44 (0)1207 56 68 67 \ Fax: +44 (0)1207 56 68 69 www.iso-chemie.co.uk \ info@iso-chemie.co.uk