



Hammerite Underbody Seal

About this product

Hammerite Underbody Seal gives heavy duty protection for underbody, wheel arches and other high impact areas

Key Benefits

- Protects against stones, water and salt
- Proven corrosion resistance
- Remains flexible will not crack or peel
- ✓ Non drip super smooth application
- - Free from gritty and abrasive particles
- Prolongs your vehicles life

Special Features

- Non-drip super smooth application
- Free from gritty and abrasive particles

Technical Information

Touch dry	n/a
Recoatable	n/a
Coverage	500ml covers 1m2

Product Information

Typical Use

Remove heavy deposits of dirt, grease and oil. Wire brush-off loose rust and paint. Ensure surface is clean and dry

Composition

Solvent-based

Key Benefits

Protects against stones, water and salt, Proven corrosion resistance, Remains flexible - will not crack or peel, Non drip super smooth application, Free from gritty and abrasive particles, Prolongs your vehicles life

Pack size

500ML, 1L, 2.5L

System Information

Do not apply to sump, gearbox, exhaust system, cables or any mechanical parts. Brush on to a maximum film thickness of 2mm. Allow to dry overnight. To remove Hammerite Underbody Seal from paintwork, wipe off immediately with white spirit.

Application Method

Do not apply to sump, gearbox, exhaust system, cables or any mechanical parts. Brush on to a maximum film thickness of 2mm. Allow to dry overnight. To remove Hammerite Underbody Seal from paintwork, wipe off immediately with white spirit.