

StopWater Premium

Version: apr-21

StopWater Premium is a temporary anti-humidity treatment which allows the application of paint on surfaces with humidity. It is applied prior to painting and also acts as a consolidator of mineral substrates. The product degrades as a result of the high pH of Graphenstone coatings.

PRODUCT DESCRIPTION

Features:

- Retains moisture.
- Temporary barrier. Progressive degradation.
- Consolidates mineral substrates.
- Allows mineral paint application.
- Allows correct drying for lime-based paints.
- Increases solution durability.
- Penetrates the substrate.
- Does not form an impermeable layer.
- Does not alter substrate breathability.
- Suitable for interiors and exteriors.

Technical properties:

Specific weight	1.04 ± 0.05 g/cm ³
pH	8 ± 1
Viscosity	< 50 U.K.
Volume Solids	30 ± 5%
Composition	Acrylic copolymer
Appearance	Transparent liquid
Finish	Transparent

Yield/Coverage:

28-32 m²/L or 1140-1300 Sq.Feet per Gallon (1 coat). However, exact yield depends on type and condition of substrate, as well as tools used. Exact consumption should be determined by making onsite sample.

Pack Size:

1L and 5L.

Storage:

Store in original container. Keep tightly sealed in cool, dry place. Do not store in extremes of temperature, avoid direct exposure to sunlight and protect from

frost. Unopened, storage stability is 12 months from date of manufacture.

APPLICATION METHOD

Substrate Types:

Surfaces with high humidity.

Substrate Condition:

The substrate must be dry, firm, well adhered, even and free of any impurities that could hinder the perfect bonding of the product.

Substrate Preparation:

It is highly recommended to locate and repair the primary source of damp for a lasting solution.

Any organic growth and/or other impurities should be removed by thorough cleaning using specific products for this purpose.

If the substrate is not well adhered, remove the non-adherent areas by scraping and brushing.

If the substrate has salt deposits, brush and apply *Neutralysal Premium*.

Product preparation:

Shake and dilute 1: 1 with water to ensure a good mix.

Application method:

Apply one coat evenly.

Drying:

At 25 ° C (77 °F) and 60% relative humidity: 8-12 hours. Apply paint within 24 hours of product application.

Ambient conditions:

The working temperature (ambient and substrate) must be between +10 °C and +32 °C (50 °F and 90 °F). Do not apply under direct sunlight or on surfaces heated by the sun.

Tools:

Roller, brush or airless.

Tool cleaning:

Clean tools after use with warm water.

Notes:

Mineral substrates must be at least 28 days old.

Do not apply to surfaces in permanent contact with water. It is not a waterproofing system.

It is recommended to protect the treated surface from rain before paint application.

Parts that are not going to be treated should be protected (glassware or carpentry).

To maintain product efficacy do not mix with other brands.

Complementary products:

It is recommended to use the Graphenstone® product range for complementary actions according to the application, repair and/or finish required. Please refer to the corresponding Technical Data Sheets.

ADDITIONAL INFORMATION

Usage warnings:

None, particularly in situations where normal product application is expected and by people without any specific medical conditions. Alkaline product, protect skin and eyes especially. Do not inhale the product. Keep out of reach of children.

Waste management:

According to local legal regulations. The containers are made of polypropylene. Please contribute to the protection of the environment, do not throw waste down the drain and use the nearest recycling point.

Sustainability gesture:

Minimise product waste by carefully estimating the amount you will need. Store any unused product for future use according to the "Storage" guidelines.

Safety information:

For information regarding safety, physical, ecological and toxicological details please see the latest version of the product's Material Safety Data Sheet.

Technical Support:

For further information, please contact your local distributor or manufacturer.
(technicalsupport@graphenstone.com).

GRAPHENSTONE

THE ORIGINAL AND AUTHENTIC

PAINTS
FOR THE
green
GENERA
TION

#PaintDifferent

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Any modification to the instructions and recommendations by the user, he will assume all the corresponding risk and responsibility. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.

Graphenstone | IEdiSa, S.A. Polg Ind Poliviso. Carpinteros, 25. 41520 El Viso del Alcor, Sevilla. España (Spain). Phone: +34 955 529 435

