

BREWERS DECORATORS CAULK

High quality acrylic dispersion sealant

Product Description

Brewers Decorators Caulk is a plasto elastic sealant based on an acrylic dispersion. After application the product forms a soft plasto-elastic rubber by evaporation of water from the sealant.

Benefits

- Paintable with water based- and synthetic paints
- Perfect adhesion without the use of a primer, even slightly damp substrates
- In- and outside applicable
- Nearly non smelling
- Easy to apply
- Easy to clean
- Non corrosive towards metals

Applications

Brewers Decorators Caulk was specifically developed to seal connection joints between stairs, walls, ceilings, skirtings, windowsills, wooden and metal window frames, concrete and brickwork. For interior use.

Directions Of Use

A well-designed joint is a joint with a sufficient width so it would be able to take and process the movement of the adjacent building elements. The joint depth should always be in the correct relationship of the joint width. A general rule is the ratio of joint depth to the width of the joint with a joint width till 10 mm is 1:1, with a minimum of 5mm in width and depth. For joints wider than 10 mm, the depth is the width divided by 3 plus 6 mm. For further questions please contact our technical service.

Technical Specifications

100 % modulus	DIN 53504 S2	0,3 N/mm ²
Application rate	@ Ø3 mm/4 bar	450 g/min
Application temperature		+5 °C to +40 °C
Base		Acrylic dispersion
Density	ISO 1183-1	1,71 g/ml
Elongation at break	DIN 53505/ ISO 868	200%
Flow	ISO 7390	< 2mm
Frost resistance during transportation		Up to -15 °C
Joint movement		7,5%
Shorea hardness	DIN 53505/ ISO 868	30
Skin formation	DBTM 16	5 minutes @ +23 °C/50% RH
Temperature resistance		-20 °C to +75 °C
Tensile strength	DIN 53504 S2	0,3 N/mm ²

These are typical values

Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Application temperature +5 °C to +40 °C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Substrates to be cleared of all loose particles, absorbent substrates are not required to be absolutely dry. Very porous substrates like: gypsum, airated concrete, limestone, etc, need to be primed with a mixture of 1 part

Brewers

DECORATOR CENTRES

BREWERS DECORATORS CAULK

High quality acrylic dispersion sealant

Brewers Decorators Caulk and 2 parts water. Always test adhesion prior to application. Finish and smooth with water.

Paintability

Brewers Decorators Caulk is paintable after full drying of sealant. During curing product will show shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recommend testing compatability with paint prior to application.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with Wipes and/or water and soap.

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life is up to 18 months from production date, stored in a dry place.

Certifications	EN 15651-1: F-EXT-INT 7.5P A+ French VOC Regulation
----------------	--

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Brewers warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Brewers. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Brewers written consent. The technical information in this document serves as an indication and is non-exhaustive. Brewers is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Brewers reserves the right to amend the wording of this document. Brewers cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.