INTRAlink²





INTRAlink²

A heavy duty, interlocking tile system with outstanding eco credentials, ideally suited to exposed entrance environments. This costeffective, closed construction entrance matting offers excellent durability and performance even under high point loading. Installation is simple, requiring no specialist cutting tools.



100% recycled PVC and Econyl



Engineered for Multi Directional Traffic



Excellent Moisture Absorption



5 Year Warranty










SPECIFICATION


INTRAlink²

Product Reference	INTRAlink ² PVC Grid Entrance Matting	
Strength Rating	High - suitable for areas with heavy foot and wheeled traffic	
Zonal Location	High Traffic environments Zone 2 Interior area - with high quality fibre inserts	
Construction	Closed construction, interlocking tile format - Tile size 250mm x 250mm. UV resistant, hardwearing 100% recycled PVC - with 100% Econyl recycled polyamide fibre inserts. PVC-free (PureBase) backing option available with Ultimate inserts	
Sustainability	100% recycled PVC carrier 100% Econyl Fibre inserts PVC-free PureBase option available with Ultimate inserts All inserts recyclable	
Typical Application	High Traffic Locations such as Retail, Sports, Education and Leisure facilities	
Design Options	Range of design options including logo application. Packaged in cases of 24 tiles (1.5m²) for ease of delivery and handling	
Weight	10.7kg/m ²	
Matwell Framing	INTO14 / INTRO12	
Slip Rating	Will vary with insert, in excess of PTV 38	
Warranty	5 years	
Uniclass 2015	Pr_35_57_11_26 Entrance Mats	
CAWS	N10 / 300 Entrance Matting	

PROFILE



А	14mm	1	Finished Floor surface
В	12mm	2	Recessed matwell frame
С	112mm Insert	3	Levelling latex to matwell base
D	250mm Tile Module	4	Screed sub-floor
		5	Screw fixings





INSFRTS

INTRAlux® Elite

Recommended for effective scraping and dirt removal



INTRAlux® Ultimate

PUREBASE®

Recommended for rapid moisture absorption, with PureBase backing



INTRAlux® Select

Best value fibre, for good all-round performance



208 Black



ENVIRONMENT & SUSTAINABILITY

INTRAsystems has an undeviating commitment to act responsibly in its care of the environment. Working on key projects throughout the UK and Europe, the company is familiar with all environmental ratings such as Ska, BREEAM and WRAP to help clients achieve, and exceed, their sustainability goals.

We are ISO 14001 accredited and all production processes are managed in accordance with the Waste Management Act, with a clear goal to 'reduce the production of waste and its harmful effects.' INTRAsystems regularly reviews its wider operations to minimise negative environmental impacts.

Our Environmental Sustainability Statement sets clear targets for ongoing improvement to ensure the company continues to play its part in helping tackle the climate crisis. Environmental credentials for each fibre option are provided and highlighted throughout this brochure.



BREEAM®



Benefits of specifying ECONYL® fibre

ECONYL® is regenerated nylon that would otherwise pollute the Earth. It is the same as brand new nylon and can be infinitely recycled, recreated and remoulded. ECONYL® is Cradle-to-Cradle certified and therefore our fibres are eligible for LEED® v4 points, as part of the LEED green building rating system.

PUREBASE

Benefits of specifying PureBase backing

PureBase is a new, PVC-free backing material for entrance matting. It has a significantly lower environmental impact in terms of production processing, greenhouse gas emissions and end of life waste disposal. PureBase is 20% lighter and 3 x more flexible for easier handling and installation.

