

Conex | Bänninger  
**Series 8000**



 A range of yellow brass threaded fittings.

**Features and benefits:**

- Available in sizes 1/8 - 2".
- Manufactured to EN 1254-4.
- Our bronze threaded fittings are made to DIN ISO 7.
- Suitable to material with EN 12165, CW617N, EN 12164 and CW617N.
- Hydraulic working temperatures and pressures:

Size (inches)	Working pressure (bar)	
	-20 °C to 120 °C	120 °C to 225 °C
1/4 to 3/4	25	16
1 to 2	16	10
2 to 4	10	6



## Series 8000 range

<b>Brass Plug Male Thread (Parallel)</b>	<b>Female Elbow Female x Female Thread</b>	<b>Male x Female Elbow Male x Female Thread</b>	<b>Tee - Equal Female Thread All Ends</b>
			
<b>8595</b> From: 1/4" To: 2"	<b>8090</b> From: 1/4" To: 3/4"	<b>8092</b> From: 3/8" To: 1"	<b>8130</b> From: 1/4" To: 1"
<b>Reduced Bush Male x Female Thread</b>	<b>Straight Coupler Female x Female Thread</b>	<b>Hexagon Nipple Male x Male Thread</b>	<b>Flanged Backnut</b>
			
<b>8241</b> From: 3/8 x 1/4" To: 2 x 1 1/2"	<b>8270</b> From: 1/4" To: 2"	<b>8280</b> From: 1/8" To: 2"	<b>8310</b> From: 1/2" To: 2"
<b>Barrel Nipple Male Thread x Length (mm)</b>	<b>Running Nipple Male (Parallel)</b>	<b>Blank Cap Female Thread</b>	
			
<b>8530</b> From: 3/8" x 40 mm To: 2" x 100 mm	<b>8531</b> From: 1/4" To: 3/4"	<b>8599</b> From: 1/4" To: 2 1/2"	

\*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: [technical@ibpgroup.com](mailto:technical@ibpgroup.com).

**Conex Universal Limited:** Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.  
 Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: [sales@ibpgroup.com](mailto:sales@ibpgroup.com) | Website: [www.conexbanninger.com](http://www.conexbanninger.com)

This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries.