Conex Bänninger



A range of Compression fittings.

Features and Benefits:

- Suitable for use with copper tube EN 1057, carbon steel tube EN 10305 and stainless steel tube EN 10312.
- Suitable for connecting polybutylene pipes (PB) and PEX to EN15876-2, EN15875-2 and BS57291:2 and 3.
- Fittings compatible with PB and PEX pipes are available in dimensions 10,15,18,22 and 28mm.
- Installation with PB and PEX pipe requires liners recommended by the tube manufacturer or supplied by IBP.

- Used in plumbing, heating, cooling, compressed air, solar and gas applications.
- Manufactured in duplex brass and available in DZR brass.
- Manufactures in accordance with EN 1252-2 and threaded connection to EN 1254-4.
- Flame-free installation.
- PTFE tape is not required for installation.
- Adapters available for Imperial tube sizes.









A range of Conex Compression fittings



*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM. Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: sales@ibpgroup.com | Website: www.conexbanninger.com

This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries

IK/02/20

CB/U