CLEAN BUSINESS:

OPENING AIDS


The new opening aids on our bags ensure quick and easy opening.

The first 'rip' aid on the top allows for easy and clean opening. You will now also find the exact water quantity information on the bags for perfect mixing.

The second indicator in the middle of the bag is intended for opening with the ripper or for cutting.

Simply smart: the new top of our bags.





QUICK-CHECK:

Thanks to the QR code, you can access all the important product information on your screen at the touch of a button and in the right language.

This is how it works: Simply focus on the QR code "Select your language" with the smartphone camera and tap on the link. This leads you to the landing page with more country specific product information.



Easy to understand: scan and select your language.



Uzin Utz UK Ltd.

Unit 2, Mitchell Court Central Park, Rugby Warwickshire, CV23 0UY United Kingdom

T +44 1788 530080 F +44 1788 536508 uzin.uk@uzin-utz.com www.uzin.co.uk





THE UZIN PRODUCTS SHINE IN NEW DESIGN.

As you can see, there is a lot that is new at UZIN in 2022, because we keep our promise: UZIN offers more.

After redesigning the packaging for all UZIN UTZ brands, all UZIN products now shine in UZIN blue.

The information on the packaging has also changed, with new relevant information added and some superfluous information removed. With all the changes, one thing remains the same: the unique quality of our products.

021/13.000/ms/



OVERVIEW OF THE UZIN PICTOGRAMS











3 - 7 d*





INSULATING AND INSTALLATION UNDERLAYS

l w 25 2,0 → 90 mm mm kg



2,8 kg/m²

6 – 8 min

\$ h | 100 60 4 | mm mm mm

3 - 7 d*

80 – 150 g/m²

Nylon
B2
200 – 600 g/m²/Layer

Can be applied with nylo fibre roller or TKB-B2 notched trowel

SMART PACKAGING.

STILL UNBEATABLE:

THE NEW UZIN





10 min













B2

23/80 50 – 280 g/m² 23/TL 350 – 450 g/m²

mixing ratio
weight
1
:
7.8

Working time

SWITCHTEC® ADHESIVE TECHNOLOGY











switchTec® solutions now appear in blue.



THE OUANTITY OF WATER

is clearly depicted **on the**

20 KG

TECHNICAL INFORMATION

is quickly recognisable through

understandable **pictograms**

top of the bags in large print.

and consumption information for standard application

LIZIN LITZ

GENERAL





before applying of the second second



and hotel locations

coverage ~ 13 m²

B11/16 kg

UZIN 1: t 5C 980

Coverage per unit by using the displayed notch















for more detailed information about the product in many languages

CREDENTIALS

THE UZIN BLUE IS

APPLIED ACROSS

PRODUCT RANGE

THE WHOLE

and environmental **certificates** of the product


in large print on the front

of **UZIN UTZ** on all products


















150 mm ± 5 mm

B_{fl}-s1





max 80 mm


min 25 mm











ml = = = A\$ 52 250 ml/300 ml

CM 50 g/ 10 min

SMOOTHING COMPOUNDS







Suitable for forklift traffic at minimum layer thickness of

max 30 min

Building materials class acc. to DIN 4102 / reaction to fire acc to DIN EN 13501-1