

# Remur 25 / 35 mm

## Installing PVC trims

### MAIN APPLICATION FIELD:

Metal-reinforced special system for the dimensionally stable installation of flexible PVC capping & suchlike on smooth substrates. Remur allows quick and clean working without solvents. For interior areas only.

### PRODUCT BENEFITS/FEATURES:

- ▶ Flexible PVC capping with smooth backing (such as Quantum)
- ▶ PVC cove formers with smooth backing (except: stair nosing profiles)
- ▶ For common building applications in interior areas
- ▶ Request application consulting for other materials

Note: Obtain technical advice for additional combinations of floor covering and skirtings

### SUITABLE ON / FOR:

- ▶ Masonry
- ▶ Smooth plaster
- ▶ Painted surfaces
- ▶ Metal • Plastics
- ▶ Wood • Concrete
- ▶ Ceramics
- ▶ Gypsum (primed)
- ▶ Smoothing compound



### PRODUCT BENEFITS/FEATURES:

Metal-reinforced special tape for the dimensionally stable installation of flexible PVC and CV skirting on smooth substrates. Remur allows quick and clean working without solvents. For interior areas only.

- ▶ dimensionally stable
- ▶ avoids use of contact adhesive
- ▶ no prior fitting and priming
- ▶ 3 – 5 times faster
- ▶ solvent-free
- ▶ will not dry out or become brittle

### TECHNICAL DATA:

Packaging	carton
Shelf life	min. 24 months
Colour	transparent
Open time	none
Setting time / cure time	none
Ready for foot traffic	immediately after installation
Roll width	25 / 35 mm
Roll length	50 m
Minimum application temperature	15 ° C at ground level
Loadable	immediately after installation
Joint sealing	immediately after installation

\*At 20 °C and 65% relative humidity.



## SUBSTRATE PREPARATION:

- ▶ The substrate must be permanently dry, hard, load-bearing, level, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- ▶ Acclimatisation: Allow skirting and Remur to acclimatise over 24 hours at min. 18 °C in the room.
- ▶ Wallpaper must be cut/removed for the area covered by the skirting.
- ▶ Dust binding: Bind dust with a solvent-free primer (e. g. UZIN PE 260).
- ▶ PVC cove formers, PVC soft skirting as well as the backing of floor coverings must be free from dust, dirt and grease. Clean well and rub dry with a clean rag.

## IMPORTANT NOTES:

### Storage:

Store on protected cut area, in a dry, cool area without exposure to direct sunlight.

Subsequent removal: Adhesive residues can remain on the substrate when subsequently removing floor covering bonded with Remur. Please obtain technical advice for removal.

### UZIN grants a 5-year warranty for all properties claimed in the installation instructions.

- ▶ Follow the generally acknowledged rules of the trade and of technology for the installation of floor covering of the respective applicable standards (EN, DIN, VOB, OE, SIA) In all cases, some adhesion tests must be carried out on-site before carrying out the installation.

The warranty becomes void if:

- ▶ unusual influences, and in particular those of a chemical or mechanical nature, affect the product.
- ▶ used or processed differently than stated in the installation instructions.
- ▶ Remur 95 is used on staircases.
- ▶ moisture affects Remur 95.
- ▶ the floor covering was installed under pulling forces or tension.
- ▶ installation was performed below 18 °C (on the wall).
- ▶ Remur 95 is used in areas with increased humidity or thermal exposures (e. g. conservatories).

## SEALS OF QUALITY & ECOLABELS:

- ▶ EMICODE EC 1 PLUS / Very low emission

## COMPOSITION:

Metal-reinforced special film carrier, acrylic copolymers, wetting and defoaming agents, paper.

## PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

The product does not require any special labour protection measures. For reasons of working hygiene, we recommend avoiding eating, drinking and smoking during processing of

this product. Store out of the reach of children. For more information refer to [www.uzin.com](http://www.uzin.com) or contact +49 731 4097-0.

## DISPOSAL:

Empty shells and the cardboard packaging can be recycled. Material remnants can be disposed of as household waste.