

STAFFLINE DOOR

DIMENSIONS (mm)

H: 1800 - 2400

W: 700 - 1200

D: 115

WEIGHT (kg)

Bullet resistant: 140

Manual attack: 100

RESISTANCE

Bullet Resistance: BS 5051 G2 and S86

Optional Bullet Resistance to client specification

CONSTRUCTION

Door leaf and frame are fabricated from timber and composite materials to match the required bullet and/or manual attack resistance levels.

The door leaf is hung on heavy duty hinges that include dog bolts and fitted with a T section to protect the leading edge of the door.

TIMBER SECURITY DOORS

STAFFLINE DOOR

Safetell's internal timber security doors provide bullet and manual attack resistance. We can provide standard or bespoke solutions to match project requirement. Typical applications include cash offices, banks, retail, rail, airports, corporate buildings, government offices and internal secure areas.

MAIN FEATURES

- Manual attack and/or bullet resistant
- Standard certified doors have a single leaf and frame
- Secured by a Chubb 3R35 keylock
- Standard opening is outwards towards the attack side
- Timber standard finish in American White Oak. Other optional finishes are available on request
- Standard heavy duty door closer for commercial use

OPTIONAL

- Uncertified inward opening doors are available but not recommended
- Kick plates, push plates and D handles are available
- Eye viewer, single or multiple vision panels with or without vertical venetian reflector strips to obscure public view
- Bespoke door finishes are available on request
- Bespoke automated door opening, access control and remote locking integration solutions are available to suit project requirements
- Uncertified double leaf Staffline doors and frame are available subject to limitations in attack resistance
- CEIA metal detector



SERVICE &
MAINTENANCE
AVAILABLE

+44 (0) 1322 223 233

sales@safetell.co.uk safetell.co.uk