

TECHNICAL DATA SHEET – HPC 11 NU-GUARD WB MASONRY

DESCRIPTION:

Nu-Guard WB Masonry Coating is a water based exterior material giving maximum durability, weather resistance, and breathability with excellent opacity and good adhesion to general masonry surfaces.

ADVANTAGES:

Will provide in excess of 10 years protection on properly prepared sound substrates.

USES:

For external use on dry, smooth or textured, cement rendering, plaster, brickwork, asbestos cement, pebble dash and other masonry surfaces.

COLOUR RANGE:

Available in selected BS 4800 colour range.
Consult Hydron Technical Services.

PACK SIZE:

Single component product, supplied in 10, 15 litres & 1000 Litre IBCs.

VOLUME SOLIDS:

40%

COVERAGE RATE:

10m² per litre dependant upon porosity and texture of the substrate.

DRYING TIME:

Usually touch dry and recoatable after 4-6 hours at 20°C

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

Two coats by brush, roller or spray.

EQUIPMENT CARE:

All equipment should be cleaned with water

STORAGE:

Store away from direct sunlight and sources of heat.
Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS