

TECHNICAL DATA SHEET – HPC 10 NU-GUARD WB CONCRETE SEALER

DESCRIPTION:

Nu-Guard WB Concrete Sealer is a modified Vinyl Acetate, non-flammable and non-toxic sealer. It is formulated primarily for use on concrete and brickwork.

ADVANTAGES:

Single pack ready for immediate use. Prevents the darkening of light substrates prior to the application of Nu-Guard AG.

USES:

Brick and Concrete
First coat of the Nu-Guard AG

COLOUR RANGE:

Clear

PACK SIZE:

Single component product, supplied in 5, 25 litres & 1000 Litre IBCs.

COVERAGE RATE:

This is dependant upon the surface porosity. Average coverage rate is in the region of 6 – 10 m² per litre.

DRYING TIME:

Touch dry.....1 Hour @ 20°C.
Hard dry.....4 - 6 Hours.
Overcoat.....24 hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surfaces then should be washed off to provide a clean neutral surface and allowed to dry overnight.

APPLICATION:

One coat by brush, roller or spray.

EQUIPMENT CARE:

All equipment should be cleaned with water

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS