

TECHNICAL DATA SHEET – HPC 21 NU-GUARD SP TACK PRIMER

DESCRIPTION:

Nu-Guard SP Tack Primer is a smooth, non-toxic, water-soluble primer, to help with adhesion as well as being used as part of the Nu-Guard Mural Paint System.

ADVANTAGES:

Nu-Guard SP Tack Primer provides excellent adhesion to porous and previously painted surfaces prior to the application of various topcoats.

USES:

Adhesion promoter for glazed and previously painted surfaces as well as porous surfaces

COLOUR RANGE:

White

PACK SIZE:

Single component product, supplied in 5 & 10 litre cans.

COVERAGE RATE:

6 - 14 m² per litre

VOLUME SOLIDS:

40%

DRYING TIME:

Touch: 2 Hours
Overcoat: 4 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS