

Von Duprin - 98/9957 - Surface Mounted Three Point Latching Device Protection at Flood Defence Doors



PAS 1188-1:2009. Flood Protection Products. Specification. Part 1: Building Aperture Products

Effective July 2014 and in association with our colleagues at Loddon Door Services Ltd, Relcross is pleased to announce that this product is certified for use on outward opening flood defence doors:

Certificate:

PAS 1188-1:2009. Flood protection products. Specification. Part 1: Building Aperture Products

PAS 1188-1 applies to flood protection products used in the temporary sealing of building apertures and entrances to properties, in the event of static flood water rising up to a level between 600 mm and 900 mm above ground level.

98/9957 - Surface Mounted Three Point Latching Device

Characteristics

Our flagship range of architectural grade escape devices includes the [98 Series](#) with its smooth mechanism case and the established [99 Series](#) with its familiar grooved design. The two styles are mechanically and dimensionally identical and provide a wide selection of additional features to suit many applications.

The Quiet One®

A fluid dampener decelerates the touch bar on its return stroke and eliminates most noise associated with exit device operations.
Furnished on all 98/99 Series Exit Devices

UK Fire Certification in accordance with EN 1634-1:2000 (timber)
WFRC No. C132276 120mins BS EN 1125:1997

CE Certified.



Related Tags: [Von Duprin Exit Hardware](#) | [Door Hardware](#)
