

1461.US28 Door Closer

Standard Duty Closer w. Backcheck, Plastic Cover - Adjustable Power Size 2-5.

Pull Side of Door, Push Side of Door or Push Side Transom. Silver w. Matching Arm

Best suited to standard duty situations on perimeter and internal doors where a high level of traffic is anticipated.

The 1461 is adjustable through spring sizes 2-5 and mounts to the most common commercial footprint. The 1460 Series also features a complete line of regular and extra duty arms and LCN's peel-n-stick installation templates.

The LCN 1460 series manages to cram in amazingly high levels of strength and accurate adjustability. 'Super Stock' closers will control internal doors up to 1524mm wide and external (perimeter) doors to 1220mm.

CE Certification applies to all applications.

Suits doors <102 kilos



- Hinge (Pull Side) Mounting
 - Top Jamb (Push Side) Mounting
 - Stop Face (Push Side) Mounting
 - Non-handed for right and left swinging doors
 - Adjustable hydraulic backcheck cushions opening swing prior to 90 degrees
 - Separate regulation of general closing speed and latching speed
 - Joints in arm and shoe adapt to uneven trim
 - Reversible shoe to boost latching power on double lever arms
 - All Weather Fluid - Performs without variation:
 - Manual Closers - between -35° to +49°C
 - Electronic HO Closers & Automatic Operators - between +2° to +49°C
- At approx. +75°C the fluid will begin to leak from the mechanism. The flash point is approx. 110°C

UK Fire Certification in accordance with BS EN 1634-1:2014 (timber) - 120 mins
WFRC No. 142058

EN 1154: 1996 + A1: 2002/AC:2006



LCN 1000 Series Door Closers

Designed for maximum versatility, the 1460 Series, available with multiple cover options, can be used for both commercial and institutional applications. This fully universal closer (1461) offers a wide variety of options and new fast & accurate installation.