

VESDA SENSEPOINT XCL

VESDA Sensepoint XCL – Large Bore is a gas detection solution that utilizes the ASD pipe network to deliver superior gas detection via multiple hole (multi-point) sampling.

The VESDA Sensepoint XCL – Large Bore portfolio has a range of gas sensors that addresses a wide range of applications and through its Bluetooth interface can be paired with a smart device for commissioning and maintenance. The smart device application (Sensepoint App) provides quick access to detector diagnostic

The combined solution provides reliable detection of gases for occupant protection and process monitoring whilst simultaneously ensuring protection against fire threats.

HOW IT WORKS

VESDA Sensepoint XCL – Large Bore is designed to be easily incorporated to existing or new ASD pipe networks without major construction or electrical cabling / conduit and utilizes the flow in the pipe for the continuous delivery of air samples to the gas sensor for analysis.

It is capable of remote sampling which means the detector can be placed outside the detection zone at a convenient location for maintenance & service where free business operation, restricted access and safety of personnel is important. Air drawn to the detector can be conditioned to remove contaminants which ensures the detector maintains reliable long-term performance in a wide range of environments.

A single VESDA Sensepoint XCL – Large Bore detector delivers multi-point gas sampling capability giving it the advantage of providing larger coverage, increased design flexibility and reliable detection in high airflow areas compared to fixed point gas detectors.

APPLICATIONS INCLUDE

- Energy storage systems (batteries)
- Utility / service tunnels
- Heating plant rooms
- Manufacturing / Petroleum industries
- Parking garages / Loading bays
- Power generation
- Refrigerated storage
- Waste handling facilities
- Agriculture
- Water treatment / sewerage plants
- Health care / Hospitals
- Food / beverage industry

FLEXIBLE OUTPUT OPTIONS

VESDA Sensepoint XCL – Large Bore is available with either 4-20 mA analog or Modbus RTU output, both versions being equipped with relays. The result is a flexible solution that can be integrated to BMS, fire alarm panels, PLCs, HVAC, etc.



FEATURES AND BENEFITS

- Wide range of gases to support most application needs:
 - Carbon Monoxide (ppm)
 - Flammable gases (% LEL)
 - Oxygen (% v/v)
 - Carbon Dioxide (% v/v, ppm)
- Multi-point gas sampling:
 - Greater coverage area
 - Increased design flexibility
 - Reliable detection in high airflows
- Integral alarm status LEDs
- Field replaceable gas sensor cartridges
- Smart device application (Sensepoint App) enables faster detector commissioning, maintenance and service
- Bluetooth Wireless Interface (compatible smart device iOS10 / Android 4.3 or above)
- Multiple output options (configurable relays, 4-20 mA or Modbus RTU)
- Aspirated gas sampling technology
 - Capable of remote sampling – no need to enter detection zone
 - Centralized maintenance & service
 - Saves time & money
 - Detector protected against the harshness of the environment – reliable long term performance

INSTALLATION

The VESDA Sensepoint XCL – Large Bore detector is designed to be inserted in-line to the pipe network and is supplied with 60° elbows in the box:



VESDA SENSEPOINT XCL Technical Specification

SPECIFICATION	
Supply Voltage	24 VDC nominal 11 to 32V DC (Analog 4-20 mA) 9 to 32V DC (Modbus) 24V AC 50/60Hz Nominal (20 to 27 VAC) 20 to 27V AC (all versions)
Maximum Power Consumption	4-20 mA: < 1.2 W (toxic), < 1.7W (CAT, CO2) Modbus: < 0.7 W (toxic), < 1.2W (CAT, CO2) Relay: additional 0.6W total Maximum Inrush Current: 850 mA
Dimensions (WxHxD)	113 x 113 x 59 mm (4.4 x 4.4 x 2.3 in)
Weight	500 g (1.1 lb)
Casing Material	Polycarbonate
Ingress Protection Rating	IP65, Type 4 (NEMA 250)
Operating Conditions	
Operating Temperature	-20 °C to +50 °C (-4 °F to +122 °F)
Storage Temperature	0 °C to +30 °C (+32 °F to +86 °F)
Humidity:	0 to 99% (non-condensing) CAT versions: 10 to 90% RH. Operating the detector outside this range may result in increased drift and a reduction in detector accuracy.
Atmospheric pressure:	90 to 110 kPa
Wire/Terminal size	Connects to ASD pipe networks 25mm (0.98"), 27mm (1.06") OD
Output	Analog: 0 to 22 mA Digital: Modbus RTU 2 Relays (24V DC / 240V AC, 5A)

LISTINGS / APPROVALS *	
Electrical safety	EN/UL/IEC 61010-1 CSA-C22.2 No. 61010-1-12
CE - EMC	EN 50270
RADIO	RED, FCC, BT SIG
OTHERS	UL2075 (CO and CH4), AS 1668.2

***These Listings/Approvals are owned by Xtralis, a Honeywell company. They are for the products covered in this document.**

VESDA SENSEPOINT XCL ORDERING INFORMATION

The VESDA Sensepoint XCL – Large Bore detector comes complete with the main detector unit (pre-installed with sensor cartridge), flow cap and elbows.

PART NUMBERS		
DESCRIPTION	ORDER CODE 4-20MA ANALOGUE, RELAY	ORDER CODE MODBUS RTU, RELAY
Flammable (CAT) 20-100% LEL	XCL-LB-CH4-RA	XCL-LB-CH4-RM
Oxygen 25.0% v/v (Fixed)	XCL-LB-O2-RA	XCL-LB-O2-RM
Carbon Monoxide 50 to 1000 ppm	XCL-LB-CO-RA	XCL-LB-CO-RM
Carbon Dioxide 1000 to 5000 ppm	XCL-LB-CO2PP-RA	XCL-LB-CO2PP-RM
Carbon Dioxide 1.0 to 5.0% v/v	XCL-LB-CO2VV-RA	XCL-LB-CO2VV-RM
SPARE PARTS	ORDER CODE	
Replacement Gas Sensor		
Flammable (CAT)	XCL-SC-CH4	
Oxygen	XCL-SC-O2	
Carbon Monoxide	XCL-XRL-SC-CO	
Carbon Dioxide (ppm)	XCL-SC-CO2PP	
Carbon Dioxide (% v/v)	XCL-SC-CO2VV	
Flow Cap	XCL-LB-CAP	
60° Elbows - pack of 4	XCL-LB-ELB	
Cable Glands - Pack of 10	XCL-M20-CG	
Filter CAT, NH3, CO2 – pack of 10	XCL-LB-FLT-1	
Filter CO, O2, H2S, NO2, H2 – pack of 10	XCL-LB-FLT-2	
Sensor Cover CAT, NH3, CO2	XCL-LB-COV-1	
Sensor Cover CO, O2, H2S, NO2, H2	XCL-LB-COV-2	

All technical data is correct at the time of publication and is subject to changes without notice. All trademarks acknowledged.
Installation information: In order to ensure full functionality, refer to the installation instructions as supplied.