

Med0 SedumPlug

Product Data Sheet



Med0

SedumPlug

General Information

Radmat SedumPlug are low maintenance, drought resistant, ready to install sedum plug plants grown in the UK to suit the environment climate. The range of species provides the opportunity to select plant mixes to achieve a variety of objectives including: extending the flowering season, managing degrees of shade or exposure, orientation and/or indigenous planting requirements.

Installation instructions

Install by hand into a suitably prepared and irrigated Radmat growing medium at the specified rate per m². Insert so root ball is below the finished growing medium surface. Once installed irrigate for the prescribed period based on season.

Fire performance

Approved Document B *Fire Safety* points to the DCLG document *Fire Performance of Green Roofs and Walls* for best practice guidance in achieving Regulation 7(2) fire compliance with a green roof. DCLG *Fire Performance of Green Roofs and Walls* states that the compliance requirements for achieving Broof(t4) are a growing medium layer of a minimum 80mm and an organic content of not more than 50% (<https://www.gov.uk/government/publications/fire-performance-of-green-roofs-and-walls>). In addition, The Green Roof Organisation (GRO) Code of Best Practice, also recommends fire breaks consisting of 50mm deep 20/40mm rounded ballast are used at perimeters and penetrations. Gravel fire/vegetation breaks should be 500mm wide where they abut habitable space but can be reduced to 300mm in some circumstances. Key to ensuring ongoing fire performance of a green roof, and the plant performance, is maintenance as some plants will die back, others will shed leaves naturally during their lifecycle and invasive species will try to take hold. These factors all create additional organic matter that could pose a fire spread risk on the roof therefore unwanted organic matter should be removed as part of the maintenance program.

Delivery

Delivery Form

Trays of plugs

Storage and transport

Delivered in a box or on a pallet. Store flat.

For further information on Radmat products and services please call **01858 410372**, email tech enquiries@radmat.com or visit our website www.radmat.com



Radmat Building Products Ltd Holland House, Valley Way, Rockingham Road, Market Harborough, Leicestershire, LE16 7PS T : 01858 410 372 E : tech enquiries@radmat.com

Med0

SedumPlug

Product Dimensions

Subject	Performance	Unit
Volume	65	Cc
Depth	62	mm
Dimensions of top face of tapered cell	35 x 47	mm

Species available

Blue Pearl	Sedum Ewersii	Sedum Relfexum Blue Spruce	Sedum Spurius Red Carpet
Cherry Tart	Sedum Faro Form	Sedum Rose Carpet	Sedum Spurius Roseum
Dazzleberry	Sedum Glaucophyllum	Sedum Roseum	Sedum Spurius Rosy Glow
Lime Zinger	Sedum Gold Digger	Sedum Rupestre	Sedum Spurius Summer Glory
Sedum Acre Golden Carpet	Sedum Hispanicum	Sedum Russian Stonecrop	Sedum Spurius Tricolour
Sedum Acre Oktoberfest	Sedum Hispanicum Blue Carpet	Sedum Sarmentosum	Sedum Spurius Voodoo
Sedum Album	Sedum Immergrunchen	Sedum Selskianum Goldilocks	Sedum Stoloniferum
Sedum Album Superbum	Sedum Kamtschaticum	Sedum Sexangulare	Sedum Sunset Cloud
Sedum Angelina	Sedum Kamtschaticum Variegatum	Sedum Sieboldii	Sempervivum Tectorum
Sedum Arachnoideum	Sedum Lemon Drop	Sedum Spurius	Sedum Vera Jameson
Sedum Spurius Bronze Carpet	Sedum Lidakense	Sedum Spurius Dragon's Blood	Sedum Weihenstephaner Gold
Sedum Cauticola Stonecrop	Sedum Midd Diffusum	Sedum Spurius Elizabeth	Sempervivum Blue Boy
Sedum Spurius Coccineum	Sedum Murale	Sedum Spurius Fool's Gold	Sempervivum Arachnoideum Cobweb
Sedum Coral Carpet	Sedum Pachyclados (Silver Gem)	Sedum Spurius Fuldaglut	Sempervivum Green Wheel
Sedum Czar's Gold	Sedum Pulchellum	Sedum Spurius John Creech	Sempervivum Purple Beauty
Sedum Ellacombianum	Sedum Reflexum Iceberg	Sedum Spurius Purple Carpet	Talinum Calycinum

This information given in good faith and is based on the latest knowledge available to Radmat Building products Ltd. Whilst every effort has been made to ensure that the contents of the publication are current while going to press, customers are advised that products, techniques and codes of practice are under constant review and liable to change without notice.

For further information on Radmat products and services please call **01858 410372**, email techenquiries@radmat.com or visit our website www.radmat.com **JAN 2021**