

Sovereign Timber Treatment



Sovereign Timber Treatment contains a resin, pigments in a low odour solvent. The product also contains biocides for the protection of the coating.



Product Code

Straw: 30806153
Red Cedar: 30806158
Green: 30806513
Brown: 30806478

Description

Sovereign Timber Treatment contains a resin, pigments in a low odour solvent. The product also contains biocides for the protection of the coating. Sovereign Timber Treatment can be used for pretreating all types of soft or hard wood.

Sovereign Timber Treatments are designed to give a fast drying quality treatment with a UV stable colour that can be subsequently painted or stained.

Form Supplied: Solvent based, ready to use

Pack Sizes: 5 Litres

Colour Range: Straw, Red Cedar, Green and Brown*

Contains: Biocide for the protection of the coating

Properties

Provides protection from initial manufacture to installation. Once installed a full weatherproof timber coating should be applied e.g. Sovereign SX70 Woodstain or primer and paint.

*Brown Timber Treatment contains bitumen so should not be overcoated.

Preparation

Timber should be dry, clean and free from sawdust

General

Suitable for all types of soft and hardwood applications such as: Windows, doors/frames, skirting and rails, floorboards, roofing timbers, soffits, sheds, fencing and garden furniture.

Sovereign Timber Treatment

Technical 318
Data Sheet 318

GUIDELINES FOR USE IN DIP TANKS

- Empty and clean out the tank thoroughly on a regular basis (at least every 6 months).
- 2. Always cover when not in use.
- 3. Stir gently before use.
- 4. Use as much 'old' material up as possible before topping up the tank.
- 5. Do not dip damp wood.
- 6. The wood to be dipped must be free from sawdust, wood shavings, or other extraneous materials.
- 7. Use a grate raised above the bottom of the tank so that any debris, etc. is deposited below.
- 8. Ensure that the tank is not contaminated with, for example, solvent washings from paint brushes, etc. as this can also lead to settlement/separation.
- 9. Do not blend with other products, as they could be incompatible.

A gel forming in the tank and/or loss of colour indicates the tank is excessively contaminated with sawdust and requires empting, cleaning and new treatment using.

GENERAL MAINTENANCE

Timber coated with Sovereign Timber Treatment should have a further protective coating applied as soon after installation as possible. Traditional wood coatings such as paints, stains and varnishes are suitable.

LIMITATIONS

Brown Timber Treatment should not be over coated in paint due to its bitumen content. Once weathered it can be primed with Sovereign Stain Blocking Primer and then painted with e.g. gloss.

Normally Brown Timber Treatment is used on rough sawn timber such as sheds and fences and is reapplied as and when required.

CLEAN UP

Use white spirit or brush cleaner on tools and brushes

DRYING TIME

Typically touch dry in 3 – 4 hours and hard dry overnight under ideal conditions.

COVERAGE

Approximately

Dip: 3 minutes minimum

Spray: $6 - 7 \text{ m}^2/\text{litre}$ Brush: $4 - 5 \text{ m}^2/\text{litre}$

Storage: Between 5°C - 30°C. **Shelf Life:** 12 months unopened.

HEALTH & SAFETY

- Keep out of reach of children.
- ! Keep away from food, drink and animal feeding stuff. When using do not eat, drink or smoke.
- Avoid contact with skin and eyes.



Health & safety information available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice.

Please ensure you have the latest updated information.



Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

