



Neeva

The smooth laminated finish of the Neeva products combines Class A sound absorption and aesthetics.

Key Features

- Excellent sound absorption: up to 1.00 α_w
- High light reflectance: 82%
- Fibre glass fleece on the back to add strength
- Ideal for open spaces, call centres and libraries



Edge Detail	Board																																																													
																																																														
Thickness (mm)	15 / 18																																																													
Modules (mm)	600 x 600 x 15..... 2691M 1200 x 1200 x 18 2406M																																																													
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 CR / TLS Prelude 24 Sixty ² XL ² / TLS																																																													
Colour	Global White																																																													
Sustainability	 20		 A	 EN 13964 / E1																																																										
Acoustics	 EN ISO 354 & EN ISO 11654  EN ISO 10848-2 & EN ISO 717-1  EN ISO 140-3 & EN ISO 717-1 <table><thead><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>R_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th colspan="5">Hz α_p</th></tr><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>Board (15mm)</td><td>1.00</td><td>–</td><td>7 dB</td><td>A</td><td>0.95</td><td>0.40</td><td>0.90</td><td>1.00</td><td>0.90</td><td>1.00</td><td>1.00</td></tr><tr><td>Board (18mm)</td><td>1.00</td><td>24 dB</td><td>–</td><td>A</td><td>0.95</td><td>0.40</td><td>0.85</td><td>1.00</td><td>0.90</td><td>1.00</td><td>0.95</td></tr></tbody></table>														α_w	D _{nfw}	R _w	Class	NRC	125	250	Hz α_p													500	1000	2000	4000	Board (15mm)	1.00	–	7 dB	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00	Board (18mm)	1.00	24 dB	–	A	0.95	0.40	0.85	1.00	0.90	1.00	0.95
	α_w	D _{nfw}	R _w	Class	NRC	125	250	Hz α_p																																																						
								500	1000	2000	4000																																																			
Board (15mm)	1.00	–	7 dB	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00																																																			
Board (18mm)	1.00	24 dB	–	A	0.95	0.40	0.85	1.00	0.90	1.00	0.95																																																			
Fire Reaction	 EEA Euroclass A1 EN 13501-1																																																													
Performances & Features	 82%	 95% RH		 30 Year System Guarantee																																																										
	 1.2 Kg/m ² Board (15mm) 1.3 Kg/m ² Board (18mm)			 BIM READY																																																										
Custom Options	 Dimensions																																																													

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email info@zentia.com