




Fission FT

The non-directional Fine Fissured surface provides a solution for providing Class C sound absorption.

Key Features

- Good sound absorption: 0.60(H) α_w
- Ideal for storage facilities, corridor and warehouses



Edge Detail	Board		Tegular		MicroLook									
Thickness (mm)	15		15		15									
Modules (mm)	600 x 600 9121M 1200 x 600 9120M		600 x 600 9122M		600 x 600 9202M									
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 15 TL / XL ² Interlude HRC XL ²									
Colour	Global White / Black (available for 9121M only)													
Sustainability	 51% A+ EN 13964 / E1													
Acoustics	 EN ISO 354 & EN ISO 11654		 EN ISO 21040-9 & EN ISO 717-1											
		α_w	D _{nfw}	Class	NRC	125	250	Hz α_p			500	1000	2000	4000
	Board, Tegular, MicroLook	0.60(H)	34 dB	C	0.65	0.40	0.40	0.55	0.80	0.85	0.85			
	Board (Black)	0.60(H)	34 dB	C	0.65	0.35	0.40	0.55	0.75	0.80	0.85			
Fire Reaction	 Euroclass A2-s1, d0 EN 13501-1													
Performances & Features	 85%		 95% RH		 3.4 Kg/m ²				 30 Year System Guarantee		 BIM READY			
	 Dimensions													

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 076.1.10.22