




Aruba dB

The higher attenuation performance of Aruba dB offers a perfect solution for improving the privacy between adjacent spaces. Whilst the class-leading whiteness helps to create spaces that are brighter and better, and which offer a greater sense of well-being for your customers.

Key Features

- Excellent sound attenuation (39 dB sound reduction) to eliminate the need for sound barriers in close office applications
- Enhanced acoustical absorption performance of 0.60 α_w for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Easy to handle and re-engineered for a better, easier fit
- Ideal for individual offices and board rooms



Edge Detail	Board		Tegular24		Tegular15																																					
Thickness (mm)	19		19		19																																					
Modules (mm)	600 x 600 5477M		600 x 600 5479M		600 x 600 5481M																																					
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 15 TL / TLS Interlude HRC XL ² Silhouette XL ²																																					
Colour	Global White																																									
Sustainability	<div><div> 37</div><div></div><div> A+</div><div> EN 13964 / E1</div><div></div></div>																																									
Acoustics	<div><div> EN ISO 354 & EN ISO 11654</div><div> EN ISO 10848-2 & EN ISO 717-1</div><div> EN ISO 140-3 & EN ISO 717-1</div><div><table><tr><th colspan="12">Hz α_p</th></tr><tr><th>α_w</th><th>D_{nfw}</th><th>R_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th><th></th></tr><tr><td>Board, Tegular24, Tegular15</td><td>0.60</td><td>39 dB</td><td>20 dB</td><td>C</td><td>0.55</td><td>0.35</td><td>0.40</td><td>0.60</td><td>0.65</td><td>0.75</td><td>0.65</td></tr></table></div></div>						Hz α_p												α_w	D _{nfw}	R _w	Class	NRC	125	250	500	1000	2000	4000		Board, Tegular24, Tegular15	0.60	39 dB	20 dB	C	0.55	0.35	0.40	0.60	0.65	0.75	0.65
Hz α_p																																										
α_w	D _{nfw}	R _w	Class	NRC	125	250	500	1000	2000	4000																																
Board, Tegular24, Tegular15	0.60	39 dB	20 dB	C	0.55	0.35	0.40	0.60	0.65	0.75	0.65																															
Fire Reaction	<div><div></div><div>Euroclass A2-s1, d0 EN 13501-1</div></div>																																									
Performances & Features	<div><div> 85%</div><div> 95% RH</div><div></div><div></div><div><div>30 Year System Guarantee</div><div>BIM READY</div></div><div> 7.9 Kg/m²</div><div></div><div></div><div><div>Lifetime Guarantee</div></div></div>																																									

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 135.1.05.23