




## Aruba Max

Aruba Max with its microperforated, finely sanded surface, offers improved levels of sound absorption and sound attenuation, making it a great choice for classrooms and other areas requiring Class C sound absorption.

## Key Features

- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Balanced acoustical absorption performance of 0.65  $\alpha_w$  and sound attenuation of 35dB
- Fully painted, reinforced edges for a more robust tile and greater durability
- Easy to handle and re-engineered for a better, easier fit
- Ideal for classroom and general teaching conditions



Edge Detail	Board		Tegular24		Tegular15																																		
Thickness (mm)	18		18		18																																		
Modules (mm)	600 x 600 ..... 5471M 1200 x 600 ..... 5472M		600 x 600 ..... 5473M		600 x 600 ..... 5475M																																		
Suspension Systems	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS		Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS		Prelude 15 TL/ XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette XL <sup>2</sup>																																		
Colour	Global White																																						
Sustainability	<div><div> 46</div><div></div><div> A</div><div> EN 13964 / E1</div><div></div></div>																																						
Acoustics	<div><div> EN ISO 354 &amp; EN ISO 11654</div><div> EN ISO 10848-2 &amp; EN ISO 717-1</div><div> EN ISO 140-3 &amp; EN ISO 717-1</div><div><table><thead><tr><th colspan="10">Hz <math>\alpha_p</math></th></tr><tr><th><math>\alpha_w</math></th><th>D<sub>nfw</sub></th><th>R<sub>w</sub></th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>Board, Tegular24, Tegular15</td><td>0.65</td><td>35 dB</td><td>17 dB</td><td>C</td><td>0.60</td><td>0.35</td><td>0.45</td><td>0.60</td><td>0.65</td><td>0.70</td><td>0.65</td></tr></tbody></table></div></div>						Hz $\alpha_p$										$\alpha_w$	D <sub>nfw</sub>	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65
Hz $\alpha_p$																																							
$\alpha_w$	D <sub>nfw</sub>	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000																													
Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65																												
Fire Reaction	<div><div> A2-s1, d0 EN 13501-1</div></div>																																						
Performances & Features	<div><div> 85%</div><div> 95% RH</div><div></div><div></div><div><div>Lifetime Guarantee</div></div><div><div>30 Year System Guarantee</div></div><div> 4.3 Kg/m<sup>2</sup></div><div></div><div></div><div><div>BIM READY</div></div></div>																																						
Custom Options	<div><div> Dimensions</div></div>																																						

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 134.1.05.23