






















Hygiene

Hygiene offers a Class A sound absorption, washability and hygiene performances.

Key Features

- ✓ Suitable for high pressure water cleaning
- ✓ Excellent sound absorption 0.95 α_w
- ✓ ISO 4 with Clean Room grid
- ✓ Ideal for commercial kitchens and healthcare environments



Edge Detail	Board									
										
Thickness (mm)	18									
Modules (mm)	600 x 600 9702M 1200 x 600 9703M									
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant Clean Room 24 (to achieve ISO4)									
Colour	Global White									
Sustainability	 20		 A	 EN 13964 / E1						
Acoustics	 EN ISO 354 & EN ISO 11654									
		Hz α_p								
		α_w	Class	NRC	125	250	500	1000	2000	4000
Board		0.95	A	0.95	0.40	0.85	0.90	0.90	0.95	0.90
Fire Reaction	 Euroclass A2-s1, d0 EN 13501-1									
Performances & Features	 82%	 95% RH	 ISO 4 ISO 14644-1		 1	 30 Year System Guarantee				
	 1.3 Kg/m ²				 BIM READY					

¹ The application must be in the form of a fan spray of 30° angle and not a high pressure 'cutting jet'. The suggested minimum distance between the nozzle and the ceiling tile should not be less than 300 mm and the angle of projection should be 45°. Hygiene should be installed with Prelude 24 Corrosive Resistant grid and be clipped for high pressure water cleaning. Cleaning recommended twice a year.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 099.1.02.23