



## Oplia Triangle

Oplia Triangle is an exciting addition to the Oplia product family. These suspended ceiling tiles are cut into isosceles triangles and are available in 35 exciting colours, allowing you to create acoustic ceilings that make a real design statement.

Key Features

Oplia Triangle is a unique decorative ceiling tile that doesn't compromise on technical performance.

- //

With Class C sound absorption and excellent sound attenuation, it's a striking addition to any interior
- //

The triangular shape makes this ceiling tile particularly useful for wayfinding and zoning when used in combination with coloured tiles
- //

Compatible with Zentia's Prelude 24 suspended ceiling grid using a standard main runner, a unique cross tee and an innovative angled nodal bracket
- //

30 Year System Guarantee



Edge Detail	Board																																																		
Thickness (mm)	17																																																		
Modules (mm)	1162 x 1010 ..... BPTT2802M																																																		
Suspension Systems	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS																																																		
Sustainability	 41		 A+	 EN 13964 / E1																																															
Acoustics	<div><div> EN ISO 354 &amp; EN ISO 11654</div><div> EN ISO 10848-2 &amp; EN ISO 717-1</div><div> EN ISO 140-3 &amp; EN ISO 717-1</div></div> <table><tr><th></th><th></th><th></th><th></th><th></th><th></th><th colspan="7">Hz <math>\alpha_p</math></th></tr><tr><th></th><th><math>\alpha_w</math></th><th>D<sub>nfw</sub></th><th>R<sub>w</sub></th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th><th></th></tr><tr><td>Triangle</td><td>0.65(H)</td><td>37 dB</td><td>20 dB</td><td>C</td><td>0.65</td><td>0.55</td><td>0.50</td><td>0.55</td><td>0.75</td><td>0.85</td><td>0.85</td><td></td></tr></table>																		Hz $\alpha_p$								$\alpha_w$	D <sub>nfw</sub>	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000		Triangle	0.65(H)	37 dB	20 dB	C	0.65	0.55	0.50	0.55	0.75	0.85	0.85	
						Hz $\alpha_p$																																													
	$\alpha_w$	D <sub>nfw</sub>	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000																																								
Triangle	0.65(H)	37 dB	20 dB	C	0.65	0.55	0.50	0.55	0.75	0.85	0.85																																								
Fire Reaction	 Euroclass A2-s1, d0 EN 13501-1																																																		
Performances & Features	 86%	 95% RH																																																	
	 4.6 Kg/m <sup>2</sup>	 ISO 5 ISO 14644-1																																																	
Custom Options	 Dimensions																																																		

Colour	Global White and colour options							
Colours	To specify a colour, simply add the appropriate suffix from the provided colour palette to the item code. <b>Example:</b> BPTT2802M Oplia Triangle (White), BPTT2802MOR1 Oplia Triangle (RAL2009/Orange)							
	<div>GY1</div> <div>RAL 000 85 00</div>	<div>BL5</div> <div>RAL 260 90 05</div>	<div>GR5</div> <div>RAL 130 90 10</div>	<div>YE3</div> <div>RAL 080 90 10</div>	<div>OR3</div> <div>RAL 050 90 10</div>	<div>RE5</div> <div>RAL 010 90 10</div>	<div>PU5</div> <div>RAL 340 90 05</div>	<div>BR4</div> <div>RAL 050 70 10</div>
	<div>GY2</div> <div>RAL 000 65 00</div>	<div>BL4</div> <div>RAL 260 80 15</div>	<div>GR4</div> <div>RAL 130 80 30</div>	<div>YE2</div> <div>RAL 075 80 40</div>	<div>OR2</div> <div>RAL 050 80 30</div>	<div>RE4</div> <div>RAL 020 80 20</div>	<div>PU4</div> <div>RAL 340 80 20</div>	<div>BR3</div> <div>RAL 050 70 20</div>
	<div>GY3</div> <div>RAL 000 30 00</div>	<div>BL3</div> <div>RAL 260 50 25</div>	<div>GR3</div> <div>RAL 140 50 30</div>	<div>YE1</div> <div>RAL 1003</div>	<div>OR1</div> <div>RAL 2009</div>	<div>RE3</div> <div>RAL 020 60 40</div>	<div>PU3</div> <div>RAL 340 60 35</div>	<div>BR2</div> <div>RAL 040 30 30</div>
	<div>BK1</div> <div>RAL 9005</div>	<div>BL2</div> <div>RAL 260 30 20</div>	<div>GR2</div> <div>RAL 140 30 20</div>			<div>RE2</div> <div>RAL 020 30 40</div>	<div>PU2</div> <div>RAL 340 30 30</div>	<div>BR1</div> <div>RAL 8004</div>
		<div>BL1</div> <div>RAL 5015</div>	<div>GR1</div> <div>RAL 6037</div>			<div>RE1</div> <div>RAL 3020</div>	<div>PU1</div> <div>RAL 4006</div>	

We recommend ordering a full colour sample prior to specification and ordering. If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com).

Please note that even though great care has been taken to ensure correct colour match, colours can only be as accurate as the printing process allows.

Every monitor or mobile display has a different capability to display colours, and every individual may see these colours differently.



Order a sample

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 178.1.01.24