



















Hydrabloc ($\leq 100\%$ RH)

Hydrabloc can resist permanent RH up to 95% and temporary conditions of up to 100% RH. Install with Gridline 24 Corrosive Resistant grid system for higher humidity areas.

Key Features

- Stable at humidity levels of up to 100% RH
- Can be installed in temperatures ranging from 0°C to 40°C
- High acoustic absorption up to 1.00 α_w
- Ideal for WC, shower areas and hydrotherapy rooms. Should be installed on Corrosive Resistant grid



Edge Detail	Board	Tegular24																						
																								
Thickness (mm)	15	15																						
Modules (mm)	600 x 600 3687M 1200 x 600 3688M	600 x 600 3689M																						
Suspension Systems	Gridline 24 Joggled/Butt Cut Gridline 24 Corrosive Resistant Gridline 24 Sixty² Joggled/Butt Cut Cleanroom 24 Butt Cut	Gridline 24 Joggled/Butt Cut Gridline 24 Corrosive Resistant Gridline 24 Sixty² Joggled/Butt Cut Cleanroom 24 Butt Cut																						
Colour	Global White																							
Sustainability	<div><div> 20</div><div> 85</div><div> EN 13964 / E1</div></div>																							
Acoustics	<div><div> EN ISO 354 & EN ISO 11654</div><div> EN ISO 10848-2 & EN ISO 717-1</div></div> <table><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board</td><td>1.00</td><td>-</td><td>A</td><td>0.95</td><td>0.55</td><td>0.85</td><td>1.00</td><td>0.90</td><td>1.00</td><td>1.00</td></tr></table>			α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000	Board	1.00	-	A	0.95	0.55	0.85	1.00	0.90	1.00	1.00
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000														
Board	1.00	-	A	0.95	0.55	0.85	1.00	0.90	1.00	1.00														
Fire Reaction	<div><div> A1 EN 13501-1</div></div>																							
Performances & Features	<div><div><div> 89%</div><div> ≤100% RH</div><div></div><div> 30 Year System Guarantee</div></div><div><div> 2 Kg/m² Board 2.5 Kg/m² Tegular24</div><div></div><div> BIM READY</div></div></div>																							

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 181.1.02.24