

Arbo Glazing Blocks

Recommended for use in Glazing applications (as specified in BS8000 Part 7) and Balustrade applications (as specified in BS6180).

APPLICATION INSTRUCTIONS

For detailed applications contact Adshead Ratcliffe Technical Services Department.

TECHNICAL DATA	
Composition:	100 % PVC
Shore Hardness (typical value):	35 Shore D (90 Shore A)
Storage Life:	Not Applicable
Application Temperature:	+ 5 º C to + 30º C (in conjunction with specified Arbo Sealants)

HEALTH AND SAFETY

No chemical hazards associated with this product.



ARBO GLAZING BLOCKS

SIZES AND PACKAGING AVAILABLE

Flat Section

75mm x 25mm x 3mm	(250 per bag)
50mm x 12.5mm x 3mm	(500 per bag)
50mm x 25mm x 3mm	(500 per bag)
25mm x 22mm x 3mm	(1000 per bag)
25mm x 12.5mm x 3mm	(1000 per bag)
25mm x 12.5mm x 6mm	(1000 per bag)
25mm x 6mm x 1.5mm	(2000 per bag)
25mm x 6mm x 3mm	(2000 per bag)
25mm x 9mm x 3mm	(2000 per bag)
25mm x 9mm x 6mm	(1000 per bag)
25mm x 12.5mm x 1.5mm	(2000 per bag)
Wedge Section	
25mm x 22mm x 3mm	(500 per bag)

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Arbo sealants are manufactured in the U.K. by Adshead Ratcliffe.

CARLISLE® Adshead Ratcliffe & Co Ltd.	United Kingdom				
Derby Road Belper	DE56 1WJ	Т	+44 (0)1773 826661	Е	arbo@arbo.co.uk
Derbyshire	United Kingdom	F	+44 (0)1773 821215		www.arbo.co.uk