

# Arbo HV SGS

Arbo HV SGS is an increased viscosity, minimal slumping PVC adhesive and gap filler. Product is supplied in an industry standard cartridge for use with common application guns for ease of use.

The product forms a permanent bond to PVCu, Polycarbonate and many other plastics. Arbo HV SGS also has excellent adhesion to glass, aluminium and many other common construction substrates.

## MAIN APPLICATIONS

Recommended for sealing mitre joints, cleats, screws and hinges in window and door assemblies. Recommended for joints up to 5 mm width.

**NB**. Please contact Adshead Ratcliffe Technical Services Department for advice on other substrates.

## APPLICATION INSTRUCTIONS

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. It is recommended that Adshead Ratcliffe Technical Services Department be contacted to discuss effect of solvents on sensitive plastics.



| TECHNICAL DATA               |  |
|------------------------------|--|
| Work Life:                   | Product skins over within 5 minutes at 20° C |
| Solids Content:              | 58 % ± 3 %                                   |
| Application Temperature:     | + 5 ° C to + 30° C                           |
| Service Temperature:         | - 10 ° C to + 80° C                          |
| UV Resistance:               | Very Good                                    |
| Shelf Life:                  | 9 months                                     |
| Viscosity (Typical at 20°C): | 700-900 poise                                |
|                              |  |

### PACKAGING

300 ml cartridge

### COLOURS

White

#### HEALTH AND SAFETY

Product contains solvents. Please refer to Material Safety Data Sheet for full information.

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Arbo sealants are manufactured in the U.K. by Adshead Ratcliffe.

| CARLISLE® Adshead Ratcliffe & Co Ltd. | United Kingdom |   |                    |   |                 |
|---------------------------------------|----------------|---|--------------------|---|-----------------|
| Derby Road   Belper                   | DE56 1WJ       | Т | +44 (0)1773 826661 | Е | arbo@arbo.co.uk |
| Derbyshire                            | United Kingdom | F | +44 (0)1773 821215 |   | www.arbo.co.uk  |