

Description

Centrecoat Acoustic Suspended Ceiling Tile Paint is a high build obliterating water based matt finish, suitable for use on internal walls and ceilings. Formulated to infill block and brickwork to give a smoother surface where cost of rendering and plastering is not preferred. One coat coverage for most applications.

- ▶ Easy application
- ▶ Durable
- ▶ Low odour
- ▶ Quick drying

Colour and Finish

Available in White. Matt finish.

Application

Apply via brush, roller or airless spray. If applying via spray use a 15 - 17 thou tip size is recommended. Ensure surfaces are clean, dry and sound. Coating should be applied onto bare block work or acoustic ceiling tiles. If using on a substrate other than those specified, apply a suitable water based primer before hand. Surfaces must be sound, clean and free from wax, grease, oil, dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper. Prime any bare surfaces with an appropriate primer. New plaster and cement should be allowed to dry thoroughly before application. Thin the first coat of Centrecoat Acoustic Ceiling Tile Paint with 10% water. Minimum application temperature 8°C. Do not apply when condensation can form.

Technical Data

- ▶ Flash Point: Not applicable
- ▶ Soluble in water
- ▶ Spread of Flame: Tested to BS 476 (Part 7: 1997). On plasterboard rated Class 1 7.
- ▶ pH: 10
- ▶ Touch Dry: 1 hour at 20°C
- ▶ Overcoatable: 4 hours at 20°C
- ▶ Fully Cured: Overnight at 20°C

Coverage

Approx 6 - 10m² per litre. Coverage depends on porosity and texture of the substrate.

Clean Up

Clean equipment and tools after use with fresh water.

Storage

Store between 5°C and 25°C

Shelf Life

12 months if stored in original unopened containers.

Packaging

Available in 20 Litres