

Description

Centrecoat Two Pack Road Line Paint is formulated to be compatible with most of the surfaces that require line marking paints to be applied. These include roads, car parks (concrete or tarmac/weathered black top), airfield runways etc. Typical other uses are brick, paving and factory floor demarcations.

- ▶ Hard wearing
- ▶ Chemical and fuel resistant
- ▶ Resistant to tyre marking
- ▶ Easy to clean
- ▶ Long maintenance life
- ▶ Withstands constant traffic
- ▶ Resistant to oil, petrol and diesel

Colour & Finish

Available in Yellow, White and Black. Sheen finish.

Preparation

All surfaces must be clean, dry and free from oil, grease, anti-freeze, loose sand or aggregate. Do not apply when temperatures are below 10°C. Asphalt and other similar surfaces should be allowed to through harden for up to 6 months. Any curing compounds used on new concrete must be mechanically abraded off prior to striping.

Application

Apply via Brush, Roller, Conventional or airless marking machines. 13 thou top size recommended. Mechanically mix hardener and base together thoroughly before use. Allow to stand for 15 – 20 minutes. Minimum application temperature: 10°C.

Technical Data

- ▶ Volume Solids: Nominally 65%, varying slightly with colour
- ▶ Flash Point: 23 - 32°C
- ▶ Lower Explosive: Limit 1.0%
- ▶ Vapour Density: Heavier than air
- ▶ Specific Gravity: 0.95 - 1.40
- ▶ Solubility: Immiscible with water
- ▶ Pot Life: Up to 16 hours at 20°C
- ▶ Dry Film Thickness: Typically 150 - 170 microns
- ▶ Touch Dry: 1 hour at 20°C
- ▶ Handle Dry: 6 hours at 20°C
- ▶ Overcoatable: 4 - 12 hours at 20°C
- ▶ Fully Cured: 7 - 10 days at 20°C

Coverage Rate

Approx 3.7 square metres per litre at 150 microns DFT. The practical coverage rate depends on many factors and will be less than the theoretical figure.

Shelf Life

12 months if stored in original unopened container at temperatures between 5 and 35°C



PRODUCT DATA SHEET

Centrecoat Two Pack Road Line Paint

Packaging

Available in 4 Litres