



## Fixed Height Restrictor 3m, 4m, 5m, 6m and 7m Galvanised and Colour





The AUTOPA Fixed Height Restrictor has a standard clearance of 2.05m and limits access to high sided vehicles such as HGV's and Caravans. Height restrictors are ideal for use on sites where limited overhead clearance will cause problems for high sided vehicles such as multi-story or underground car parks.

Manufactured from galvanised mild steel, the body of the height restrictor is coated red as standard (other colours are available upon request; please state BS/RAL numbers at time of order). The AUTOPA Fixed Height Restrictor is available ragged or flanged and as an optional extra can be fitted with a knocking bar and/or a maximum height warning sign upon request.



The standard clearance is 2.05m with a knock bar, 2.2m without a knock bar.



Part Number	<u>Description</u>
138 106 534	3m Galvanised & Colour - Bolt Down
138 106 535	3m Galvanised & Colour - Concrete In
138 106 544	4m Galvanised & Colour - Bolt Down
138 106 545	4m Galvanised & Colour - Concrete In
138 106 554	5m Galvanised & Colour - Bolt Down
138 106 555	5m Galvanised & Colour - Concrete In
138 106 564	6m Galvanised & Colour - Bolt Down
138 106 565	6m Galvanised & Colour - Concrete In
138 106 574	7m Galvanised & Colour - Bolt Down
138 106 575	7m Galvanised & Colour - Concrete In

## **Product details**

- Standard Clearance: 2.2m (without a knock bar)
- Standard clearance: 2.05m (with a knock bar) Optional Extra
- Main body 90mm x 90mm square tube

- Main Gate Arm: 60mm x 60mm square tube
- 3mm wall thickness
- Concrete in 600mm (below ground)

## Installation & use

Bolt down Height Restrictors require bolting down to a suitable concrete surface (no less than 600mm3) by means of four 16mm bolts per leg.

Concrete in Height Restrictors require an excavated hole (no less than 600mm3) for installation.

It is recommended that suitable signs are installed to ensure vehicles are aware of the obstruction.

This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

