


Double Fixed Height Restrictor with Swing Gate 6m, 8m, 10m, 12m, and 14m Galvanised and Colour







The AUTOPA Double Fixed Height Restrictor with Double Swing Gates limit access to high sided vehicles. Ideal for use on commercial sites such as retail parks, it spans two carriageways, preventing vehicles from circumnavigating access control measures in place. The booms of the Swing Gates can be opened to allow low sided vehicles to access the site whilst preventing high sided vehicles from access.

Manufactured from galvanised mild steel, the system is coated red as standard (other colours are available upon request; please state RAL numbers at time of order). The gate can both be locked in the open and closed positions using additional catch posts and padlocks (available separately).

Knock bars to suit the barrier can be supplied at an extra cost.

The standard clearance is 2.05m with a knock bar, 2.2m without a knock bar.

Part Number	Description
138 106 900	6m Galvanised & Colour - Bolt Down
138 106 900R	6m Galvanised & Colour - Concrete In
138 106 901	8m Galvanised & Colour - Bolt Down
138 106 901R	8m Galvanised & Colour - Concrete In
138 106 902	10m Galvanised & Colour - Bolt Down
138 106 902R	10m Galvanised & Colour - Concrete In
138 106 903	12m Galvanised & Colour - Bolt Down
138 106 903R	12m Galvanised & Colour - Concrete In
138 106 904	14m Galvanised & Colour - Bolt Down
138 106 904R	14m Galvanised & Colour - Concrete In

Product details

- Standard Clearance: 2.2m (without a knock bar)
- Standard Clearance: 2.05m (with a knock bar) **- Optional Extra**
- Main Body: 120mm x 120mm square tube
- Main Gate Arm: 60mm x 60mm square tube
- 3mm wall thickness
- Concrete in 600mm (below ground)

Installation & use

Bolt down Height Restrictors require bolting down to a suitable concrete surface (no less than 600mm3) by means of four M16 bolts per leg.
Concrete in Height Restrictors & Catch Posts require an excavated hole (no less than 600mm3) for installation.
It is recommended that suitable signs are installed to ensure vehicles are aware of the obstruction.
This product is guaranteed for 12 months (if installed and used correctly).

British Made

www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

bsi
ISO 9001 Quality Management Systems CERTIFIED FM 31071
ISO 14001 Environmental Management CERTIFIED EMS 503166
ISO 45001 Occupational Health and Safety Management CERTIFIED OHS 552103