



# **Technical Information**

vers up to 24m2 with 1 coat or 8
The 9L can covers up to 43m2 with 1
ice panels. Coverage can vary
application method and the
l nature of the surface

### **Product Information**

### Typical Use

Read the health, safety and environmental information opposite. Bare or untreated wood should be pretreated with an appropriate wood preserver to prevent rot and decay. Surfaces should be dry and free from dirt and algae etc. remove any algae, lichen, fungi or moss using an appropriate fungicidal wash or cleaner designed for the job.

#### Composition

#### **Key Benefits**

5 years protection, Non drip easy application, Shower proof in 1 hour, Wax enriched water repellant, Water based

#### Pack size

30ml, 5L, 9L

## **Application Method**

Stir thoroughly before use, try a test area first to ensure that colour and adhesion are acceptable. Apply 2-3 coats evenly along the grain avoiding overlaps. Allow 2-4 hours between coats under normal weather conditions. This product is wax enriched to repel water. Recoat within 2-3 days of previous coat. If a longer period elapses try a flat a test area to ensure product is not repelled, product performance will be reduced if applied to grey and weathered smooth wood. Do not apply in temperatures below 5C, in damp conditions or if rains likely before the product has dried. Please note that the colour in the tub may be different to the final shade when dry. Where a strong colour change is involved, more coats may be required. If using more than one can it is advisable to mix them together in a larger container or finish in a corner before starting a new can.