

	Hammerite Radiator Enamel Satin Aerosol	About this product Hammerite Radiator Enamel is specially formulated to provide a heat resistant, brilliant white finish on domestic water filled household radiators and hot water pipes.Provides a tough long lasting finish
Key Benefits   Heat resistant protection   Hard wearing   Resists yellowing		
Special Featu Tough & dur Prevents yel	ures able lowing	
Technical In Touch dry Recoatable Coverage	formation	1-2 hours 15 minutes 0.5m2per litre
Product Info Typical Use	rmation	

All surfaces must be clean, dry and free from rust, flaking paint, dirt, dust and grease. Rub down all painted surfaces with abrasive paper. Radiators must be turned off and only painted when cold. Mask off the surrounding area to protect from overspray

## **Composition** Solvent-based

**Key Benefits** Heat resistant protection, Hard wearing, Resists yellowing, Solvent based

Pack size

## System Information

Store aerosol at room temperature for 2 hours prior to use. Shake can vigorously, in a vertical motion, until the agitator ball is heard and then for a further 3 minutes. Apply light even coats, from a distance of approximately 15cm (6"), and keep the aerosol moving. Do not concentrate spray on one spot. When touch dry (15 minutes) apply a further 2-3 coats, allowing 30 minutes between coats. Do not overspray as sagging may occur if excessive paint is applied. Between coats invert can and spray for 2 seconds to avoid blockages.

## Application Method

Store aerosol at room temperature for 2 hours prior to use. Shake can vigorously, in a vertical motion, until the agitator ball is heard and then for a further 3 minutes. Apply light even coats, from a distance of approximately 15cm (6"), and keep the aerosol moving. Do not concentrate spray on one spot. When touch dry (15 minutes) apply a further 2-3 coats, allowing 30 minutes between coats. Do not overspray as sagging may occur if excessive paint is applied. Between coats invert can and spray for 2 seconds to avoid blockages.