

## PERFORMANCE & QUALITY

CNC manufactured to order in the UK to international standards.

Whether you are the designer, the contractor, or responsible for maintenance of the building, Profab Access Riser Doors meet all of your demands. Security, Fire Protection, Functionality & led by Design to be aesthetically discreet.

A full portfolio of doors with lock and frame options, and excellence in bespoke design to solve all of your access requirements without compromise.

Quality at the core of the business and leading the field in accreditation.

# CERTIFIRE® TESTED TO 4 HOURS







### 4000 SERIES

60-120-240



Exova Warrington Certificate

UL Labs Chicago





#### **BENEFITS**

- Fast & Simple to Install
- Seamless Aesthetic Finish
- Even Frame/Door Gap Adjustment
- Single, Double & Multi-Leaf Configurations
- Fully Recyclable at End Of Life

#### STANDARD FEATURES

- Certifire Fire Rated to 240 Minutes
- UL Labs Certificated to 120 Minutes
- 36dB Acoustic Shielding as Standard
- Up to 80 Minutes Insulation
- Airtight to Part L
- □ Frame Construction: 1.5mm Zintec Steel
- Door Construction: 1.2mm Zintec Steel
- Rockwool Core Door Leaf
- 12.5mm Fireline Board Door Leaf Backing
- Intumescent Smoke Seal
- Fully Welded Rigid Box Section Frame
- Euro Profile Cylinder Multi-Point Locking
- Concealed Continuous Piano Hinge
- Fully Polyester Powder Coated Matt RAL 9010
- Suitable for Finishing On-Site

#### **OPTIONS**

- ☐ Up to 44dB Acoustic Upgrade (ACU)
- Choice of Frame Profiles to suit Finishing Requirements
- ☐ Flush Frame Skirting Profile
- Shadow Gap Frame Profiles
- 2 or 3 Point Multi Locking
- Visible or Concealed Escutcheon
- Left or Right Handed Opening
- □ Removable Safety Handrails to BS6180:2011 (SHR)
- Door Closers

#### BIM LEVEL 2

Profab Access riser doors are available to download now as objects for use in your current & future projects.







BF-3HS-SD-SHR








### TYPICAL RISER DOOR CONFIGURATIONS

Full height single, double, triple & quad door leaf sets. Maximum Height: 3100mm for 240 minutes fire rating, CERTIFIRE certification.



### MULTI-POINT LOCKING OPTIONS

Euro Profile cylinder locks are employed thoughout our range of TRUSTED ACCESS SOLUTIONS riser doors, to prevent unauthorised access.



#### 2PL: TWO POINT LOCKING

- 1 Suction Cup
- 2 CE: Concealed Escutcheon Plate (Patent Pending)
- 3 Euro Profile Cylinder Lock
- 4 Locking Assembly: Engages Top & Bottom

#### 3HS: THREE POINT HIGH SECURITY LOCKING

- 1 T Bar Key: Used to Unlatch & Pull Door Leaf Open
- 2 Secondary Locking
- 3 Euro Profile Cylinder Lock
- 4 Locking Assembly: Engages Top, Bottom & Lock Side
- 4 Stainless Steel Collar (White Plastic Plug Removed)

### FRAME PROFILE OPTIONS

A comprehensive choice of frame profiles are available as standard to suit all wall finishes. FRAME DEPTHS: 91.5mm





#### TO SUIT APPLICATION

- 1 VRA: Visible Raised Architrave Ideal for Retro Fitting/Finished Areas & Creating Shadow Gaps
- 2 PF: Picture Frame
- Ideal for Retro Fitting/Finished Areas 3 BF: Beaded Frame
- Ideal for Tape & Jointing/Skimming
- 4 DPF: Deep Plaster Frame for Wet Plaster
- Ideal for wet plastering/float and set
- 5 DFF: Dutch Folded Frame Ideal for Masonry/Blockwork

#### SAFETY HANDRAILS OPTION

Option where void cavity presents a danger to service maintenance.



#### SHR

Each handrail is secured with 4 fixing bolts for strength. Allow 45mm in addition to standard frame depth where fitted.

SPECIFY AS DESIRED

### SIZE INFORMATON

requirements. Our team will assist you to determine the correct



### SALES/TECHNICAL ENQUIRIES



+44 (0)1827 719 051



technical@profabaccess.com

### **CONNECT WITH US**



profabriserdoors.com

profabaccesspanels

@accesspanels

Profab Access Ltd Unit C-D Riversdale House Riversdale Road Carlyon Road Ind Est Atherstone Warwickshire UK CV9 1FA





