

Blackout Blinds, Screens and Shading: The Options

The sizes shown below provide a broad guideline for each of the applications, but various factors will affect these sizes. More accurate dimensions for any given head box size and method of operation can be found in the size charts in the Technical section of this menu.

Our standard head box sizes range from 65mm through to 200mm square, however larger and custom sizes are available.

Blackout for normal window



Operation: Hand or Electric.

Size Range: Width 200 to 5000 mm; Drop 200 to 6000 mm

Blackout for sloping window



Operation: Hand or Electric.

Size range: Width 300 to 3000 mm; Drop 300 to 6000 mm

NB: Above 25 degrees from vertical - see Roof Light.



Lifting Up: Width 300 to 3000 mm; Drop 300 to 6000 mm

Operation: Hand , Cord or Electric.

Size range: Width 300 - 3000 mm; Drop 300-6000 mm

1 Bilton Road Industrial Estate,
Cadwell Lane, Hitchin,
Herts, SG4 0SB


E info@shy.co.uk

T +44 (0)1462 455400

F +44 (0)1462 437600

www.shy.co.uk

Manual Rooflight




Operation: Hand, Cord, Gearbox and Crank Handle

Size Range: Width 300 - 3000 mm; Drop 300-6000 mm



Electric roof light (tensioned, including FTS - Fabric Tensioning System)



Operation: Electric

NB: See here for head-box sizes.

Size range Width 600 to 3500 mm; Drop 600 to 10000 mm

NB: Guide Figures - Subject to angle of slope



Curved



Operation: Hand, Side winder, Gearbox and Crank Handle, Electric

Size Range: (Guide Figures, Depending on Curve Radius)

Width 500 - 3000mm Drop 500 - 6000mm

1 Bilton Road Industrial Estate,
Cadwell Lane, Hitchin,
Herts, SG4 0SB

E info@shy.co.uk

T +44 (0)1462 455400

F +44 (0)1462 437600

www.shy.co.uk

Twin Blind



NB: Above 9 sq m must be electric or gearbox operation