

**NEW GENERATION** 

NON-ELECTRIC SEPTIC SYSTEMS



ALL-IN-ONE COMPACT SOLUTIONS FOR DOMESTIC WASTEWATER TREATMENT

# **MONOBLOCK**

AIR OUTLET

# THE ALL-IN-ONE COMPACT SOLUTION



AND-PLAY

## **SUSTAINABILITY HIGHLIGHTS**

√ Long lifespan BIOROCK Media

**UNIQUE ADVANTAGES** 

✓ Ultra-compact and discrete

✓ Non-Electric

✓ Totally silent

✓ Odourless

✓ Low running costs

- ✓ Low carbon footprint
- ✓ Minimum annual maintenance
- ✓ Long Septic Tank pump out intervals

#### **PRIMARY TANK**


Clarifies the wastewater coming from the residence by retaining oils, fats, greases and organic solids. The water passes through an effluent filter before discharging into the BIOROCK reactor.

#### **BIOREACTOR**


The BIOROCK Media in the Bioreactor treats the wastewater naturally with an aerobic digestion process (Secondary Treatment) and a filtration process (Tertiary Treatment).

### **2 DISCHARGE OPTIONS**

#### 1 BIOROCK® Gravity Discharge



#### 2 BIOROCK® Pumped Discharge



Our high-level discharge is equipped with a reliable, high quality, pump kit. This kit is delivered pre-assembled for ease and speed of installation. Intermittent operation by float switch.

#### **BIOROCK® MEDIA**

The wastewater percolates through the filtering media. The BIOROCK Media is a very effective carrier material for bacteria. The BIOROCK media is highly resistant to degradation and remains extremely stable over a long term.

The BIOROCK Media is 100% recyclable



Since 1988, BIOROCK has become an internationally acclaimed and experienced leader in the field of onsite and decentralized Non-Electric Wastewater Treatment Technologies for residential and commercial sectors.



# More BIOROCK Systems available from 4-300 persons!







## **BIOROCK®** versus Traditional

BIOROCK provides a revolutionary and efficient system when compared with all other Wastewater treatment brands available today.

FACTS	BIOROCK®	Traditional units
Non-electric*	Yes	No
Silent & odourless	Yes	No
Handles intermittent loading	Yes	No
Handles absence periods	Yes	No
Septic tank conversion unit*	Yes	No
Low maintenance	Yes	No
Low operational costs	Yes	No

<sup>\*</sup> Subject to site conditions

## Significant savings

through very low maintenance and running costs



No energy costs for the treatment process



Long emptying intervals of the primary tank: 3 - 5 year only



Minimal maintenance and repair costs.

Not prone to failure. No breakdowns, thus no need for expensive spare parts.



Save up to £ 400,- per year\*

\*compared to a conventional wastewater treatment plant

All BIOROCK® systems are delivered complete and pre-assembled for ease of installation.

