

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 1

Compilation date: 20/03/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Product code: 31207/31208/31209

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Wood Repair

1.3. Details of the supplier of the safety data sheet

Company name: C Brewers & Sons Ltd

Albany House

Ashford Road

Eastbourne

East Sussex

BN21 3TR

England

Tel: 01323 411080

Email: enquiries@brewers.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319

Classification under CHIP: This product has no classification under CHIP.

2.2. Label elements

Label elements under CLP:

Hazard statements: H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P102: Keep out of reach of children.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 2

contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

Label elements under CHIP:

Hazard symbols: No significant hazard.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S37: Wear suitable gloves.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

VINYL TOLUENE - REACH registered number(s): 01-21196222074-50-0000

EINECS	CAS	CHIP Classification	CLP Classification	Percent
246-562-2	25013-15-4	-: R10; Xn: R20; Xi: R36/37/38	Acute Tox. 4: H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226	10-20%

ISOPENTANE

201-142-8	78-78-4	F+: R12; Xn: R65; -: R66; -: R67; N: R51/53	Flam. Liq. 1: H224; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066	<1%
-----------	---------	--	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: No symptoms.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

[cont...]

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 3

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 4

ISOPENTANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m ³	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Not applicable.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Relative density: TBC

VOC g/l: TBC

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Not applicable.

10.4. Conditions to avoid

Conditions to avoid: Air.

[cont...]

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 5

10.5. Incompatible materials

Materials to avoid: Not applicable.

10.6. Hazardous decomposition products

Haz. decomp. products: None, if stored and handled correctly.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: No symptoms.

Delayed / immediate effects: Not applicable.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Small quantities of the product can be mixed and allowed to cure, then can be disposed as solid waste.

Waste code number: 03 03 99

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 6

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R12: Extremely flammable.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect concentration

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

[cont...]

SAFETY DATA SHEET

WOOD FILLER SF WHITE / NATURAL 770ML AND 2200ML

Page: 7

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

OPT = optical

INH = inhalation

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.