

INTERIOR READY MIXED **FINE SURFACE FILLER**

GENERAL INFORMATION

Description

Ready mixed fine surface filler

Intended use

Interior

- Finishing substrates
- Allows to hide small defects

Use

Application thickness



Working

Dilution

Manual application





PRODUCT ADVANTAGES

- Very fine finish
- Excellent adhesion to substrates
- No need to spot prime
- + Enhance the paint finish
- White
- Easy to sand
- Easy to apply

USE

DILUTION Ready mixed

APPLICATION

- Conditions Do not apply at temperatures of below +8°C or

above +35°C, or at a relative humidity of above

70% H.R.

- Equipment Smoothing trowel, blade, trowel.

- Equipment cleaning With water before completely dry.

> Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point.

Do not dispose into the environment.

APPLICATION THICKNESS 1 mm

AVERAGE CONSUMPTION 0.25 kg/m²

SUBSTRATES Concrete, cement, plaster, plasterboard, primed

wood, old painted substrates.

Substrates must be hard, cohesive, clean, sound

and dry according to the local standards.

OVERCOAT Primer, interior conventional paint, light-weight wall

coverings.



INTERIOR READY MIXED FINE SURFACE FILLER

TECHNICAL DATA

COMPONANTS Polymer base aqueous phase coat mix, mineral fillers,

additives.

рΗ 8.5 ± 1

COLOUR White

WORKING TIME AT 20°C Unlimited

WAITING TIME BEFORE OVERCOATING

Once completely dry

CLASSIFICATION NF T 36-005 - Family III, class 2


NORM NF EN 16566

V.O.C < 1 g/I (Ready mixed)

HEALTH AND SAFETY







1 kg bucket

12 months from date of manufacture, in unopened **PACKAGING**

original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use.

Store in original packaging. **STORAGE**

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017 The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.



Brewers Decorator Centres, Albany House, 127 Ashford Road, Eastbourne BN21 3TR

Help Line: 0845 504 5040