UltraTrack Pro

ULTRA STRENGTH, ULTRA COVERAGE, ULTRA SEAMLESS: THE NEW STANDARD IN HEAVY-DUTY ACCESS ROADS



Cutting-Edge Overlapping Design: Stronger, Leak-Proof Surfaces

The Ultimate in Versatile, Safe Ground Coverage

- Interlocking joints provide increased weight distribution and eliminate the risk of damage to vehicles or equipment.
- Significantly reduced mud seepage onto the mat due to the overlapping design.
- Maintains the standard 3-metre roadway with an enhanced connection system.
- Standard bolted connection system results in affordable replacements.
- Double-sided tread design provides versatile grip patterns. Just flip the mat to switch it up.

IDEAL FOR USE BY

- CONSTRUCTION
- CIVIL ENGINEERING
- UTILITI<u>ES</u>
- OIL & GAS
- TRANSMISSION
- WIND & SOLAR FARMS
- RENEWABLE ENERGY
- DRILLING CONTRACTORS
- EVENTS
- FORESTRY & LOGGING

IDEAL TO CREATE

- HAUL ROADS
- COMPOUNDS
- STORAGE AREAS
- DRILL PADS
- WORK PLATFORMS

GroundGuards®

UltraTrack Pro







Material: Recycled HDPE and fully recyclable

Overall Size: 3m x 2.5m x 38mm

Surface Size: 285cm x 235m

Surface Area: 6.7m²

Weight: 295kg

Tread: Dual tread design for tyre-equipped

vehicles and steel-tracked vehicles

Connectors: Standard M16 bolts

Steel reinforced connection points

Loading Guide

Supports vehicles and equipment exceeding 100 tonnes, subject to ground conditions.

This loading guide is for firm, dry ground. If the weather is likely to turn wet, or the job duration is in excess of a week, please ask for advice about using a more heavy-duty product.

It is the user's responsibility to assess the load-bearing capacity of the ground, and to only operate vehicles within the weight that the ground is capable of safely supporting. Please visit website for terms of guarantee.



GroundGuards®

Ground-Guards Ltd Rudgate, Walton, Leeds, LS23 7AU, UK +44(0)113 267 6000

www.Ground-Guards.co.uk | Info@Ground-Guards.co.uk