

ARMATHERM™ 500 SERIES

Thermal Break Material For Structural Connections



INTRODUCTION

Reducing heat flow within a building's thermal envelope reduces energy consumption as well as potential condensation issues. Armatherm™ 500 thermal break material significantly reduces energy lost from thermal bridging in building envelope connections.

Armatherm™ 500 is a high strength, polyurethane material made in several densities to support a wide range of loading conditions. Due to its closed cell structure, it does not absorb water or moisture and has limited creep under continuous load.




Armatherm™
500 Series

SPECIFICATIONS OF ARMATHERM™ 500 SERIES

Specifications of Armatherm™ 500 Series	160	250	320	490
Compressive Strength (N/mm ²)	2.0	4.3	6.8	18.5
Compressive Modulus (N/mm ²)	65	137	225	496
Thermal Conductivity (W/mK)	0.031	0.042	0.064	0.078
R Value per 25mm	4.80	3.40	2.80	2.00
Min. Operating Temperature (°C)	-185	-185	-185	-185
Max. Operating Temperature (°C)	80	80	80	80

Armatherm™ 500 is manufactured in sheets 2000mm x 1000mm x 5mm, 10mm, 12mm, 15mm, 20mm, 25mm, 50mm thick and can be bonded to create 150mm, 200mm and 250mm thicknesses to achieve a specific R value. It can be used anywhere a penetration or transition exists in the building envelope creating a thermal bridge. Solutions using Armatherm™ to minimise heatloss include:

- Parapets
- Slab/floor edge
- Column base
- Roof penetrations
- Custom windowsills
- Fenestration
- Roof edge
- Slab to foundation
- Foundation to wall
- Concrete balconies
- Custom moulding for over-insulating



Column Base Thermal Break



**Armatherm Thermal
Bridging Solutions LTD**

UK Office: Hillam Road, Bradford, BD2 1QN
+44 (0)1274 591115
info@armatherm.com
armatherm.co.uk

European Office: Riverside, Tullamore, Co. Offaly, Ireland
+353 1 697 1509
info@armatherm.com
armatherm.com/ie

ARMATHERM™ 500 SERIES


Thermal Break Material For Structural Connections



COLUMN BASE

Columns traditionally extend through the building envelope and slab insulation at their base. Thermal bridging can be prevented by using Armatherm™ 500 series material as a load supporting thermal break directly under the column base.

This is particularly important in cold storage facilities to prevent the sub grade from freezing.



Colour is dependent on load

PARAPET / ROOF PENETRATION

Roof to wall and parapet locations require structural framing for support which prevents continuous insulation from roof to facade. This creates a thermal bridge which can be prevented by providing an Armatherm™ 500 series structural thermal break under the parapet connecting the facade and roof insulation and improving the effective R value by as much as 30%. A thermal break can also be installed within the envelope at roof penetration points where structural elements are supported. This provides continuous insulation and prevents potential condensation issues.



Colour is dependent on load

SLAB / WALL TRANSITION / WALL

Foundations are part of a building's envelope. The connection from slab on grade to foundation wall and wall above foundation wall are both areas where thermal bridging occurs. Armatherm™ 500 series material can support and transfer loads up to 18.5 N/mm² while providing minimal energy loss.



Colour is dependent on load



Armatherm Thermal
Bridging Solutions LTD


UK Office: Hillam Road, Bradford, BD2 1QN
+44 (0)1274 591115
info@armatherm.com
armatherm.co.uk

European Office: Riverside, Tullamore, Co. Offaly, Ireland
+353 1 697 1509
info@armatherm.com
armatherm.com/ie

ISOLATION WASHERS AND BUSHINGS

A thermal break should also be provided at the front side of the bolt head between two steel washers and face of the exterior steel. This prevents a thermal bridge through the bolt which would otherwise provide a path for heat flow through the thermal break assembly.

Armatherm™ Isolation washers and bushings are recommended to eliminate this path and any potential for condensation within the building envelope. Contact us for assistance with your structural design or thermal calculations.



Bushing Detail

Bolt Size	Hole In Pad	Bushing ID	Bushing OD	Hole in Structure	Bushing Length (Standard)
3/8"	0.44"	0.44"	0.57"	0.64"	0.50"
M12	14mm	14mm	20mm	22mm	13mm
1/2"	0.55"	0.55"	0.78"	0.85"	0.50"
M16	18mm	18mm	24mm	26mm	13mm
5/8"	0.70"	0.70"	1.00"	1.07"	0.50"
M20	22mm	22mm	28mm	30mm	13mm
3/4"	0.86"	0.86"	1.10"	1.17"	0.50"
M23	24mm	24mm	32mm	35mm	13mm
7/8"	0.94"	0.94"	1.25"	1.31"	0.50"
M24	26mm	26mm	32mm	35mm	13mm
1"	1.05"	1.05"	1.25"	1.38"	0.50"

Washer Detail

Bolt Size	Washer ID	Washer OD	Thickness
3/8"	0.44"	1.18"	0.25"
M12	14mm	30mm	6mm
1/2"	0.55"	1.18"	0.25"
M16	18mm	40mm	6mm
5/8"	0.70"	1.57"	0.25"
M20	22mm	47mm	6mm
3/4"	0.86"	1.85"	0.25"
M23	24mm	50mm	6mm
7/8"	0.94"	2.00"	0.25"
M24	26mm	50mm	6mm
1"	1.05"	2.00"	0.25"

Armatherm has a tolerance of $\pm 0.76\text{mm}$ on the I.D. and $+ 1.52\text{mm}$ on the O.D. on our thermally broken bushings.

CUSTOMER ISOLATION BUSHINGS AND WASHERS AVAILABLE UPON REQUEST.

