



Length

The wash trough is available in five standard lengths: 1200 mm, 1500 mm, 1800 mm, 2100 mm and 2400 mm.

Waste Outlet

The wash trough is supplied as standard with a 38 mm (1½ in) BSP unslotted flush grated waste fitting positioned centrally.

Tap Hole Position

The wash trough is produced with either one central or two tap holes each 600 mm of length or per user (see Fig. 1).

Note: for 1500 mm and 2100 mm long wash troughs, tap hole centres are adjusted to suit the number of users / stations.

Tap Hole Sizes

The standard tap hole size is 22 mm diameter.

Non-standard sizes that can be provided are: 30 mm dia. and 35 mm dia.

Support Legs (Optional)

The wash trough can be supplied, as an option, with two stainless steel front support legs.

Product Code Selection for Order or Quotation

1. Base Product Code

307 - wash trough

2. Length

-1200 mm -2100 mm
 -1500 mm -2400 mm
 -1800 mm

3. Outlet (as facing)

-C - central

4. Tap Hole Position

-C - central
 -T - two

5. Tap Hole Sizes

Standard
 -22 -22 mm dia.
Non-Standard
 -30 -30 mm dia.
 -35 -35 mm dia.

6. Option

-FL - front support legs (pair)

7. Other

Please refer to our website for listings of suitable water controllers taps and valves

