conex | Bänninger >B< Press Solar



An innovative press system which provides a secure fitting for solar applications.

Features and benefits:

- Available in copper and red brass fittings.
- Flame-free installation for ensuring on site safety.
- >B< Profile 3-point press ensures a leak-free, secure and permanent joint.
- Quick and simple to install, saving time and money.
- Available in 15 mm to 28 mm.
- Compatible with various press tools and jaws.*

- Suitable for use with hard, half-hard and soft copper tubes to EN 1057.
- Manufactured and designed to EN 8537 copper tube press fittings.
- Designed for solar pressure up to 10 bar.
- Designed for temperature ranges of -15 °C to 140 °C with short term excursions to 230 °C (glycol:water 50:50).





^{*}Please see compatibility list on website for more details

>B<Press Solar range

Straight Coupler



PH1 (PH5270)

From: 15 mm To: 28 mm

Street Elbow



PH12S (PH5001)

From: 15 mm To: 28 mm

Straight Union Connector



PH69F (PH4330G)

From: 15 x 1/2" To: 22 x 1"

Fitting Reducer



PH6 (PH5243)

From: 22 x 15 mm To: 28 x 22 mm

45° Elbow



PH21 (PH5041)

From: 15 mm To: 28 mm

Tee - Female Threaded



PH30 (P4330G)

From: 15 x 15 x 1/2" To: 22 x 1/2" x 22

Female Straight Connector



PH2 (PH4270G)

From: 15 x 1/2" To: 22 x 1"

45° Street Elbow



PH21S (PH5040)

From: 15 mm To: 28 mm

Female Straight Union Connector



PH69F (PH4330G)

From: 15 x 1/2" To: 22 x 1"

Male Straight Connector



Elbow

PH12 (PH5002)

PH25 (PH5130)

From: 22 x 22 x 15 mm

To: 22 x 28 x 22 mm

Tee - Reduced Branch

From: 15 mm

To: 28 mm

PH3 (PH4243G)

From: 15 x 1/2" To: 28 x 1"

Equal Tee



PH24 (PH5130)

From: 15 mm To: 28 mm

Connector with Flat Face



PH4355

From: 15 x 3/4" To: 22 x 1"

