

50
YEAR
ANNIVERSARY
FIFTY YEARS OF EXCELLENCE

STA-LOK®

Marine Rigging Hardware

2023 Price List



“
RELIABILITY AND
ENDURANCE ARE AT
THE FOREFRONT OF
EVERYTHING WE DO.
”



Our Standard Wire	06
Sta-Lok Self-Fit Terminals	12
Sta-Lok Insulators	28
Sta-Lok Swage Terminals	36
Sta-Lok Bronze Turnbuckles	46
Sta-Lok Supajust Turnbuckles	64
Sta-Lok Threaded End Fittings	78
Tip Cup	89
Marine Toggles	90
Sta-Lok Guard Rails & Life Line Fittings	92
Other Products & Accessories	116

FOR THE MOST BEAUTIFUL
BOATS CHOOSE STA-LOK.

Sta-Lok have been supplying the global marine industry for more than 50 years after first introducing our products at the International London Boat show in 1973.

Our products are designed with safety in mind, manufactured using high specification stainless steels, selected for their strength and corrosion resistance.

Our dedication to design, manufacturing and customer service means reliability

and endurance are at the forefront of everything we do. After all, our products must stand up to the most challenging of climatic conditions.

We are proud to be ISO 9001 accredited, re-enforcing our passion for quality through our entire company and our product range.

Today, our extensive range of fittings and wire rope makes Sta-Lok the preferred choice for professionals and sail boat owners alike.

CELEBRATING 50 YEARS OF STA-LOK

It is now more than 50 years since the first introduction of Sta-Lok at the 1973 International London Boat show and our heritage is the source of our continued inspiration.

Developed by our Founder, Ivor Barfield, in an era without technology and where everything was crafted by hand, we are extremely proud to have retained our roots as a family run UK manufacturer.

Although so much has changed over 50 years, with continuous investment in advanced manufacturing, we still hold dear those family values on which our business was originally founded, where exceptional customer service and quality are engrained into our company culture.

We have a rich history, engrained with inspiring stories, beautiful boats and stunning architecture. We believe in producing products that make adventures possible and visions a reality.



Terry Barfield
TERRY BARFIELD
Managing Director



James Barfield
JAMES BARFIELD
Sales Director



Ivor Barfield, Founder



Ivor and Terry in the factory, 1994



The Works, 1994

Our 2023 Price List

Trade Accounts

Sta-Lok's Marine market is built upon key relationships with riggers, resellers and distributors, forming a global reseller network to support yacht owners worldwide.

If you would like to add Sta-Lok to your product offering, please make contact and our team will be happy to discuss your requirements further.

UK Head Office

+44 (0) 1206 390 773
enquiries@stalok.com
stalok.com

USA Office

910 259 3394
usa@stalok.com

Sta-Lok Trademark

Sta-Lok is a registered trade mark and company logos should not be used without prior approval by said company.

Pricing Policy

Prices displayed show our recommended retail price. Individual trade accounts and discount programmes to suit the needs of your business can be arranged.

Every effort has been made to ensure that prices are correct at the time of printing.

Prices can be subject to alteration throughout the year and may be changed without notice.

All prices listed are shown in £'s Sterling or \$ US Dollars as noted. All prices are exclusive of VAT, sales taxes and delivery costs.

Returns Policy

Rigging hardware manufactured by Sta-Lok is guaranteed at the time of shipment, to be free of defects in material and craftsmanship and only when used for the purpose intended.

Returned goods will not be accepted without notification and without prior approval by

Sta-Lok Terminals Ltd. All returns must be prepaid and in a re-saleable condition before a credit can be issued.

Technical Information

Ongoing product development means that product specification may change.

Every effort has been made to ensure that technical information displayed is correct at the time of printing.

For any dimensions or product details, break loads, etc. not shown, please make contact with us, and our technical team will be happy to provide.

Useful Life and Liability

Yacht rigging should be inspected, checked and maintained regularly by an experienced yacht rigger or surveyor.

Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging and thus, no guarantee can be provided for product life, load capacity or other factors due to variability in usage.

Some regulatory body's and insurances will require the replacement of rigging and rigging components within certain time frames. You should ascertain if and what regulations apply to you, your yacht/vessel or your project to determine the relevant time-scales for replacement and qualified inspections.

Sta-Lok Terminals Ltd does not assume any responsibility for any incidental or consequential damages in connection with the use of its products.

Sta-Lok does not accept responsibility for products used in applications where safe working loads are exceeded, product has been improperly installed, and/or the product has been modified.

For full information, please refer to our Terms and Conditions at the back of this brochure.



We sell reels of stainless steel wire rope.
Call us now to order yours!

Our Standard Wire

Sta-Lok stock a comprehensive range of stainless steel grade 1.4401 (AISI 316) wire rope on 100,200 and 300-metre reels. Conforming to international standards, all wire is certified and fully traceable, in line with our quality systems and ISO 9001 accreditation.


Minimum break loads are listed but some variance on actual break loads can occur between manufacturers. An appropriate factor of safety should be applied before choosing or specifying a particular product. This factor of safety may be defined by industry standards, law or other regulations depending on the application. It is the consumers responsibility to ensure the appropriate factor is used.

Sta-Lok do not list a “safe working load” as this is dependent on the variable “factor of safety” which must be determined by the user relative to application.

► 1 x 19

The 1x19 construction is the most popular stainless-steel construction as it is suitable for all types of general applications.

High specification 316 stainless steel.




		Diameter		Minimum Breaking Load		
Reference	Wire (MM)	KGF	KN	LBF	KIPS	
W119 - 2	2	336	3.29	741	0.73	
W119 - 2.5	2.5	525	5.14	1,157	1.15	
W119 - 3	3	756	7.41	1,666	1.66	
W119 - 4	4	1,340	13.14	2,954	2.95	
W119 - 5	5	2,100	20.59	4,629	4.62	
W119 - 6	6	3,030	29.70	6,680	6.67	
W119 - 7	7	4,120	40.40	9,083	9.08	
W119 - 8	8	5,251	51.50	11,576	11.57	
W119 - 10	10	8,400	82.37	18,518	18.51	
W119 - 12	12	12,102	118.68	26,680	26.68	
W119 - 14	14	16,473	161.54	36,316	36.31	
W119 - 16	16	20,500	201.03	45,194	45.19	
W119 - 19	19	30,300	297.14	66,800	66.79	
W119 - 22	22	40,686	399.00	89,697	89.69	

*Values shown are for guidance purposes and may vary by manufacturer.

► Compacted Strand

Compacted Strand wires feature high strength and very low stretch, providing this wire with excellent longevity and performance.

High specification 316 stainless steel.




		Diameter		Construction		Minimum Breaking Load			
Reference	Wire (MM)	KGF	KN	LBF	KIPS				
WC - 3	3	1 x 7	999	9.80	2,202	2.20			
WC - 4	4	1 x 7	1,784	17.50	3,933	3.93			
WC - 5	5	1 x 19	2,440	23.93	5,379	5.37			
WC - 6	6	1 x 19	3,549	34.81	7,824	7.82			
WC - 7	7	1 x 19	4,909	48.15	10,822	10.82			
WC - 8	8	1 x 19	6,149	60.31	13,556	13.55			
WC - 10	10	1 x 19	9,769	95.81	21,536	21.53			
WC - 12	12	1 x 19	14,400	141.22	31,746	31.74			
WC - 14	14	1 x 36	19,286	189.14	42,518	42.52			
WC25 - 14	14	1 x 25	19,346	189.72	42,650	42.65			
WC - 16	16	1 x 36	25,582	250.88	56,398	56.40			
WC25 - 16	16	1 x 25	25,661	251.65	56,572	56.73			
WC25 - 19	19	1 x 25	32,076	314.56	70,715	70.71			

*Values shown are for guidance purposes and may vary by manufacturer.

► 7 x 7

The 7x7 construction wire provides greater flexibility versus the 1x19 wire but it is the stronger of the flexible wire rope. It is often found within the marine industry and used widely in the height safety sector.

316 stainless steel.




		Diameter		Minimum Breaking Load			
Reference	Wire (MM)	KGF	KN	LBF	KIPS		
W77 - 2	2	248	2.44	546	0.54		
W77 - 2.5	2.5	388	3.81	855	0.85		
W77 - 3	3	558	5.48	1,230	1.23		
W77 - 4	4	920	9.03	2,028	2.03		
W77 - 5	5	1,437	14.10	3,168	3.16		
W77 - 6	6	2,243	22.00	4,944	4.94		
W77 - 8	8	3,681	36.10	8,115	8.11		
W77 - 10	10	6,212	60.92	13,695	13.69		
W77 - 12	12	8,944	87.72	19,718	19.72		

*Values shown are for guidance purposes and may vary by manufacturer.

7 x 19

The 7x19 construction is the most flexible of the multi-strand wire ropes and is used for a wide range of applications. Often found where the curves, corners or angles are required.
316 stainless steel.



Diameter		Minimum Breaking Load			
Reference	Wire (MM)	KGF	KN	LBF	KIPS
W719 - 2	2	231	2.27	509	0.51
W719 - 2.5	2.5	361	3.55	795	0.79
W719 - 3	3	522	5.12	1,150	1.15
W719 - 4	4	926	9.09	2,041	2.04
W719 - 5	5	1,447	14.20	2,528	3.19
W719 - 6	6	2,090	20.50	4,607	4.60
W719 - 7	7	2,610	25.60	5,754	5.75
W719 - 8	8	3,708	36.37	8,174	8.17
W719 - 10	10	5,791	56.80	12,766	12.70
W719 - 12	12	8,345	81.84	18,397	18.39
W719 - 14	14	11,358	111.39	25,040	25.04
W719 - 16	16	14,836	145.50	32,707	32.70

*Values shown are for guidance purposes and may vary by manufacturer.

PVC Covered

Sta-Lok offer white PVC covered 1x19 or 7x7 stainless steel wire rope as a standard. Perfect where a covering is needed for functional or aesthetic purposes. Common application includes guardrails, theatrical cables and gymnasium cables.
316 stainless steel.



7 x 7



1 x 19

	Construction	Diameter	Minimum Breaking Load			
Reference		Wire (MM)	KGF	KN	LBF	KIPS
WPC7 - 4 / 6	7 x 7	4	920	903	2,028	2.03
WPC1 - 4 / 6	1 x 19	4	1,340	1314	2,954	2.95
WPC1 - 5 / 7	1 x 19	5	2,100	2059	4,629	4.62
WPC1 - 5 / 9	1 x 19	5	2,100	2059	4,629	4.62

*Values shown are for guidance purposes and may vary by manufacturer.

*For larger sizes or any cable information not shown. Please contact us for more detail.



The Clipper Round the World Yacht Race is one of the toughest endurance challenges on the planet. This unique, epic event sees teams battle extreme conditions as they race more than 40,000 nautical miles between ports around the globe in a true test of fortitude and determination.

Sta-Lok was announced as the first Official Standing Rigging Partner for the Clipper 70s in 2017. We returned as the Official Standing Rigging Partner for both the Clipper 2019-20 Race and Clipper 2023-24 Race, supplying bespoke fittings and over 2150 metres of wire to prepare the race fleet.

“

Our fleet of 70-foot ocean racers are put to the ultimate test during their circumnavigation, so it is essential their rigging can stand up to the challenge. With more than 40 years' experience providing rigging hardware, we are very pleased to welcome Sta-Lok as our first Official Standing Rigging Partner.

”

SIR ROBIN KNOX-JOHNSTON

CLIPPER VENTURES NON-EXECUTIVE DIRECTOR &
PRESIDENT AND CLIPPER RACE FOUNDER



Sta-Lok Self-Fit Terminals



The Sta-Lok system is a simple mechanical method of terminating 1x19, 7x7, 7x19 and compacted strand wire ropes.

Over 49 years since its inception, Sta-Lok terminals are used around the world and have gained world-wide recognition for high quality and reliability.

All Sta-Lok terminals can be installed using very simple hand tools and can be used for right hand and left hand lay, stainless steel wire rope from 3mm - 26mm (1/8" - 1").

The Sta-Lok terminal will work under constant loading and variable shock loading. The termination is stronger than the rated breaking load of the wire rope we recommend.

Please note:

1. Sta-Lok Terminals have been designed for use with stainless steel wire ropes. They should not be used with Galvanized wire ropes because galvanic action will cause the wire rope to corrode and fail.
2. Sta-Lok Terminals are not suitable for use with wire ropes with fibre cores.
3. Sta-Lok Terminals are not suitable for lifting slings.

In all situations the Sta-Lok terminal has proven to be totally reliable and is re-usable*

- Manufactured from high specification 316 stainless steel
- Hand fitted instead of machined swage
- Low Maintenance Costs
- Assemble on site, easy to install with simple hand tools
- No pre-measurement required
- A different wedge is required for 1x19, 7 strand and compacted strand wire rope
- All our wedges are laser marked for easy identification and selection

**A new wedge is required when re-terminating wire.*

**Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly.*

How to fit a Sta-Lok Terminal

Stage 1


Slide socket component over wire.

TIP: Wind tape around wire approx. 12" (300mm) from end. This will prevent the socket from sliding down the wire.



Stage 2

Unravel outer strands 2" to 3" (50-76mm) to expose central core.



Stage 3

Slide wedge component over central core of wire rope



Please note:

Threads have been treated with anti-seizing gel to prevent galling.

Where it is decided to use loctite, threads should be cleaned.

You should refer to your chosen thread lock instructions / guidelines.


Stage 4

Reposition outer strands.

Turn outer strands either clockwise or anti-clockwise, depending on the lay of the wire, around the wedge. Ensure approx. 1/8" (2-3mm) of the central core protrudes from the end of the wedge.

Outer strands should be evenly situated around the wedge. Care should be taken to ensure that a strand does not slip into the slit of the wedge.

TIP: Push the socket towards end of wire, while repositioning the outer strands, this will help control. When wire strands are in position, push socket firmly, to hold wires in position.




Stage 5

Final Assembly.


Ensure former component sits in bottom of end fitting. Screw socket assembly into end fitting and tighten with spanners.

The assembly is now complete.

TIP: Undue force is not required to terminate the wire. We would recommend taking the fitting back apart to check that the termination was successful (the outer wires folded over the wedge component).



Sta-Lok Eye




- Sta-Lok Self-Fit Terminal, the reusable alternative to machine swaging
- Quick and easy to install by hand, using basic hand tools
- Packed for 1×19 wire as standard - Different wedges are available to terminate 7 strand & compacted strand wire ropes
- Wedges should be replaced when re-terminating



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Weight (KG)	Weight (LB)	Price (£)
033-03	3 MM	1/8"	17.9	0.705	10.0	0.393	5.0	0.196	6.5	1/4"	0.020	0.044	23.82
033-04	4 MM	5/32"	20.3	0.800	14.7	0.580	5.8	0.230	8.0	5/16"	0.040	0.088	26.53
033-05	5 MM	-	24.4	0.960	18.0	0.710	7.5	0.295	10.0	3/8"	0.080	0.176	30.51
133-05	-	3/16"	24.4	0.960	18.0	0.710	7.5	0.295	10.0	3/8"	0.080	0.176	30.51
133-55-3/8	-	7/32"	32.4	1.276	23.7	0.933	9.5	0.375	10.0	3/8"	0.140	0.309	39.77
133-55-7/16	-	7/32"	31.7	1.248	23.0	0.904	9.5	0.375	11.5	7/16"	0.140	0.309	39.77
133-55-1/2	-	7/32"	31.0	1.219	22.2	0.875	9.5	0.375	13.0	1/2"	0.140	0.309	39.77
033-06-3/8	6 MM	-	32.4	1.276	23.7	0.933	9.5	0.375	10	3/8"	0.14	0.309	39.77
033-06-7/16	6 MM	-	31.7	1.248	23	0.904	9.5	0.375	11.5	7/16"	0.14	0.309	39.77
033-06	6 MM	-	31.0	1.219	22.2	0.875	9.5	0.375	13.0	1/2"	0.140	0.309	39.77
133-06-3/8	-	1/4"	32.4	1.276	23.7	0.933	9.5	0.375	10.0	3/8"	0.140	0.309	39.77
133-06-7/16	-	1/4"	31.7	1.248	23.0	0.904	9.5	0.375	11.5	7/16"	0.140	0.309	39.77
133-06	-	1/4"	31.0	1.219	22.2	0.875	9.5	0.375	13.0	1/2"	0.140	0.309	39.77
033-07	7 MM	9/32"	32.5	1.281	24.6	0.969	10.5	0.413	13.0	1/2"	0.160	0.353	45.06
033-08-1/2	8 MM	5/16"	35.7	1.406	27.0	1.062	12.0	0.472	13.0	1/2"	0.240	0.529	54.97
033-08-5/8	8 MM	5/16"	35.7	1.406	27.0	1.062	13.5	0.531	16.0	5/8"	0.280	0.617	72.98
033-10	10 MM	-	41.1	1.619	29.2	1.150	13.5	0.531	16.0	5/8"	0.340	0.750	82.90
033-10-3/4	10 MM	-	41.1	1.619	29.2	1.150	13.5	0.531	19.5	3/4"	0.400	0.882	82.90
133-10	-	3/8"	41.1	1.619	29.2	1.150	13.5	0.531	16.0	5/8"	0.340	0.750	82.90
133-10-3/4	-	3/8"	41.1	1.619	29.2	1.150	13.5	0.531	19.5	3/4"	0.400	0.882	82.90
133-11	-	7/16"	42.8	1.687	33.3	1.312	19.0	0.748	19.5	3/4"	0.680	1.499	190.91
033-12	12 MM	-	42.8	1.687	33.3	1.312	19.0	0.748	19.5	3/4"	0.680	1.499	190.91
133-12	-	1/2"	42.8	1.687	33.3	1.312	19.0	0.748	19.5	3/4"	0.680	1.499	191.04
133-12-7/8	-	1/2"	42.8	1.687	33.3	1.312	19.0	0.748	22.5	7/8"	0.700	1.543	287.71
033-14	14 MM	9/16"	55.6	2.187	38.1	1.500	20.0	0.788	22.5	7/8"	1.100	2.425	239.95
033-14-1	14 MM	9/16"	55.6	2.187	38.1	1.500	23.0	0.905	26.0	1"	1.220	2.690	266.47
033-16	16 MM	5/8"	59.0	2.326	40.0	1.576	20.0	0.788	22.5	7/8"	1.420	3.131	287.71
033-16-1	16 MM	5/8"	60.0	2.364	40.0	1.576	20.0	0.788	25.4	1"	1.700	3.748	314.24
033-19	19 MM	3/4"	68.3	2.687	49.2	1.937	27.0	1.062	28.6	1 1/8"	2.820	6.217	590.11
033-22	22 MM	7/8"	82.6	3.250	60.3	2.375	33.3	1.312	35.0	1 3/8"	3.960	8.730	703.39
033-26	26 MM	1"	86.0	3.375	60.3	2.375	33.3	1.312	35.0	1 3/8"	5.300	11.684	925.44

Sta-Lok Stud




- Manufactured from high specification 316 stainless steel
- Suitable for right hand and left hand lay wire rope
- Sta-Lok Studs available in Right hand thread only and are supplied with split pin
- Packed for 1×19 wire as standard - Different wedges are available to terminate 7 strand & compacted strand wire ropes



Reference	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
036-03	3 MM	1/8"	1/4"	64.3	2.532	55.6	2.187	0.020	0.044	37.20
036-04-1/4	4 MM	5/32"	1/4"	65.0	2.562	55.6	2.187	0.040	0.088	28.58
036-04	4 MM	5/32"	5/16"	67.5	2.656	58.7	2.312	0.060	0.132	28.58
036-05-5/16	5 MM	-	5/16"	70.6	2.780	58.7	2.312	0.080	0.176	33.85
036-05	5 MM	-	3/8"	78.0	3.062	66.7	2.625	0.080	0.176	33.85
136-05-5/16	-	3/16"	5/16"	65.0	2.562	58.7	2.312	0.080	0.176	33.85
136-05	-	3/16"	3/8"	78.0	3.062	66.7	2.625	0.080	0.176	33.85
136-55	-	7/32"	3/8"	84.0	3.312	66.7	2.625	0.120	0.265	43.75
136-55-7/16	-	7/32"	7/16"	85.0	3.343	74.6	2.937	0.140	0.309	43.75
136-55-1/2	-	7/32"	1/2"	94.0	3.687	81.0	3.187	0.160	0.353	43.75
036-06-3/8	6 MM	-	3/8"	84.0	3.312	66.7	2.625	0.120	0.265	43.77
036-06	6 MM	-	7/16"	93.0	3.656	74.6	2.937	0.140	0.309	43.77
136-06-3/8	-	1/4"	3/8"	84.0	3.312	66.7	2.625	0.120	0.265	43.77
136-06	-	1/4"	7/16"	93.0	3.656	74.6	2.937	0.140	0.309	43.77
136-06-1/2	-	1/4"	1/2"	94.0	3.687	81.0	3.187	0.160	0.353	43.77
036-07-7/16	7 MM	9/32"	7/16"	95.0	3.750	74.6	2.937	0.180	0.397	53.68
036-07	7 MM	9/32"	1/2"	97.0	3.812	81.0	3.187	0.200	0.441	53.68
036-08	8 MM	5/16"	1/2"	98.0	3.875	81.0	3.187	0.240	0.529	63.72
036-08-5/8	8 MM	5/16"	5/8"	110.0	4.343	95.2	3.750	0.300	0.661	63.72
036-10	10 MM	-	5/8"	111.0	4.375	95.2	3.750	0.360	0.794	90.12
036-10-3/4	10 MM	-	3/4"	129.0	5.062	123.8	4.875	0.480	1.058	94.88
136-10	-	3/8"	5/8"	111.0	4.375	95.2	3.750	0.360	0.794	90.12
136-10-3/4	-	3/8"	3/4"	129.0	5.062	123.8	4.875	0.480	1.058	94.88
136-11	-	7/16"	3/4"	139.0	5.468	123.8	4.875	0.760	1.676	221.42
136-11-7/8	-	7/16"	7/8"	168.0	5.625	139.7	5.500	0.880	1.940	221.42
036-12	12 MM	-	3/4"	139.0	5.468	123.8	4.875	0.760	1.676	221.42
036-12-7/8	12 MM	-	7/8"	168.0	5.625	139.7	5.500	0.880	1.940	221.42
136-12	-	1/2"	3/4"	139.0	5.468	123.8	4.875	0.760	1.676	221.42
136-12-7/8	-	1/2"	7/8"	162.0	6.375	139.7	5.500	0.880	1.940	221.42
036-14	14 MM	9/16"	7/8"	170.0	6.687	139.7	5.500	1.300	2.866	257.21
036-14-100	14 MM	9/16"	1"	170.0	6.687	139.7	5.500	1.420	3.131	278.70
036-16	16 MM	5/8"	1"	171.0	6.750	139.7	5.500	1.660	3.660	321.58
036-19	19 MM	3/4"	1 1/8"	213.0	8.375	171.5	6.750	3.140	6.923	696.83
036-22	22 MM	7/8"	1 1/4"	275.0	10.812	227.0	8.937	4.540	10.009	963.30
036-26	26 MM	1"	1 3/8"	284.0	11.187	232.0	9.125	5.100	11.244	1,163.60

Sta-Lok Fork




- Sta-Lok Self-Fit Terminal, the reusable alternative to machine swaging
- Quick and easy to install by hand, using basic hand tools
- Packed for 1×19 wire as standard - Different wedges are available to terminate 7 strand & compacted strand wire ropes
- Wedges should be replaced when re-terminating



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
034-03	3 MM	1/8"	15.5	0.609	10.0	0.393	5.5	0.216	5.0	3/16"	0.040	0.088	28.58
034-04	4 MM	5/32"	21.1	0.830	14.7	0.580	6.4	0.250	6.4	1/4"	0.060	0.132	33.21
034-05	5 MM	-	29.5	1.162	18.0	0.708	8.0	0.315	8.0	5/16"	0.100	0.220	37.85
134-05	-	3/16"	29.5	1.162	18.0	0.708	8.0	0.315	8.0	5/16"	0.100	0.220	37.85
134-55	-	7/32"	37.1	1.459	22.2	0.875	11.1	0.437	10.9	7/16"	0.220	0.485	51.75
034-06	6 MM	-	37.1	1.459	22.2	0.875	11.1	0.437	10.9	7/16"	0.220	0.485	51.75
134-06	-	1/4"	37.1	1.459	22.2	0.875	11.1	0.437	10.9	7/16"	0.220	0.485	51.75
034-07	7 MM	9/32"	33.9	1.333	25.1	0.990	11.1	0.437	10.9	7/16"	0.240	0.529	68.22
034-07-1/2	7 MM	9/32"	43.9	1.729	26.3	1.035	13.7	0.540	12.6	1/2"	0.420	0.926	79.55
034-08	8 MM	5/16"	43.9	1.729	26.3	1.035	13.7	0.540	12.6	1/2"	0.420	0.926	81.61
034-10	10 MM	-	50.1	1.973	29.4	1.155	13.7	0.540	15.6	5/8"	0.620	1.367	102.35
134-10	-	3/8"	50.1	1.973	29.4	1.155	13.7	0.540	15.6	5/8"	0.620	1.367	102.35
134-11	-	7/16"	46.0	1.812	33.3	1.312	19.1	0.750	18.5	3/4"	1.180	2.601	252.70
034-12	12 MM	-	46.0	1.812	33.3	1.312	19.1	0.750	18.5	3/4"	1.180	2.601	252.70
134-12	-	1/2"	46.0	1.812	33.3	1.312	19.1	0.750	18.5	3/4"	1.180	2.601	252.70
034-14	14 MM	9/16"	54.0	2.125	38.1	1.500	20.4	0.803	21.5	7/8"	1.580	3.483	314.24
034-16	16 MM	5/8"	72.7	2.861	40.0	1.576	20.4	0.803	21.5	7/8"	1.980	4.365	401.77
034-19	19 MM	3/4"	92.0	3.622	50.0	1.970	27.8	1.093	27.5	1 1/16"	4.100	9.039	760.42
034-22	22 MM	7/8"	92.0	3.622	60.3	2.375	34.9	1.375	33.0	1 5/16"	5.600	12.346	898.98
034-26	26 MM	1"	92.0	3.622	60.3	2.375	34.9	1.375	33.0	1 5/16"	7.600	16.755	1,076.71

Sta-Lok Toggle Fork




- Manufactured from high specification 316 stainless steel
- Suitable for right hand and left hand lay wire rope
- Packed for 1×19 wire as standard - Different wedges are available to terminate 7 strand & compacted strand wire ropes
- Wedges should be replaced when re-terminating



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
050-04	4 MM	5/32"	48.0	1.890	19.0	0.750	8.4	0.331	7.9	5/16"	0.080	0.176	42.48
050-05-5/16	5 MM	-	48.0	1.890	19.0	0.750	8.4	0.331	7.9	5/16"	0.100	0.220	45.06
050-05	5 MM	-	56.0	2.205	20.0	0.787	9.9	0.390	9.5	3/8"	0.140	0.309	47.12
150-05-5/16	-	3/16"	48.0	1.890	19.0	0.748	8.4	0.453	7.9	5/16"	0.100	0.220	45.06
150-05	-	3/16"	56.0	2.205	20.0	0.787	9.9	0.390	9.5	3/8"	0.140	0.309	47.12
150-55	-	7/32"	56.0	2.205	20.0	0.787	9.9	0.390	9.5	3/8"	0.180	0.397	57.67
150-55-7/16	-	7/32"	61.0	2.406	25.0	0.984	11.5	0.453	11.1	7/16"	0.220	0.485	59.09
050-06-3/8	6 MM	-	56.0	2.205	20.0	0.787	9.9	0.390	9.5	3/8"	0.180	0.397	57.67
050-06	6 MM	-	61.0	2.406	25.0	0.984	11.5	0.453	11.1	7/16"	0.220	0.485	58.96
150-06	-	1/4"	65.9	2.594	28.0	1.102	13.1	0.516	12.7	1/2"	0.300	0.661	57.67
050-07	7 MM	9/32"	70.0	2.755	28.0	1.102	13.1	0.516	12.7	1/2"	0.340	0.750	63.72
050-08	8 MM	5/16"	72.0	2.835	28.0	1.102	13.1	0.516	12.7	1/2"	0.400	0.882	79.55
050-08-5/8	8 MM	5/16"	87.0	3.422	33.0	1.299	16.3	0.642	16.0	5/8"	0.600	1.323	86.25
050-10	10 MM	-	87.0	3.422	33.0	1.299	16.3	0.642	16.0	5/8"	0.680	1.499	109.42
150-10	-	3/8"	87.0	3.422	33.0	1.299	16.3	0.642	16.0	5/8"	0.660	1.455	109.42
050-12	12 MM	-	104.0	4.094	34.0	1.339	25.0	0.984	19.1	3/4"	0.680	1.499	218.85

Sta-Lok Long Stud




- Manufactured from high specification 316 stainless steel
- No pre-measurement needed, self-fitted using simple hand tools
- The additional length of the long stud enables replacement of damaged & unseaworthy swages or seized turnbuckles without having to replace the wire rope



Reference	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
076-04	4 MM	5/32"	5/16"	141.3	5.562	54.0	2.125	0.080	0.176	39.13
076-05-5/16	5 MM	-	5/16"	154.0	6.062	54.0	2.125	0.120	0.265	43.12
076-05	5 MM	-	3/8"	166.6	6.562	66.7	2.625	0.160	0.353	40.41
176-05-5/16	-	3/16"	5/16"	154.0	6.062	54.0	2.125	0.120	0.265	43.12
176-05	-	3/16"	3/8"	166.6	6.562	66.7	2.625	0.160	0.353	40.41
176-55	-	7/32"	3/8"	180.2	7.094	66.7	2.625	0.180	0.397	46.34
176-55-7/16	-	7/32"	7/16"	188.5	7.422	76.2	3.000	0.220	0.485	50.46
076-06-3/8	6 MM	-	3/8"	180.2	7.094	66.7	2.625	0.180	0.397	49.18
076-06	6 MM	-	7/16"	188.5	7.422	76.2	3.000	0.220	0.485	50.46
176-06-3/8	-	1/4"	3/8"	180.2	7.094	66.7	2.625	0.180	0.397	49.18
176-06	-	1/4"	7/16"	188.5	7.422	76.2	3.000	0.220	0.485	50.46
176-06-1/2	-	1/4"	1/2"	225.4	8.875	82.6	3.250	0.300	0.661	64.37
076-07	7 MM	9/32"	1/2"	225.4	8.875	82.6	3.250	0.380	0.838	72.34
076-08	8 MM	5/16"	1/2"	225.4	8.875	82.6	3.250	0.420	0.926	78.27
076-08-5/8	8 MM	5/16"	5/8"	271.5	10.687	95.2	3.750	0.600	1.323	80.32
076-10	10 MM	-	5/8"	272.3	10.719	95.2	3.750	0.700	1.543	110.07
176-10	-	3/8"	5/8"	272.3	10.719	95.2	3.750	0.700	1.543	110.07
176-11	-	7/16"	3/4"	339.7	13.375	115.1	4.531	1.300	2.866	233.39
076-12	12 MM	-	3/4"	339.7	13.375	115.1	4.531	1.300	2.866	233.39
176-12	-	1/2"	3/4"	339.7	13.375	115.1	4.531	1.300	2.866	233.39
076-14	14 MM	9/16"	7/8"	384.2	15.125	139.7	5.500	2.230	4.916	299.69
076-16	16 MM	5/8"	1"	442.0	17.041	139.7	5.500	2.850	6.283	451.45

Sta-Lok Long Eye




- Sta-Lok Self-Fit Terminal, providing instant repair, anywhere
- Quick and easy to install by hand, using basic hand tools
- Packed for 1×19 wire as standard - Different wedges are available to terminate 7 strand & compacted strand wire ropes
- Wedges should be replaced when re-terminating



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Weight (KG)	Weight (LB)	Price (£)
078-05	5 MM	-	106.0	4.187	82.5	3.250	7.5	0.295	9.8	3/8"	0.120	0.265	47.76
178-05	-	3/16"	106.0	4.187	82.5	3.250	7.5	0.295	9.8	3/8"	0.120	0.265	47.76
178-55-3/8	-	7/32"	126.0	4.875	100.0	3.937	9.5	0.375	9.8	3/8"	0.200	0.441	47.12
178-55	-	7/32"	126.0	4.875	100.0	3.937	9.5	0.375	11.5	7/16"	0.200	0.441	47.12
078-06-3/8	6 MM	-	126.0	4.875	100.0	3.937	9.5	0.375	9.8	3/8"	0.200	0.441	54.45
078-06	6 MM	-	126.0	4.875	100.0	3.937	9.5	0.375	11.5	7/16"	0.200	0.441	55.75
078-06-1/2	6 MM	-	147.0	5.750	117.5	4.625	12.0	0.472	13.0	1/2"	0.260	0.573	61.65
178-06-3/8	-	1/4"	126.0	4.875	100.0	3.937	9.5	0.375	9.8	3/8"	0.200	0.441	54.45
178-06	-	1/4"	147.0	5.750	117.5	4.625	12.0	0.472	13.0	1/2"	0.260	0.573	55.75
078-07	7 MM	9/32"	147.0	5.781	117.5	4.625	12.0	0.472	13.0	1/2"	0.300	0.661	65.01
078-08	8 MM	5/16"	147.0	5.781	117.5	4.625	12.0	0.472	13.0	1/2"	0.360	0.794	72.98
078-08-5/8	8 MM	5/16"	175.0	6.889	136.4	5.369	13.5	0.531	16.0	5/8"	0.540	1.190	87.54
078-10	10 MM	-	175.0	6.889	136.4	5.369	13.5	0.531	16.0	5/8"	0.640	1.411	108.07
178-10	-	3/8"	175.0	6.889	136.4	5.369	13.5	0.531	16.0	5/8"	0.640	1.411	106.71
178-11	-	7/16"	254.0	10.000	205.8	8.102	19.0	0.748	19.5	3/4"	1.300	2.866	216.91
078-12	12 MM	-	254.0	10.000	205.8	8.102	19.0	0.748	19.5	3/4"	1.300	2.866	215.49
178-12	-	1/2"	254.0	10.000	205.8	8.102	19.0	0.748	19.5	3/4"	1.300	2.866	215.49
078-14	14 MM	9/16"	330.0	13.000	280.5	11.000	21.0	0.827	22.5	7/8"	2.100	4.630	346.16
078-16	16 MM	5/8"	320.0	12.600	303.6	11.955	24.0	0.945	25.6	1"	2.700	5.952	536.42

Sta-Lok Stemball


- Sta-Lok Self-Fit Terminal, the reusable alternative to swage
- Packed for 1×19 wire as standard - Different wedges are available to terminate 7 strand & compacted strand wire ropes
- Two part assembly – Threadlock recommended
- Can be used with Stemball Cup (page 118) to bring head size up to fit mast / spreader brackets



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	C (MM)	C (Inch)	Weight (KG)	Weight (LB)	Price (£)
146-55	-	7/32"	96.0	3.779	21.2	0.835	0.200	0.441	59.73
046-06	6 MM	-	96.0	3.779	21.2	0.835	0.200	0.441	59.73
146-06	-	1/4"	96.0	3.779	21.2	0.835	0.200	0.441	59.73
046-07	7 MM	9/32"	110.0	4.330	21.6	0.850	0.280	0.617	76.34
046-08	8 MM	5/16"	125.0	4.921	26.5	1.043	0.380	0.838	86.25
046-10	10 MM	-	168.0	6.614	27.6	1.086	0.500	1.102	122.69
146-10	-	3/8"	168.0	6.614	27.6	1.086	0.500	1.102	122.69

Sta-Lok Stay Connector

- Sta-Lok Self-Fit Terminal, providing instant repair, anywhere
- Joins two wires together
- Quick and easy to install by hand, using basic hand tools
- Packed for 1×19 wire as standard - Different wedges are available
- Wedges should be replaced when re-terminating



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	C (MM)	C (Inch)	Weight (KG)	Weight (LB)	Price (£)
072-04	4 MM	5/32"	11.1	0.437	14.3	0.562	0.060	0.132	49.82
072-05	5 MM	-	14.3	0.563	15.9	0.625	0.080	0.176	57.67
172-05	-	3/16"	14.3	0.563	15.9	0.625	0.080	0.176	57.67
172-55	-	7/32"	20.6	0.812	19.1	0.750	0.160	0.353	66.94
072-06	6 MM	-	20.6	0.812	19.1	0.750	0.160	0.353	66.94
172-06	-	1/4"	20.6	0.812	19.1	0.750	0.160	0.353	66.94
072-07	7 MM	9/32"	19.1	0.750	22.2	0.875	0.240	0.529	75.56
072-08	8 MM	5/16"	19.1	0.750	25.4	1.000	0.300	0.661	84.19
072-10	10 MM	-	24.0	0.937	28.6	1.125	0.420	0.926	118.04
172-10	-	3/8"	24.0	0.937	28.6	1.125	0.420	0.926	118.04
172-11	-	7/16"	25.4	1.000	34.9	1.375	0.900	1.984	203.52
072-12	12 MM	-	25.4	1.000	34.9	1.375	0.900	1.984	203.52
172-12	-	1/2"	25.4	1.000	34.9	1.375	0.900	1.984	203.52

Sta-Lok 1x19 Wedge

- Must be replaced where Sta-Lok terminals are being re-used
- Must not be used for Dyform, compacted or 7 strand wire ropes
- Individual wedges are laser marked for easy identification



Reference	Wire Size (MM)	Wire Size (Inch)	Pack (Qty)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
126-03	3 MM	1/8"	5	0.006	0.013	15.31
126-04	4 MM	5/32"	5	0.010	0.022	21.88
126-05	5 MM	-	5	0.015	0.033	22.52
138-05	-	3/16"	5	0.016	0.035	22.52
138-55	-	7/32"	5	0.034	0.075	28.71
126-06	6 MM	-	5	0.150	0.331	26.14
138-06	-	1/4"	5	0.151	0.333	28.71
126-07	7 MM	9/32"	5	0.195	0.430	30.25
126-08	8 MM	5/16"	2	0.054	0.119	15.45
126-10	10 MM	-	2	0.096	0.212	21.38
138-10	-	3/8"	2	0.097	0.214	21.38
138-11	-	7/16"	1	0.048	0.106	14.41
126-12	12 MM	-	1	0.042	0.093	14.41
138-12	-	1/2"	1	0.043	0.095	14.41
126-14	14 MM	9/16"	1	0.069	0.152	25.10
126-16	16 MM	5/8"	1	0.110	0.243	29.22
126-19	19 MM	3/4"	1	0.180	0.397	92.18
126-22	22 MM	7/8"	1	0.260	0.573	99.91
126-26	26 MM	1"	1	0.380	0.838	104.14

Sta-Lok 7 Strand

- Must be replaced where Sta-Lok terminals are being re-used
- For use with 7×7 and 7×19 stainless steel wire construction only
- Laser marked for easy identification



Reference	Wire Size (MM)	Wire Size (Inch)	Pack (Qty)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
127-03	3 MM	1/8"	5	0.004	0.009	23.04
127-04	4 MM	5/32"	5	0.008	0.018	27.17
127-05	5 MM	-	5	0.013	0.029	30.76
139-05	-	3/16"	5	0.013	0.029	30.76
127-06	6 MM	-	5	0.029	0.064	32.57
139-06	-	1/4"	5	0.029	0.064	32.57
127-07	7 MM	9/32"	5	0.017	0.037	35.01
127-08	8 MM	5/16"	2	0.024	0.053	17.77
127-10	10 MM	-	2	0.042	0.093	24.46
139-10	-	3/8"	2	0.020	0.044	24.46
127-12	12 MM	-	1	0.040	0.088	25.10
139-12	-	1/2"	1	0.040	0.040	25.10
127-14	14 MM	9/16"	1	0.069	0.152	25.39
127-16	16 MM	5/8"	1	0.101	0.223	33.73

Sta-Lok Dyform & Compacted Wedges

- Compacted strand and Dyform wire ropes provide higher breaking loads and lower stretch than conventional 1 x 19 wire
- There are 5 different constructions (1×7), (1×19), (1×25), (1×31) and (1×36)
- For use only with Compacted Strand or Dyform wire rope (see table below)



Reference	Wire Size (MM)	Construction	Compacted Strand	Dyform	Pack (Qty)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
154-03C	3 MM	1x7	Yes	No	5	0.005	0.011	21.24
154-04	4 MM	1x7	Yes	Yes	5	0.005	0.011	25.24
154-05	5 MM	1x19	Yes	Yes	5	0.010	0.022	25.88
154-06	6 MM	1x19	No	Yes	5	0.025	0.055	29.99
154-06C	6 MM	1x19	Yes	No	5	0.022	0.049	29.99
154-07	7 MM	1x19	No	Yes	5	0.028	0.062	34.75
154-07C	7 MM	1x19	Yes	No	5	0.025	0.055	34.75
154-08	8 MM	1x19	Yes	Yes	2	0.017	0.037	17.77
154-10	10 MM	1x19	Yes	Yes	2	0.033	0.073	24.46
154-12	12 MM	1x19	No	Yes	1	0.033	0.073	16.48
154-12C19	12 MM	1x19	Yes	No	1	0.030	0.066	16.48
154-14C19	14 MM	1x19	Yes	No	1	0.056	0.123	28.96
154-14	14 MM	1x25	Yes	Yes	1	0.060	0.132	28.96
154-14C36	14 MM	1x36	Yes	No	1	0.060	0.132	28.96
154-16	16 MM	1x25	No	Yes	1	0.110	0.243	33.73
154-16C25	16 MM	1x25	Yes	No	1	0.110	0.243	33.73
154-16C	16 MM	1x36	Yes	No	1	0.110	0.243	33.73
154-19C25	19 MM	1x25	Yes	No	1	0.140	0.309	92.18
154-19	19 MM	1x31	No	Yes	1	0.140	0.309	92.18
154-19C36	19 MM	1x36	Yes	No	1	0.140	0.309	92.18

Sta-Lok Former

- Recommended to replace where Sta-Lok Self-Fit terminals are being re-used
- Manufactured from stainless steel
- Also available as part of Socket, Wedge & Former Kit



Reference	Wire Size (MM)	Wire Size (Inch)	Pack (Qty)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
115-03	3 MM	1/8"	5	0.005	0.011	10.17
115-04	4 MM	5/32"	5	0.005	0.011	10.29
115-05	5 MM	3/16"	5	0.010	0.022	12.09
115-06	6 MM	7/32" & 1/4"	5	0.020	0.044	12.87
115-07	7 MM	9/32"	5	0.025	0.055	15.31
115-08	8 MM	5/16"	2	0.012	0.026	7.34
115-10	10 MM	3/8"	2	0.018	0.040	9.39
115-12	12 MM	7/16" & 1/2"	1	0.020	0.044	10.81
115-14	14 MM	9/16"	1	0.043	0.095	17.77
115-16	16 MM	5/8"	1	0.063	0.139	21.50
115-19	19 MM	3/4"	1	0.121	0.267	85.61
115-22	22 MM	7/8"	1	0.158	0.348	90.12
115-26	26 MM	1"	1	0.198	0.437	104.27

Sta-Lok Socket, Wedge & Former Kit

- Recommended where Sta-Lok terminals are being re-used
- Packed for 1×19 wire as standard
- Different wedges are available to terminate 7 strand & compacted strand wire ropes



Reference	Wire Size (MM)	Wire Size (Inch)	Weight (KG)	Weight (LB)	Price (£)
208-04	4 MM	5/32"	0.020	0.044	14.55
208-05	5 MM	-	0.021	0.046	15.31
211-05	-	3/16"	0.024	0.053	16.61
211-55	-	7/32"	0.015	0.033	23.18
208-06	6 MM	-	0.040	0.088	23.18
211-06	-	1/4"	0.040	0.088	23.18
208-07	7 MM	9/32"	0.060	0.132	24.46
227-07*	7 MM	9/32"	0.058	0.128	27.19
208-08	8 MM	5/16"	0.074	0.163	28.58
208-10	10 MM	-	0.116	0.256	39.77
211-10	-	3/8"	0.116	0.256	39.77
211-11	-	7/16"	0.116	0.256	70.29
211-12	-	1/2"	0.216	0.476	70.29
208-12	12 MM	-	0.217	0.478	70.29
208-14	14 MM	9/16"	0.500	1.102	112.00
208-16	16 MM	5/8"	0.660	1.455	143.28
208-19	19 MM	3/4"	1.320	2.910	307.67
208-22	22 MM	7/8"	1.700	3.748	374.61
208-26	26 MM	1"	2.260	4.980	529.08

*227-07 is a special Terminal Part for Insulators only.



Supajust Eye Toggle.

Sta-Lok Insulators



Insulators are designed to insulate a section of the boat rigging, turning it into an aerial and the ideal antenna for radio transmission and reception.

Sta-Lok Insulators have proven themselves over the years to be an effective and totally reliable method of converting yacht backstays into radio antenna. Backstays are used as it is the longest single length of wire on the boat.

Industry guidance is that the wire between insulators should be a minimum of 7 metres, with the first insulator situated above head height to avoid touching while transmitting.

The main body of the Sta-Lok Insulator consists of an ingenious stainless steel assembly which is embedded in a black weather-proof nylon moulding, designed to exceed the breaking load of the backstay.

Electrical Properties

Impedance Measurement @15MHz, Capacitance 16pF Resistance 400K, D.C.Leakage Resistance @ 30Kv, Greater than 10 G Ohms.


Voltage Proof Test - Withstands 30 Kv applied for 2 hours without breakdown. No change in 15 MHz impedance after voltage proof test.

Please note:

- 1. Insulators should not be used with hydraulic backstay adjusters.
- 2. Yacht rigging and Insulators should be inspected, checked and maintained regularly.

Insulator Body

- Main body of the Sta-Lok Insulator
- Variety of end fittings available




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
206-06	6 MM	7/32" & 1/4"	152.0	6.000	35.0	1.375	0.370	0.816	126.15
206-08	7 MM & 8 MM	9/32" & 5/16"	164.0	6.500	38.0	1.500	0.474	1.045	145.98
206-10	10 MM	3/8"	175.0	6.875	41.0	1.625	0.605	1.334	185.12
206-12	12 MM	7/16" & 1/2"	215.0	8.500	52.0	2.000	1.700	3.748	211.12

Insulators achieve 90% of rated breaking load on compacted strand wire rope.

Insulator Swage to Swage

- Use on standing rigging to provide radio antenna
- Requires professional swaging
- Manufactured from high specification 316 stainless steel




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
193-55	-	7/32"	111.0	4.370	35.0	1.378	0.580	1.279	178.29
093-06	6 MM	-	114.0	4.488	35.0	1.378	0.580	1.279	178.29
193-06	-	1/4"	108.0	4.252	35.0	1.378	0.580	1.279	172.37
093-07	7 MM	9/32"	112.0	4.409	38.0	1.496	0.792	1.746	209.06
093-08	8 MM	5/16"	112.0	4.409	38.0	1.496	0.868	1.914	221.42
093-10	10 MM	-	121.0	4.764	41.0	1.614	1.145	2.524	290.68
193-10	-	3/8"	121.0	4.764	41.0	1.614	1.145	2.524	290.68
193-11	-	7/16"	149.0	5.866	52.0	2.047	1.145	2.524	375.64
093-12	12 MM	-	149.0	5.866	52.0	2.047	2.702	5.957	375.64
193-12	-	1/2"	149.0	5.866	52.0	2.047	2.702	5.957	375.64

Insulators achieve 90% of rated breaking load on compacted strand wire rope.

Insulator Terminal to Terminal

- Use on standing rigging to provide radio antenna
- Incorporates Sta-Lok Self fit termination
- Packed for 1×19 wire as standard
- Different wedges are available to terminate 7 strand and compacted strand wire ropes




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
143-55	-	7/32"	114.0	4.488	35.0	1.375	0.459	1.012	167.35
043-06	6 MM	-	114.0	4.488	35.0	1.375	0.459	1.012	167.35
143-06	-	1/4"	114.0	4.488	35.0	1.375	0.459	1.012	167.35
043-07	7 MM	9/32"	112.0	4.409	38.0	1.500	0.625	1.378	193.99
043-08	8 MM	5/16"	112.0	4.409	38.0	1.500	0.626	1.380	202.24
043-10	10 MM	-	121.0	4.764	41.0	1.625	0.851	1.876	268.01
143-10	-	3/8"	121.0	4.764	41.0	1.625	0.851	1.876	268.01
143-11	-	7/16"	149.0	5.866	52.0	2.000	2.100	4.630	401.00
043-12	12 MM	-	149.0	5.866	52.0	2.000	2.100	4.630	401.00
143-12	-	1/2"	149.0	5.866	52.0	2.000	2.100	4.630	401.00

Insulators achieve 90% of rated breaking load on compacted strand wire rope.

Insulator Swage & Eye

- Use on standing rigging to provide radio antenna
- Requires professional swaging
- Manufactured from high specification 316 stainless steel




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Price (£)
194-55	-	7/32"	228.5	8.996	35.0	1.378	23.0	0.940	9.5	0.375	11.5	7/16"	195.79
094-06	6 MM	-	230.0	9.055	35.0	1.378	22.2	0.875	9.5	0.375	13.0	1/2"	195.79
194-06	-	1/4"	227.0	8.937	35.0	1.378	22.2	0.875	9.5	0.375	13.0	1/2"	195.79
094-07	7 MM	9/32"	242.0	9.528	38.0	1.496	24.6	0.969	10.5	0.413	13.0	1/2"	239.44
094-08	8 MM	5/16"	255.0	10.039	38.0	1.496	27.0	1.062	12.0	0.472	13.0	1/2"	244.85
094-10	10 MM	-	271.0	10.669	41.0	1.614	29.2	1.150	13.5	0.531	16.0	5/8"	326.98
194-10	-	3/8"	271.0	10.669	41.0	1.614	29.2	1.150	13.5	0.531	16.0	5/8"	326.98
194-11	-	7/16"	325.0	12.795	52.0	2.047	33.3	1.312	19.0	0.748	19.5	3/4"	412.08
094-12	12 MM	-	325.0	12.795	52.0	2.000	33.3	1.312	19.0	0.748	19.5	3/4"	412.08
194-12	-	1/2"	325.0	12.795	52.0	2.047	33.3	1.312	19.0	0.748	19.5	3/4"	412.08

Insulators achieve 90% of rated breaking load on compacted strand wire rope.

Insulator Terminal & Eye

- Use on standing rigging to provide Radio Antenna
- Weather proof nylon moulded body
- Incorporates Sta-Lok Self fit termination - Packed for 1×19 wire as standard




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Price (£)
140-55	-	7/32"	177.0	6.969	35.0	1.375	23.0	0.940	9.5	0.375	11.5	7/16"	177.91
091-06	6 MM	-	177.0	6.969	35.0	1.375	22.2	0.875	9.5	0.375	13.0	1/2"	177.91
140-06	-	1/4"	177.0	6.969	35.0	1.375	22.2	0.875	9.5	0.375	13.0	1/2"	177.91
091-07	7 MM	9/32"	189.0	7.449	38.0	1.500	24.6	0.969	10.5	0.413	13.0	1/2"	220.13
091-08	8 MM	5/16"	198.0	7.795	38.0	1.500	27.0	1.062	12.0	0.472	13.0	1/2"	229.65
091-10	10 MM	-	216.0	8.504	41.0	1.625	29.2	1.150	13.5	0.531	16.0	5/8"	313.71
140-10	-	3/8"	216.0	8.504	41.0	1.625	29.2	1.150	13.5	0.531	16.0	5/8"	313.71
140-11	-	7/16"	254.0	10.000	52.0	2.000	33.3	1.312	19.0	0.748	19.5	3/4"	391.48
091-12	12 MM	-	254.0	10.000	52.0	2.000	33.3	1.312	19.0	0.748	19.5	3/4"	391.48
140-12	-	1/2"	254.0	10.000	52.0	2.000	33.3	1.312	19.0	0.748	19.5	3/4"	391.48

Insulators achieve 90% of rated breaking load on compacted strand wire rope.

Insulator Swage Part


- Swage part for insulators
- Screws directly into insulator body
- Requires professional swaging



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	BSF Thread	Weight (KG)	Weight (LB)	Price (£)
213-55	-	7/32"	10.7	0.422	5/8"	0.105	0.231	41.06
203-06	6 MM	-	12.4	0.489	5/8"	0.105	0.231	41.06
213-06	-	1/4"	12.5	0.494	5/8"	0.105	0.231	41.06
203-07	7 MM	9/32"	14.2	0.558	3/4"	0.159	0.351	43.77
203-08	8 MM	5/16"	16.1	0.630	3/4"	0.197	0.434	43.77
203-10	10 MM	-	17.7	0.698	7/8"	0.270	0.595	53.04
213-10	-	3/8"	17.7	0.698	7/8"	0.270	0.595	53.04
203-12	12 MM	-	21.3	0.839	1 1/8"	0.501	1.105	90.89
213-12	-	1/2"	21.3	0.839	1 1/8"	0.501	1.105	90.89

Insulator Eye Kit

- Eye Part for Insulators
- Includes adaptor screw for assembly into insulator body
- Thread lock is recommended to use with this product



Reference	Body Reference	B (MM)	B (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Weight (KG)	Weight (LB)	Price (£)
20907-55	206-06	23.0	0.940	9.5	0.375	11.5	7/16"	0.137	0.302	28.58
20907-06	206-06	22.2	0.875	9.5	0.375	13.0	1/2"	0.137	0.302	28.58
20907-07	206-08	24.6	0.969	10.5	0.413	13.0	1/2"	0.179	0.395	49.69
20907-08	206-08	27.0	1.062	12.0	0.472	13.0	1/2"	0.156	0.344	55.09
20907-08-5/8	206-08	27.0	1.062	13.5	0.531	16.0	5/8"	0.276	0.608	82.25
20907-10	206-10	29.2	1.150	13.5	0.531	16.0	5/8"	0.336	0.741	88.82
20907-12	206-12	33.3	1.312	19.0	0.748	19.5	3/4"	0.486	1.071	110.07

Sta-Lok Swage Terminals



Our stainless steel swage terminals have been designed for use with 1×19, 7×19, 7×7 and compacted strand stainless steel wire rope and can be installed using both rotary & fixed die swaging machines.

Designed with 10 x D hole depths for greater grip and high breaking loads.

Manufactured from 316 stainless steel. All swage terminals are machined to close tolerances to ensure accurate termination.

We have developed a wide selection of products to suit all masts, spreaders and chainplates for metric and inch wire rope from 3mm (1/8") to 26mm (1").

Sta-Lok Swage fittings require professional swaging onto wire rope and are not designed for hand crimping.


Please note:

1. Sta-Lok Swage Terminals have been designed for use with stainless steel wire ropes. They should not be used with Galvanized wire ropes because galvanic action will cause the wire rope to corrode and fail.

2. Sta-Lok Swage Terminals are not suitable for use with fibre ropes or wires with fibre cores.

"Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly."


Swage Stud Open Body



- Suitable for Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Suitable for use with rotary & fixed die swaging machines
- Minimum hole depth 10x wire diameter
- Right hand thread only - Can be used with both open and closed body turnbuckles
- Supplied with split pin

Reference	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
051-03	3 MM	1/8"	1/4"	6.2	0.245	56.0	2.204	0.020	0.044	7.34
051-04-1/4	4 MM	5/32"	1/4"	7.4	0.292	56.0	2.204	0.020	0.044	7.34
051-04	4 MM	5/32"	5/16"	7.4	0.292	60.0	2.362	0.040	0.088	7.34
051-05-5/16	5 MM	3/16"	5/16"	9.0	0.354	60.0	2.362	0.040	0.088	11.33
051-05	5 MM	3/16"	3/8"	9.0	0.354	67.0	2.625	0.060	0.132	11.33
151-55	-	7/32"	3/8"	10.7	0.422	67.0	2.625	0.070	0.154	16.61
151-55-7/16	-	7/32"	7/16"	10.7	0.422	75.0	2.953	0.080	0.176	16.61
051-06-3/8	6 MM	-	3/8"	12.4	0.489	67.0	2.625	0.080	0.176	16.61
051-06	6 MM	-	7/16"	12.4	0.489	75.0	2.953	0.100	0.220	16.61
151-06-3/8	-	1/4"	3/8"	12.5	0.494	67.0	2.625	0.100	0.220	16.61
151-06	-	1/4"	7/16"	12.5	0.494	75.0	2.953	0.100	0.220	16.61
151-06-1/2	-	1/4"	1/2"	12.5	0.494	81.0	3.187	0.140	0.309	16.61
051-07-7/16	7 MM	9/32"	7/16"	14.2	0.558	75.0	2.953	0.140	0.309	25.88
051-07	7 MM	9/32"	1/2"	14.2	0.558	81.0	3.187	0.160	0.353	25.88
051-08	8 MM	5/16"	1/2"	16.1	0.630	81.0	3.187	0.180	0.397	29.22
051-08-5/8	8 MM	5/16"	5/8"	16.1	0.630	100.0	3.937	0.260	0.573	31.15
051-10	10 MM	-	5/8"	17.7	0.698	100.0	3.937	0.300	0.661	41.84
151-10	-	3/8"	5/8"	17.7	0.698	100.0	3.937	0.300	0.661	41.84
151-11	-	7/16"	3/4"	19.6	0.776	124.0	4.875	0.540	1.190	64.37
051-12	12 MM	-	3/4"	21.3	0.839	124.0	4.875	0.540	1.190	64.37
051-12-7/8	12 MM	-	7/8"	21.3	0.839	140.0	5.511	0.680	1.499	116.12
151-12	-	1/2"	3/4"	21.3	0.839	124.0	4.875	0.540	1.190	64.37
051-14	14 MM	9/16"	7/8"	24.9	0.979	140.0	5.511	0.900	1.984	119.34
051-16	16 MM	5/8"	1"	28.0	1.104	162.0	6.375	1.260	2.778	143.28
051-19	19 MM	3/4"	1 1/8"	34.4	1.354	184.0	7.250	2.100	4.630	257.46
051-22	22 MM	7/8"	1 1/4"	40.3	1.588	215.0	8.464	3.220	7.099	394.56
051-26	26 MM	1"	1 3/8"	45.8	1.807	220.0	8.656	4.000	8.818	456.22

Swage Stud Closed Body




- Suitable for use with rotary & fixed die swaging machines
- Designed for Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Right and left hand thread available - Use with closed body turnbuckles only
- Nuts supplied separately (see page 120)



Left Hand Reference	Right Hand Reference	Wire Size (MM)	Wire Size (Inch)	Thread (Metric)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
061-03-M6L	061-03-M6R	3 MM	1/8"	M6	6.2	0.244	56.0	2.206	0.020	0.044	7.34
061-04-M6L	061-04-M6R	4 MM	5/32"	M6	7.4	0.292	56.0	2.206	0.027	0.060	7.34
061-04-M8L	061-04-M8R	4 MM	5/32"	M8	7.4	0.292	60.0	2.364	0.044	0.097	7.34
061-05-M8L	061-05-M8R	5 MM	3/16"	M8	9.0	0.355	60.0	2.364	0.045	0.099	11.33
061-05-M10L	061-05-M10R	5 MM	3/16"	M10	9.0	0.355	67.0	2.640	0.058	0.128	11.33
061-06-M10L	061-06-M10R	6 MM	-	M10	12.4	0.489	67.0	2.640	0.081	0.179	16.61
061-06-M12L	061-06-M12R	6 MM	-	M12	12.4	0.489	81.0	3.191	0.116	0.256	16.61
061-07-M12L	061-07-M12R	7 MM	9/32"	M12	14.2	0.559	81.0	3.191	0.160	0.353	25.88
061-08-M12L	061-08-M12R	8 MM	5/16"	M12	16.1	0.634	81.0	3.191	0.183	0.403	29.22
061-08-M16L	061-08-M16R	8 MM	5/16"	M16	16.1	0.634	100.0	3.940	0.280	0.611	31.15
061-10-M16L	061-10-M16R	10 MM	-	M16	17.7	0.697	100.0	3.940	0.320	0.705	41.84
061-12-M20L	061-12-M20R	12 MM	-	M20	21.4	0.843	124.0	4.886	0.579	1.276	64.37
061-14-M22L	061-14-M22R	14 MM	9/16"	M22	25.0	0.985	140.0	5.516	0.856	1.887	119.34
061-16-M24L	061-16-M24R	16 MM	5/8"	M24	28.2	1.111	162.0	6.378	1.178	2.597	143.28
061-19-M27L	061-19-M27R	19 MM	3/4"	M27	34.5	1.359	184.0	7.250	2.100	4.630	257.46
061-22-M30L	061-22-M30R	22 MM	7/8"	M30	40.3	1.588	200.0	7.880	3.220	7.099	394.56
061-26-M36L	061-26-M36R	26 MM	1"	M36	45.8	1.805	220.0	8.668	4.000	8.818	456.22

Swage Toggle Fork



- Suitable for use with rotary & fixed die swaging machine
- Manufactured from high specification 316 stainless steel
- Use with Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Unique toggle action for articulation in two planes




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
038-03	3 MM	1/8"	6.2	0.245	14.4	0.567	6.4	0.252	6.4	1/4"	0.040	0.088	17.25
038-04	4 MM	5/32"	7.4	0.292	19.0	0.750	8.4	0.331	7.9	5/16"	0.060	0.132	20.60
038-05	5 MM	3/16"	9.0	0.354	20.0	0.787	9.9	0.390	9.5	3/8"	0.100	0.220	21.88
132-55	-	7/32"	10.7	0.422	25.0	0.984	11.5	0.453	11.1	7/16"	0.200	0.441	25.88
038-06	6 MM	-	12.4	0.439	25.0	0.984	11.5	0.453	11.1	7/16"	0.200	0.441	28.58
132-06	-	1/4"	12.5	0.494	28.0	1.102	13.1	0.516	12.7	1/2"	0.250	0.551	28.58
038-07	7 MM	9/32"	14.2	0.558	28.0	1.102	13.1	0.516	12.7	1/2"	0.280	0.617	37.20
038-08	8 MM	5/16"	16.1	0.630	28.0	1.102	13.1	0.516	12.7	1/2"	0.320	0.705	41.84
038-08-5/8	8 MM	5/16"	16.1	0.630	33.0	1.299	16.3	0.642	16.0	5/8"	0.500	1.103	75.56
038-10	10 MM	-	17.7	0.698	33.0	1.299	16.3	0.642	16.0	5/8"	0.560	1.235	75.56
132-10	-	3/8"	17.7	0.698	33.0	1.299	16.3	0.642	16.0	5/8"	0.560	1.235	75.56
132-11	-	7/16"	19.6	0.776	34.0	1.339	19.1	0.752	18.5	3/4"	1.140	2.513	142.64
038-12	12 MM	-	21.3	0.839	34.0	1.339	19.1	0.752	18.5	3/4"	1.140	2.513	142.64
132-12	-	1/2"	21.3	0.839	34.0	1.339	19.1	0.752	18.5	3/4"	1.140	2.513	142.64



Did you know?

Sta-Lok stock and supply industry-leading KOS 1x19 wire.
Available in 100, 200 & 300 metre reels.
Call one of our sales representatives to order yours.

Swage Eye Toggle Fork



- Suitable for use with rotary & fixed die swaging machine
- Manufactured from high specification 316 stainless steel
- Use with Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Modular system
- Unique toggle action for articulation in two planes




Ref	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	F (MM)	F (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
132 ET-11	-	7/16"	19.6	0.776	56.0	2.205	20.0	0.787	66.0	2.598	18.5	3/4"	1.420	3.131	133.88
038 ET-12-16	12 MM	-	21.3	0.839	57.4	2.260	20.0	0.787	66.0	2.598	16.0	0.630	1.420	3.131	133.88
038 ET-12	12 MM	-	21.3	0.839	56.0	2.205	20.0	0.787	66.0	2.598	18.5	3/4"	1.420	3.131	133.88
132 ET-12	-	1/2"	21.3	0.839	56.0	2.205	20.0	0.787	66.0	2.598	18.5	3/4"	1.420	3.131	133.88
038 ET-14-20	14 MM	9/16"	24.9	0.979	64.0	2.520	25.0	0.984	78.0	3.071	20.0	0.787	2.160	4.762	238.66
038 ET-14	14 MM	9/16"	24.9	0.979	63.0	2.480	25.0	0.984	78.0	3.071	21.5	7/8"	2.160	4.762	238.66
038 ET-16-22	16 MM	5/8"	28.0	1.104	69.4	2.732	28.0	1.102	82.0	3.228	22.0	0.866	3.080	6.790	282.44
038 ET-16	16 MM	5/8"	28.0	1.104	67.5	2.657	28.0	1.102	82.0	3.228	25.0	1"	3.080	6.790	282.44
038 ET-19	19 MM	3/4"	34.4	1.354	70.0	2.756	31.5	1.240	89.0	3.504	28.2	1 1/8"	4.700	10.362	517.11
038 ET-22	22 MM	7/8"	40.3	1.588	79.0	3.110	35.0	1.378	98.0	3.858	31.5	1 1/4"	6.800	14.991	630.53
038 ET-26	26 MM	1"	45.8	1.807	98.0	3.858	38.0	1.496	110.0	4.331	34.6	1 3/8"	9.500	20.944	924.16




New Products Added

Sta-Lok now supply downsized pin variations on our 12mm, 14mm and 16mm Swage Eye Toggles.

Swage Eyes




- Suitable for use with rotary & fixed die swaging machine
- Manufactured from high specification 316 stainless steel
- Use with Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Available in 3 different styles, Narrow, Forged and Machined



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Weight (KG)	Weight (LB)	Price (£)
Narrow Eyes											
039N-03	3 MM	1/8"	6.2	0.245	4.0	0.157	6.5	1/4"	0.014	0.031	6.71
039N-04	4 MM	5/32"	7.4	0.292	5.0	0.197	8.5	5/16"	0.022	0.049	8.01
039N-05	5 MM	3/16"	9.0	0.354	6.0	0.236	10.0	3/8"	0.040	0.088	9.30
130N-55	-	7/32"	10.7	0.422	8.0	0.315	11.5	7/16"	0.100	0.220	16.02
039N-06	6 MM	-	12.4	0.488	8.0	0.315	11.5	7/16"	0.100	0.220	16.02
130N-06	-	1/4"	12.5	0.494	8.0	0.315	13.0	1/2"	0.100	0.220	16.02
039N-07	7 MM	9/32"	14.2	0.558	9.0	0.354	13.0	1/2"	0.120	0.265	19.38
039N-08	8 MM	5/16"	16.1	0.630	10.0	0.394	13.0	1/2"	0.180	0.397	26.60
039N-08-5/8	8 MM	5/16"	16.1	0.630	12.0	0.472	16.5	5/8"	0.240	0.529	27.91
039N-10	10 MM	-	17.7	0.698	11.0	0.433	16.2	5/8"	0.260	0.573	47.93
130N-10	-	3/8"	17.7	0.698	11.0	0.433	16.0	5/8"	0.240	0.529	47.93
Forged Eyes											
039-03	3 MM	1/8"	6.2	0.245	5.0	0.197	6.4	1/4"	0.020	0.044	9.03
039-04	4 MM	5/32"	7.4	0.292	6.5	0.256	8.1	5/16"	0.020	0.044	9.72
039-05	5 MM	3/16"	9.0	0.354	7.8	0.307	9.6	3/8"	0.040	0.088	11.19
039-06	6 MM	-	12.4	0.488	9.5	0.374	11.2	7/16"	0.080	0.176	18.08
039-07	7 MM	9/32"	14.2	0.558	11.5	0.453	12.8	1/2"	0.120	0.265	22.25
039-08-1/2	8 MM	5/16"	16.1	0.630	11.5	0.453	12.8	1/2"	0.140	0.309	29.14
039-08	8 MM	5/16"	16.1	0.630	13.5	0.531	14.5	9/16"	0.180	0.397	34.80
039-08-5/8	8 MM	5/16"	16.1	0.630	15.0	0.591	16.1	5/8"	0.180	0.397	46.20
039-10	10 MM	-	17.7	0.698	15.0	0.591	16.1	5/8"	0.240	0.529	47.01
Machined Eyes											
130-11	-	7/16"	19.6	0.773	18.0	0.709	19.5	3/4"	0.520	1.146	86.89
039-12	12 MM	-	21.4	0.842	18.0	0.709	19.5	3/4"	0.520	1.146	86.89
130-12	-	1/2"	21.3	0.839	18.0	0.709	19.5	3/4"	0.520	1.146	86.89
039-14	14 MM	9/16"	25.0	0.979	21.0	0.827	22.5	7/8"	0.800	1.764	149.84
039-16	16 MM	5/8"	28.2	1.104	24.4	0.961	25.7	1"	1.180	2.601	171.72
039-19	19 MM	3/4"	34.5	1.354	27.5	1.083	28.6	1 1/8"	1.900	4.189	376.54
039-22	22 MM	7/8"	40.3	1.588	32.0	1.260	32.0	1 1/4"	2.800	6.173	485.96
039-26	26 MM	1"	45.8	1.807	34.0	1.339	35.0	1 3/8"	3.950	8.708	943.47

Swage Fork




- Suitable for use with rotary & fixed die swaging machine
- Manufactured from high specification 316 stainless steel
- Use with Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Designed to suit most mast chain plates and fixing points



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
035-03	3 MM	1/8"	6.2	0.245	10.0	0.393	6.4	0.252	6.2	1/4"	0.020	0.044	14.67
035-04	4 MM	5/32"	7.4	0.292	14.7	0.580	7.9	0.311	7.7	5/16"	0.060	0.132	15.31
035-05	5 MM	3/16"	9.0	0.354	17.5	0.687	9.5	0.374	9.3	3/8"	0.100	0.220	25.24
135-55	-	7/32"	10.7	0.422	19.0	0.748	11.1	0.437	10.9	7/16"	0.160	0.353	32.57
035-06	6 MM	-	12.4	0.489	19.0	0.748	11.1	0.437	10.9	7/16"	0.160	0.353	32.57
135-06	-	1/4"	12.5	0.494	19.0	0.748	11.1	0.437	10.9	7/16"	0.160	0.353	33.85
035-07	7 MM	9/32"	14.2	0.558	25.1	0.990	11.1	0.437	10.9	7/16"	0.200	0.441	45.83
035-08	8 MM	5/16"	16.1	0.630	25.1	0.990	12.7	0.500	12.6	1/2"	0.340	0.750	48.41
035-10	10 MM	-	17.7	0.698	29.4	1.155	15.9	0.625	15.6	5/8"	0.560	1.235	78.27
135-10	-	3/8"	17.7	0.698	29.4	1.155	15.9	0.625	15.6	5/8"	0.560	1.235	77.63
135-11	-	7/16"	19.6	0.716	33.3	1.312	19.1	0.750	18.5	3/4"	0.900	1.984	206.22
035-12	12 MM	-	21.3	0.839	33.3	1.312	19.1	0.750	18.5	3/4"	0.900	1.984	206.22
135-12	-	1/2"	21.3	0.839	33.3	1.312	19.1	0.750	18.5	3/4"	0.900	1.984	206.22
035-14	14 MM	9/16"	24.9	0.979	38.1	1.500	22.2	0.875	21.5	7/8"	1.600	3.527	291.71
035-16	16 MM	5/8"	28.0	1.104	40.0	1.576	25.4	1.000	25.0	1"	1.700	3.748	356.07
035-19	19 MM	3/4"	34.4	1.354	50.0	1.970	28.6	1.125	28.2	1 1/8"	2.500	5.512	458.79
035-22	22 MM	7/8"	40.3	1.588	60.3	2.375	31.8	1.250	31.5	1 1/4"	3.620	7.981	746.51
035-26	26 MM	1"	45.8	1.807	60.3	2.375	35.0	1.375	34.6	1 3/8"	5.000	11.023	991.24

Swage Shroud




- Suitable for use with rotary & fixed die swaging machine
- Use with Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Fits N840 backing plates
- For Sta-Lok Shroud Backing Plates, see page 119



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	D (MM)	D (Inch)	Weight (KG)	Weight (LB)	Price (£)
045-04	4 MM	5/32"	7.4	0.292	88.2	3.474	7.5	0.295	16.0	0.630	0.040	0.088	18.76
045-05	5 MM	3/16"	9.0	0.354	103.8	4.089	9.1	0.358	19.0	0.748	0.060	0.132	21.58
045-06	6 MM	-	12.4	0.488	130.0	5.118	12.5	0.492	22.0	0.866	0.140	0.309	25.77
145-06	-	1/4"	12.5	0.494	130.0	5.118	12.5	0.492	22.0	0.866	0.140	0.309	25.77
045-07	7 MM	9/32"	14.2	0.558	149.0	5.866	14.3	0.563	28.0	1.102	0.200	0.441	35.48
045-08	8 MM	5/16"	16.1	0.630	168.0	6.614	16.0	0.629	30.0	1.181	0.280	0.617	52.88
045-10	10 MM	-	17.7	0.698	197.0	7.756	17.8	0.700	32.0	1.260	0.380	0.838	63.94
145-10	-	3/8"	17.7	0.698	197.0	7.756	17.8	0.700	32.0	1.260	0.380	0.838	63.94
045-12	12 MM	-	21.4	0.842	241.0	9.488	21.4	0.842	38.0	1.496	0.660	1.455	118.18
145-12	-	1/2"	21.3	0.839	241.0	9.488	21.4	0.842	38.0	1.496	0.660	1.455	118.18

Swage T




- Suitable for use with rotary & fixed die swaging machine
- Manufactured from high specification 316 stainless steel
- Use with Metric and Inch 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- For Sta-Lok T Terminal Backing Plates, see page 119



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	D (MM)	D (Inch)	Weight (KG)	Weight (LB)	Price (£)
044-03	3 MM	-	6.3	0.248	86.0	3.386	6.3	0.248	13.5	0.531	0.025	0.055	12.01
044-04	4 MM	5/32"	7.5	0.295	101.0	3.976	7.5	0.295	16.5	0.650	0.040	0.088	12.66
044-05	5 MM	3/16"	9.0	0.354	112.0	4.409	9.0	0.354	18.5	0.728	0.060	0.132	13.95
044-06	6 MM	-	12.5	0.492	136.0	5.354	12.6	0.496	27.7	1.089	0.140	0.309	18.74
144-06	-	1/4"	12.5	0.492	136.0	5.354	12.6	0.496	27.7	1.089	0.140	0.309	25.96
044-07	7 MM	9/32"	14.2	0.559	148.0	5.826	14.0	0.551	30.0	1.180	0.180	0.397	25.96
044-08	8 MM	5/16"	16.0	0.630	184.0	7.244	16.0	0.630	33.5	1.319	0.300	0.661	39.92
044-10	10 MM	-	17.8	0.701	214.0	8.425	17.8	0.701	36.4	1.434	0.420	0.926	83.19
144-10	-	3/8"	17.8	0.701	214.0	8.425	17.8	0.701	36.4	1.434	0.420	0.926	83.19

Swage Stemball



- Suitable for use with rotary & fixed die swaging machine
- Manufactured from high specification 316 stainless steel
- Use with 1×19, 7 Strand and Compacted Strand wire rope (IWRC)
- Minimum hole depth 10x wire diameter
- Metric and Inch wire ropes
- Can be used with Stemball Cup (page 118) to bring head size up to fit mast / spreader brackets



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	C (MM)	C (Inch)	Weight (KG)	Weight (LB)	Price (£)
042-04	4 MM	5/32"	7.4	0.292	14.6	0.574	0.020	0.044	8.62
042-05Z	5 MM	3/16"	9.0	0.354	14.6	0.574	0.040	0.088	9.27
042-05	5 MM	3/16"	9.0	0.354	18.3	0.720	0.040	0.088	9.39
142-55	-	7/32"	10.7	0.422	21.2	0.835	0.080	0.176	11.97
042-06	6 MM	-	12.4	0.489	21.2	0.835	0.080	0.176	11.97
142-06	-	1/4"	12.5	0.494	21.2	0.835	0.080	0.176	11.97
042-07	7 MM	9/32"	14.2	0.558	21.6	0.850	0.120	0.265	24.59
042-07Z	7 MM	9/32"	14.2	0.558	26.5	1.043	0.130	0.287	21.24
042-08	8 MM	5/16"	16.1	0.630	26.5	1.043	0.140	0.309	27.29
042-10	10 MM	-	17.7	0.698	27.6	1.086	0.240	0.529	39.13
142-10	-	3/8"	17.7	0.698	27.6	1.086	0.240	0.529	39.13
142-11	-	7/16"	19.6	0.776	33.1	1.303	0.340	0.750	63.72
042-12E*	12 MM	-	20.0	0.787	27.9	1.098	0.310	0.683	68.36
042-12	12 MM	-	21.3	0.839	33.1	1.303	0.400	0.882	63.72
142-12	-	1/2"	21.3	0.839	33.1	1.303	0.400	0.882	63.72
042-14	14 MM	9/16"	24.9	0.979	31.8	1.250	0.560	1.235	164.38
042-16	16 MM	5/8"	28.0	1.104	39.4	1.553	0.860	1.896	197.61
042-19	19 MM	3/4"	34.4	1.354	54.0	2.126	1.920	4.233	413.74

*Must be swaged with 12E die only.

Sta-Lok Bronze Turnbuckles



Our ever-popular Sta-Lok Forged Turnbuckles have grown to become one of the leading turnbuckles found on yacht rigging worldwide.

All turnbuckles are forged and machined from high strength bronze alloy and finished in highly polished chromium.

The aerodynamic design of this turnbuckle provides one of the strongest and most elegant bronze turnbuckles on the world market today.

Sta-Lok supply a wide variety of stainless steel threaded end options to suit all rigging layouts.

The following Sta-Lok Bronze Turnbuckle arrangements are available with 1/4" - 3/4" UNF threads and combine our Bronze Turnbuckle body with our stainless steel end fittings.

Please note:

- 1. The following pages show a series of different Bronze Turnbuckle arrangements. If you do not see your preferred assembly, you can combine the Bronze Body with any of our Threaded End Fittings (page 78) by matching the UNF Threads.

"Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly."

Bronze Body

- The aerodynamic design provides one of the strongest and most elegant bronze turnbuckles on the world market today
- Forged from high strength bronze alloy
- Finished in highly polished chromium



Reference	Thread (UNF)	A (MM)	A (Inch)	Adjustment (MM)	Adjustment (Inch)	Weight (KG)	Weight (LB)	Price (£)
B19-14	1/4"	114.0	4.488	76.0	2.992	0.060	0.132	21.88
B19-516	5/16"	123.0	4.843	83.0	3.268	0.080	0.176	25.24
B19-38	3/8"	133.0	5.236	92.0	3.622	0.120	0.265	31.93
B19-716	7/16"	152.0	5.984	100.0	3.937	0.160	0.353	39.77
B19-12	1/2"	163.0	6.417	104.0	4.094	0.220	0.485	43.12
B19-58	5/8"	195.0	7.677	126.0	4.961	0.400	0.882	71.41
B19-34	3/4"	255.0	10.039	168.0	6.615	0.800	1.764	169.15

Bronze Eye Toggle & Blank

- Supplied with a stainless steel Threaded Eye Toggle (ET18) at one end. See page 81 for toggle dimensions



Reference	Thread (UNF)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
B20 ET-34	3/4"	20.0	0.787	18.5	3/4"	168.0	6.615	283.08

Bronze Toggle & Blank


- Supplied with a stainless steel Threaded Strap Toggle (B18) at one end. See page 79 for toggle dimensions



Reference	Thread (UNF)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
B20-14	1/4"	6.4	0.252	6.4	1/4"	76.0	2.992	33.22
B20-516	5/16"	8.4	0.331	7.9	5/16"	83.0	3.268	37.20
B20-38	3/8"	9.9	0.390	9.5	3/8"	92.0	3.622	47.76
B20-716	7/16"	11.5	0.453	11.1	7/16"	100.0	3.937	57.03
B20-12	1/2"	13.1	0.516	12.7	1/2"	104.0	4.094	68.36
B20-58	5/8"	16.3	0.642	16.0	5/8"	126.0	4.961	116.12
B20-34	3/4"	19.1	0.752	18.5	3/4"	168.0	6.615	283.08

Bronze U-Strap Toggle & Blank


- Provided with Forged U Strap toggle (U18) design for longer chain plates. See page 80 for toggle dimensions



Reference	Thread (UNF)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
UB20-14	1/4"	7.6	0.299	6.4	1/4"	76.0	2.992	36.28
UB20-516	5/16"	9.2	0.362	7.9	5/16"	83.0	3.268	40.49
UB20-38	3/8"	10.8	0.425	9.5	3/8"	92.0	3.622	55.69
UB20-716	7/16"	12.3	0.484	11.1	7/16"	100.0	3.937	64.97
UB20-12	1/2"	13.0	0.512	12.7	1/2"	104.0	4.094	66.30
UB20-58	5/8"	18.0	0.709	16.0	5/8"	126.0	4.961	125.19

Bronze Toggle & Swage

- Elegant Bronze Turnbuckle assembly
- Supplied with a Threaded Strap Toggle (B18) at one end and Swage Stud (051) at the other
- Forged from high strength bronze alloy with a high quality polished chromium finish
- Toggle action gives full articulation in two planes



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
B24-03	3 MM	1/8"	1/4"	232.0	156.0	9.134	6.142	6.4	0.252	6.4	1/4"	37.94
B24-144	4 MM	5/32"	1/4"	243.0	167.0	9.567	6.575	6.4	0.252	6.5	1/4"	38.92
B24-04	4 MM	5/32"	5/16"	261.0	178.0	10.276	7.008	8.4	0.331	7.9	5/16"	41.32
B24-5165	5 MM	3/16"	5/16"	261.0	178.0	10.276	7.008	8.4	0.331	7.9	5/16"	45.19
B24-05	5 MM	3/16"	3/8"	284.0	192.0	11.181	7.559	9.9	0.390	9.5	3/8"	51.10
B25-55	-	7/32"	3/8"	289.0	197.0	11.378	7.756	9.9	0.390	9.5	3/8"	56.39
B24-386	6 MM	-	3/8"	289.0	197.0	11.378	7.756	9.9	0.390	9.5	3/8"	56.39
B24-06	6 MM	-	7/16"	316.0	216.0	12.441	8.504	11.5	0.453	11.1	7/16"	65.66
B25-386	-	1/4"	3/8"	294.0	202.0	11.574	7.953	9.9	0.390	9.5	3/8"	56.39
B25-06	-	1/4"	7/16"	316.0	216.0	12.441	8.504	11.5	0.453	11.1	7/16"	65.66
B25-126	-	1/4"	1/2"	343.0	239.0	13.504	9.409	13.1	0.516	12.7	1/2"	81.61
B24-7167	7 MM	9/32"	7/16"	323.0	223.0	12.717	8.780	11.5	0.453	11.1	7/16"	74.92
B24-07	7 MM	9/32"	1/2"	343.0	239.0	13.504	9.409	13.1	0.516	12.7	1/2"	81.61
B24-08	8 MM	5/16"	1/2"	344.0	240.0	13.543	9.449	13.1	0.516	12.7	1/2"	88.82
B24-588	8 MM	5/16"	5/8"	415.0	289.0	16.339	11.378	16.3	0.642	16.0	5/8"	139.28
B24-10	10 MM	-	5/8"	421.0	295.0	16.575	11.614	16.3	0.642	16.0	5/8"	147.91
B25-10	-	3/8"	5/8"	421.0	295.0	16.575	11.614	16.3	0.642	16.0	5/8"	147.91
B25-11	-	7/16"	3/4"	537.0	369.0	21.142	14.528	19.1	0.752	18.5	3/4"	315.65
B24-12	12 MM	-	3/4"	537.0	369.0	21.142	14.528	19.1	0.752	18.5	3/4"	315.65
B25-12	-	1/2"	3/4"	537.0	369.0	21.142	14.528	19.1	0.752	18.5	3/4"	315.65

Bronze Eye Toggle & Swage


- Supplied with a Threaded Eye Toggle (ET18) at one end and a Swage Stud (051) at the other



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
B24 ET-12	12 MM	-	3/4"	583.0	425.0	22.953	16.732	20.0	0.787	18.5	3/4"	347.44
B25 ET-11	-	7/16"	3/4"	583.0	425.0	22.953	16.732	20.0	0.787	18.5	3/4"	347.44
B25 ET-12	-	1/2"	3/4"	583.0	425.0	22.953	16.732	20.0	0.787	18.5	3/4"	347.44

Bronze Eye Toggle & Sta-Lok


- Supplied with a Threaded Eye Toggle (ET18) at one end and a Sta-Lok Self-Fit Stud (036) at the other



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
B22 ET-12	12 MM	-	3/4"	564.0	407.0	22.205	16.024	20.0	0.787	18.5	3/4"	504.49
B23 ET-716	-	7/16"	3/4"	564.0	407.0	22.205	16.024	20.0	0.787	18.5	3/4"	504.49
B23 ET-12	-	1/2"	3/4"	564.0	407.0	22.205	16.024	20.0	0.787	18.5	3/4"	504.49

Bronze Toggle & Sta-Lok


- Elegant Bronze Turnbuckle assembly
- Supplied with a Threaded Strap Toggle (B18) at one end and a Sta-Lok Self-Fit Stud (036) at the other
- Toggle action gives full articulation in two planes



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
B22-03	3 MM	1/8"	1/4"	231.0	155.0	9.094	6.102	6.4	0.252	6.4	1/4"	70.43
B22-144	4 MM	5/32"	1/4"	231.0	155.0	9.094	6.102	6.4	0.252	6.5	1/4"	61.80
B22-04	4 MM	5/32"	5/16"	252.0	169.0	9.921	6.654	8.4	0.331	7.9	5/16"	65.77
B22-5165	5 MM	-	5/16"	254.0	171.0	10.000	6.732	8.4	0.331	7.9	5/16"	71.06
B22-05	5 MM	-	3/8"	282.0	190.0	11.102	7.480	9.9	0.390	9.5	3/8"	81.62
B23-5165	-	3/16"	5/16"	249.5	166.5	9.823	6.555	8.4	0.331	7.9	5/16"	71.06
B23-05	-	3/16"	3/8"	282.0	190.0	11.102	7.480	9.9	0.390	9.5	3/8"	81.62
B23-55	-	7/32"	3/8"	283.0	191.0	11.142	7.520	9.9	0.390	9.5	3/8"	91.53
B22-386	6 MM	-	3/8"	283.0	191.0	11.142	7.520	9.9	0.390	9.5	3/8"	91.53
B22-06	6 MM	-	7/16"	313.0	213.0	12.323	8.386	11.5	0.453	11.1	7/16"	100.80
B23-386	-	1/4"	3/8"	283.0	191.0	11.142	7.520	9.9	0.390	9.5	3/8"	91.53
B23-06	-	1/4"	7/16"	313.0	213.0	13.323	8.386	11.5	0.453	11.1	7/16"	100.80
B23-126	-	1/4"	1/2"	336.0	323.0	13.228	12.717	13.1	0.516	12.7	1/2"	112.13
B22-7167	7 MM	9/32"	7/16"	316.0	216.0	12.441	8.504	11.5	0.453	11.1	7/16"	110.71
B22-07	7 MM	9/32"	1/2"	339.0	235.0	13.346	9.252	13.1	0.516	12.7	1/2"	122.04
B22-08	8 MM	5/16"	1/2"	339.0	235.0	13.346	9.252	13.1	0.516	12.7	1/2"	132.08
B22-588	8 MM	5/16"	5/8"	402.0	276.0	15.827	10.866	16.3	0.642	16.0	5/8"	179.83
B22-10	10 MM	-	5/8"	402.0	276.0	15.827	10.866	16.3	0.642	16.0	5/8"	206.22
B23-10	-	3/8"	5/8"	402.0	276.0	15.827	10.866	16.3	0.642	16.0	5/8"	206.22
B23-11	-	7/16"	3/4"	521.0	353.0	20.512	13.898	19.1	0.752	18.5	3/4"	504.49
B22-12	12 MM	-	3/4"	521.0	353.0	20.512	13.898	19.1	0.752	18.5	3/4"	504.49
B23-12	-	1/2"	3/4"	521.0	353.0	20.512	13.898	19.1	0.752	18.5	3/4"	504.49

Bronze Toggle & Toggle


- Elegant Bronze Turnbuckle assembly,
- Supplied with a Threaded Strap Toggle (B18/B15) at each end
- Toggle action gives full articulation in two planes
- Provides the additional alignment and articulation required on many yacht rigs



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
B41-14	1/4"	248.0	172.0	9.764	6.772	6.4	0.252	6.4	1/4"	50.30
B41-516	5/16"	272.0	189.0	10.709	7.441	8.4	0.331	7.9	5/16"	55.31
B41-38	3/8"	312.0	220.0	12.283	8.661	9.9	0.390	9.5	3/8"	67.72
B41-716	7/16"	349.0	249.0	13.740	9.803	11.5	0.453	11.1	7/16"	79.55
B41-12	1/2"	372.0	268.0	14.646	10.551	13.1	0.516	12.7	1/2"	96.94
B41-58	5/8"	456.0	330.0	17.953	12.992	16.3	0.642	16.0	5/8"	165.94
B41-34	3/4"	580.0	415.0	22.835	16.339	19.1	0.752	18.5	3/4"	409.91

Bronze Eye Toggle & Eye Toggle


- Elegant Bronze Turnbuckle assembly, supplied with a Threaded Eye Toggle (ET18/ET15) at each end



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
B41 ET-34	3/4"	688.0	524.0	27.087	20.630	20.0	0.787	18.5	3/4"	478.11

Bronze Eye Toggle & Fork

- Supplied with a Threaded Eye Toggle (ET18) at one end and a Threaded Fork (B17) at the other
- Elegant design
- Forged from high strength bronze alloy with polished chromium finish
- Toggle action gives full articulation in two planes



Ref	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
B21 ET-34	3/4"	615.0	447.0	24.213	17.598	20.0	0.787	18.5	3/4"	19.1	0.752	18.5	3/4"	501.27

Bronze Toggle & Fork

- Supplied with a Threaded Strap Toggle (B18) at one end and a Threaded Fork End (B17) at the other
- Forged from high strength bronze alloy
- High quality polished chromium finish



Ref	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
B21-14	1/4"	238.0	162.0	9.370	6.378	6.4	0.252	6.4	1/4"	6.4	0.252	6.2	1/4"	61.80
B21-516	5/16"	268.0	185.0	10.551	7.283	8.4	0.331	7.9	5/16"	7.9	0.311	7.7	5/16"	67.71
B21-38	3/8"	302.0	210.0	11.890	8.268	9.9	0.390	9.5	3/8"	9.5	0.374	9.3	3/8"	84.96
B21-716	7/16"	339.0	239.0	13.346	9.409	11.5	0.453	11.1	7/16"	11.1	0.437	10.9	7/16"	100.15
B21-12	1/2"	373.0	269.0	14.685	10.591	13.1	0.516	12.7	1/2"	12.7	0.500	12.6	1/2"	123.46
B21-58	5/8"	441.0	315.0	17.362	12.402	16.3	0.642	16.0	5/8"	15.9	0.625	15.6	5/8"	242.14
B21-34	3/4"	566.0	398.0	22.283	15.669	19.1	0.752	18.5	3/4"	19.1	0.752	18.5	3/4"	501.27

Bronze Fork & Blank

- Elegant design
- Forged from high strength bronze alloy
- High quality polished chromium finish
- Supplied with a Machined Threaded Fork at one end.
For further dimensions, please refer to Threaded Fork End (B16)



Reference	Thread (UNF)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
B30-14	1/4"	6.4	0.252	6.2	1/4"	76.0	2.992	50.46
B30-516	5/16"	7.9	0.311	7.7	5/16"	83.0	3.268	55.75
B30-38	3/8"	9.5	0.374	9.3	3/8"	92.0	3.622	69.12
B30-716	7/16"	11.1	0.437	10.9	7/16"	100.0	3.937	82.90
B30-12	1/2"	12.7	0.500	12.6	1/2"	104.0	4.094	98.23
B30-58	5/8"	15.9	0.625	15.6	5/8"	126.0	4.961	197.44
B30-34	3/4"	19.1	0.752	18.5	3/4"	168.0	6.615	387.35

Bronze Fork & Fork

- Bronze Turnbuckle assembly, supplied with a fully machined Threaded Fork End (B16/B17) at each end



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
B31-14	1/4"	225.0	149.0	8.858	5.866	6.4	0.252	6.2	1/4"	79.04
B31-516	5/16"	260.0	177.0	10.236	6.969	7.9	0.311	7.7	5/16"	86.25
B31-38	3/8"	293.0	201.0	11.535	7.913	9.5	0.374	9.3	3/8"	106.33
B31-716	7/16"	333.0	233.0	13.110	9.173	11.1	0.437	10.9	7/16"	126.02
B31-12	1/2"	368.0	267.0	14.488	10.512	12.7	0.500	12.6	1/2"	153.32
B31-58	5/8"	427.0	301.0	16.811	11.850	15.9	0.625	15.6	5/8"	323.46
B31-34	3/4"	547.0	382.0	21.535	15.039	19.1	0.752	18.5	3/4"	605.55

Sta-Lok Bronze Turnbuckles

Bronze Fork & Swage

- Bronze Turnbuckle assembly, supplied with a fully machined Threaded Fork End (B16) at one end and a Swage Stud (051) at the other
- Forged from high strength bronze alloy
- High quality polished chromium finish




Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
B28-03	3 MM	1/8"	1/4"	221.0	145.0	8.701	5.709	6.4	0.252	6.2	1/4"	57.79
B28-144	4 MM	5/32"	1/4"	228.0	152.0	8.976	5.984	6.4	0.252	6.2	1/4"	57.79
B28-04	4 MM	5/32"	5/16"	251.0	168.0	9.882	6.614	7.9	0.311	7.7	5/16"	63.08
B28-5165	5 MM	3/16"	5/16"	251.0	168.0	9.882	6.614	7.9	0.311	7.7	5/16"	67.08
B28-05	5 MM	3/16"	3/8"	278.0	186.0	10.945	7.323	9.5	0.374	9.3	3/8"	80.45
B29-55	-	7/32"	3/8"	279.0	187.0	10.984	7.362	9.5	0.374	9.3	3/8"	85.73
B28-386	6 MM	-	3/8"	279.0	187.0	10.984	7.362	9.5	0.374	9.3	3/8"	85.73
B28-06	6 MM	-	7/16"	308.0	208.0	12.126	8.189	11.1	0.437	10.9	7/16"	99.50
B29-386	-	1/4"	3/8"	284.0	192.0	11.181	7.559	9.5	0.374	9.3	3/8"	85.73
B29-06	-	1/4"	7/16"	308.0	208.0	12.126	8.189	11.1	0.437	10.9	7/16"	99.50
B29-126	-	1/4"	1/2"	336.0	232.0	13.228	9.134	12.7	0.500	12.6	1/2"	114.82
B28-7167	7 MM	9/32"	7/16"	311.0	211.0	12.244	8.307	11.1	0.437	10.9	7/16"	108.78
B28-07	7 MM	9/32"	1/2"	338.0	234.0	13.307	9.213	12.7	0.500	12.6	1/2"	124.11
B28-08	8 MM	5/16"	1/2"	339.0	235.0	13.346	9.252	12.7	0.500	12.6	1/2"	127.45
B28-588	8 MM	5/16"	5/8"	401.0	277.0	15.787	10.906	15.9	0.625	15.6	5/8"	228.58
B28-10	10 MM	-	5/8"	407.0	283.0	16.024	11.142	15.9	0.625	15.6	5/8"	239.27
B29-10	-	3/8"	5/8"	407.0	283.0	16.024	11.142	15.9	0.625	15.6	5/8"	239.27
B29-11	-	7/16"	3/4"	522.0	358.0	20.551	14.094	19.1	0.752	18.5	3/4"	451.71
B28-12	12 MM	-	3/4"	522.0	358.0	20.551	14.094	19.1	0.752	18.5	3/4"	451.71
B29-12	-	1/2"	3/4"	522.0	358.0	20.551	14.094	19.1	0.752	18.5	3/4"	451.71

Sta-Lok Bronze Turnbuckles

Bronze Fork & Sta-Lok

- Bronze Turnbuckle assembly, supplied with a fully machined Threaded Fork End (B16) at one end and a reusable Sta-Lok Self-Fit Stud (036) at the other
- Forged from high strength bronze alloy
- High quality polished chromium finish



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
B26-03	3 MM	1/8"	1/4"	216.0	140.0	8.504	5.512	6.4	0.252	6.2	1/4"	87.65
B26-144	4 MM	5/32"	1/4"	217.0	141.0	8.543	5.551	6.4	0.252	6.2	1/4"	79.04
B26-04	4 MM	5/32"	5/16"	239.0	156.0	9.409	6.142	7.9	0.311	7.7	5/16"	84.32
B26-5165	5 MM	-	5/16"	244.0	161.0	9.606	6.339	7.9	0.311	7.7	5/16"	89.60
B26-05	5 MM	-	3/8"	273.0	181.0	10.748	7.126	9.5	0.374	9.3	3/8"	102.99
B27-5165	-	3/16"	5/16"	236.5	153.5	9.311	6.043	7.9	0.311	7.7	5/16"	89.60
B27-05	-	3/16"	3/8"	273.0	181.0	10.748	7.126	9.5	0.374	9.3	3/8"	102.99
B27-55	-	7/32"	3/8"	272.0	180.0	10.709	7.087	9.5	0.374	9.3	3/8"	112.90
B26-386	6 MM	-	3/8"	272.0	180.0	10.709	7.087	9.5	0.374	9.3	3/8"	112.90
B26-06	6 MM	-	7/16"	303.0	203.0	11.929	7.992	11.1	0.437	10.9	7/16"	126.67
B27-386	-	1/4"	3/8"	272.0	180.0	10.709	7.087	9.5	0.374	9.3	3/8"	112.90
B27-06	-	1/4"	7/16"	303.0	203.0	11.929	7.992	11.1	0.437	10.9	7/16"	126.67
B27-126	-	1/4"	1/2"	328.0	224.0	12.913	8.819	12.7	0.500	12.6	1/2"	141.99
B26-7167	7 MM	9/32"	7/16"	307.0	207.0	12.087	8.150	11.1	0.437	10.9	7/16"	136.57
B26-07	7 MM	9/32"	1/2"	331.0	227.0	13.031	8.937	12.7	0.500	12.6	1/2"	151.91
B26-08	8 MM	5/16"	1/2"	332.0	228.0	13.071	8.976	12.7	0.500	12.6	1/2"	161.94
B26-588	8 MM	5/16"	5/8"	389.0	263.0	15.315	10.354	15.9	0.625	15.6	5/8"	261.15
B26-10	10 MM	-	5/8"	389.0	263.0	15.315	10.354	15.9	0.625	15.6	5/8"	287.54
B27-10	-	3/8"	5/8"	389.0	263.0	15.315	10.354	15.9	0.625	15.6	5/8"	287.54
B27-11	-	7/16"	3/4"	504.0	339.0	19.843	13.346	19.1	0.752	18.5	3/4"	608.77
B26-12	12 MM	-	3/4"	504.0	339.0	19.843	13.346	19.1	0.752	18.5	3/4"	608.77
B27-12	-	1/2"	3/4"	504.0	339.0	19.843	13.346	19.1	0.752	18.5	3/4"	608.77

Bronze Stemball & Blank

- High quality polished chromium finish
- Supplied with a Threaded Stemball (186) at one end
- Designed to fit most spreader ends, deck cups, tip cups and coquilles
- Stemball Cup (page 118) may be required to bring head size up




Reference	Thread (UNF)	C (MM)	C (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
B50-14	1/4"	14.6	0.574	76.0	2.992	32.57
B50-516	5/16"	18.0	0.709	83.0	3.268	37.86
B50-38	3/8"	20.3	0.799	92.0	3.622	48.52
B50-716	7/16"	20.3	0.799	100.0	3.937	60.37
B50-12	1/2"	26.0	1.024	104.0	4.094	69.65
B50-58	5/8"	27.0	1.063	126.0	4.961	115.17
B50-34	3/4"	28.0	1.102	168.0	6.615	236.22

Bronze

Stemball & Swage

- Bronze Turnbuckle assembly, supplied with a Threaded Stemball (186) at one end and a Swage Stud (051) at the other
- Designed to fit most deck cups, tip cups, coquilles and backing plates
- Stemball Cup (page 118) may be required to bring head size up




Reference	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	C (MM)	C (Inch)	Price (£)
B54-03	3 MM	1/8"	1/4"	235.0	159.0	9.252	6.260	14.6	0.574	39.91
B54-144	4 MM	5/32"	1/4"	241.0	165.0	9.488	6.496	14.6	0.574	39.91
B54-04	4 MM	5/32"	5/16"	255.0	172.0	10.039	6.772	18.0	0.709	45.19
B54-5165	5 MM	3/16"	5/16"	257.0	174.0	10.118	6.850	18.0	0.709	49.19
B54-05	5 MM	3/16"	3/8"	290.0	198.0	11.417	7.795	20.3	0.799	59.86
B54-386	6 MM	-	3/8"	288.0	196.0	11.339	7.717	20.3	0.799	65.13
B54-06	6 MM	-	7/16"	315.0	215.0	12.402	8.465	20.3	0.799	76.98
B54-7167	7 MM	9/32"	7/16"	322.0	222.0	12.677	8.740	20.3	0.799	86.25
B54-07	7 MM	9/32"	1/2"	339.0	235.0	13.346	9.252	26.0	1.024	95.53
B54-08	8 MM	5/16"	1/2"	338.0	234.0	13.307	9.213	26.0	1.024	98.87
B54-588	8 MM	5/16"	5/8"	397.0	271.0	15.630	10.669	27.0	1.063	146.33
B54-10	10 MM	-	5/8"	405.0	279.0	15.945	10.984	27.0	1.063	157.01
B54-12	12 MM	-	3/4"	512.0	348.0	20.157	13.701	28.0	1.102	300.58

Bronze

Eye & Blank

- Elegant design
- Supplied with a Threaded Eye (C770) at one end
- Forged from high strength bronze alloy
- High quality polished chromium finish




Reference	Thread (UNF)	C (MM)	C (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
B40-14	1/4"	8.4	0.331	6.0	0.236	6.4	1/4"	76.0	2.992	33.17
B40-516	5/16"	9.5	0.374	6.5	0.256	8.0	5/16"	83.0	3.268	37.40
B40-38	3/8"	11.0	0.433	7.8	0.307	9.5	3/8"	92.0	3.622	47.65
B40-716	7/16"	12.0	0.472	9.3	0.366	11.1	7/16"	100.0	3.937	60.27
B40-12	1/2"	13.5	0.531	11.5	0.453	12.7	1/2"	104.0	4.094	69.56
B40-58	5/8"	18.3	0.720	13.6	0.535	16.0	5/8"	126.0	4.961	113.56
B40-34*	3/4"	22.5	0.886	18.0	0.709	19.5	3/4"	168.0	6.615	242.78

*Eye machined not forged.

Bronze Eye & Swage

- Bronze Turnbuckle assembly, supplied with a Threaded Eye (C770) at one end and a Swage Stud (051) at the other
- Forged from high strength bronze alloy
- High quality polished chromium finish



Reference	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	C (MM)	C (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
B44-03	3 MM	1/8"	1/4"	8.4	0.331	6.0	0.236	6.4	1/4"	76.0	2.992	40.51
B44-144	4 MM	5/32"	1/4"	8.4	0.331	6.0	0.236	6.4	1/4"	76.0	2.992	40.51
B44-04	4 MM	5/32"	5/16"	9.5	0.374	6.5	0.256	8.0	5/16"	83.0	3.268	44.74
B44-5165	5 MM	3/16"	5/16"	9.5	0.374	6.5	0.256	8.0	5/16"	83.0	3.268	48.73
B44-05	5 MM	3/16"	3/8"	11.0	0.433	7.8	0.307	9.5	3/8"	92.0	3.622	58.98
B44-386	6 MM	-	3/8"	11.0	0.433	7.8	0.307	9.5	3/8"	92.0	3.622	64.24
B44-06	6 MM	-	7/16"	12.0	0.472	9.3	0.366	11.1	7/16"	100.0	3.937	76.87
B44-7167	7 MM	9/32"	7/16"	12.0	0.472	9.3	0.366	11.1	7/16"	100.0	3.937	86.15
B44-07	7 MM	9/32"	1/2"	13.5	0.531	11.5	0.453	12.7	1/2"	104.0	4.094	95.44
B44-08	8 MM	5/16"	1/2"	13.5	0.531	11.5	0.453	12.7	1/2"	104.0	4.094	98.78
B44-588	8 MM	5/16"	5/8"	18.3	0.720	13.6	0.535	16.0	5/8"	126.0	4.961	144.72
B44-10	10 MM	-	5/8"	18.3	0.720	13.6	0.535	16.0	5/8"	126.0	4.961	155.40
B44-12*	12 MM	-	3/4"	22.5	0.886	18.0	0.709	19.5	3/4"	168.0	6.615	307.15

*Eye machined not forged.



Don't see your perfect arrangement or require a different size for Inch Wire?

Refer to Eye & Blank (page 61) and choose your Swage Stud to match from page 37.



Bronze U-Strap Toggle.

Sta-Lok Supajust Turnbuckles



Sta-Lok’s premium range turnbuckles are machined from high specification solid 316 stainless steel and feature permanently sealed threaded bronze inserts in each end.

The beautiful aesthetics and ingenious performance of the Supajust Turnbuckle carries all the hallmarks of Sta-Lok design and engineering.

Providing distinct advantages over other turnbuckles on the market, the Supajust turnbuckle is designed to ensure superb adjustment, even under high load, without the risk of seizing or galling.

Supajust turnbuckles are available with 3/8" – 1 3/8" UNF threads, with a wide range of end fittings for wire rigging from 5mm (3/16") to 26mm (1").


For the most beautiful boats, choose Sta-Lok.

Please note:

- 1. The following pages show a series of different Supajust Turnbuckle arrangements. If you do not see your preferred assembly, you can combine the Supajust Body with any of our Threaded End Fittings (page 78) by matching the UNF Threads.

"Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly."

Supajust Body



- High specification stainless steel turnbuckle with threaded bronze inserts permanently sealed in each end
- Superb adjustment, even under high load without the risk of seizing or galling
- Positive locking is achieved with traditional split pins

Reference	Thread (UNF)	A (MM)	A (Inch)	Adjustment (MM)	Adjustment (Inch)	Weight (KG)	Weight (LB)	Price (£)
S19-38	3/8"	161.0	6.339	77.0	3.032	0.200	0.441	60.37
S19-716	7/16"	161.0	6.339	86.0	3.386	0.220	0.485	65.66
S19-12	1/2"	182.0	7.165	98.0	3.858	0.320	0.705	75.56
S19-58	5/8"	210.0	8.268	108.0	4.252	0.640	1.411	129.37
S19-34	3/4"	248.0	9.764	124.0	4.882	0.880	1.940	169.15
S19-78	7/8"	280.0	11.024	144.0	5.669	1.100	2.425	265.19
S19-100	1"	315.0	12.402	174.0	6.850	1.880	4.145	386.20
S19-118	1 1/8"	365.0	14.370	214.0	8.425	3.020	6.658	629.25
S19-114	1 1/4"	441.0	17.362	260.0	10.236	4.460	9.833	893.14
S19-138	1 3/8"	441.0	17.362	260.0	10.236	5.600	12.346	1,153.57

-

S20-38	3/8"	9.9	0.390	9.5	3/8"	77.0	3.032	68.79
S20-716	7/16"	11.5	0.453	11.1	7/16"	86.0	3.386	75.53
S20-12	1/2"	13.1	0.787	12.7	1/2"	98.0	3.858	87.54
S20-58	5/8"	16.3	0.984	16.0	5/8"	108.0	4.252	156.87
S20-34	3/4"	19.1	0.752	18.5	3/4"	124.0	4.882	269.25

-

S20 ET-34-16	3/4"	20.0	0.787	16.0	0.630	124.0	4.882	335.51
S20 ET-34	3/4"	20.0	0.787	18.5	3/4"	124.0	4.882	335.51
S20 ET-78-20	7/8"	25.0	0.984	20.0	0.787	144.0	5.669	440.47
S20 ET-78	7/8"	25.0	0.984	21.5	7/8"	144.0	5.669	440.47
S20 ET-100-22	1"	28.0	1.102	22.0	0.866	174.0	6.850	630.53
S20 ET-100	1"	28.0	1.102	25.0	1"	174.0	6.850	630.53
S20 ET-118	1 1/8"	31.5	1.240	28.2	1 1/8"	214.0	8.425	1,030.50
S20 ET-114	1 1/4"	35.0	1.378	31.5	1 1/4"	260.0	10.236	1,512.21
S20 ET-138	1 3/8"	38.0	1.496	34.6	1 3/8"	260.0	10.236	1,971.01

-

US20-38	3/8"	10.8	0.425	9.5	3/8"	77.0	3.032	64.20
US20-716	7/16"	12.3	0.484	11.1	7/16"	86.0	3.386	78.54
US20-12	1/2"	13.0	0.512	12.7	1/2"	98.0	3.858	90.60
US20-58	5/8"	18.0	0.709	16.0	5/8"	108.0	4.252	176.97

[illegible]

Supajust Toggle & Swage

- High Specification stainless steel open body turnbuckle with threaded bronze inserts
- Supplied with a Threaded Strap Toggle (B18) at one end and Swage Stud (051) at the other
- Toggle action gives full articulation in two planes



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
S24-05	5 MM	3/16"	3/8"	302.0	228.0	11.890	8.976	9.9	0.390	9.5	3/8"	73.96
S25-55	-	7/32"	3/8"	305.0	228.0	12.008	8.976	9.9	0.390	9.5	3/8"	76.22
S24-386	6 MM	-	3/8"	305.0	228.0	12.008	8.976	9.9	0.390	9.5	3/8"	76.22
S24-06	6 MM	-	7/16"	317.0	231.0	12.480	9.094	11.5	0.453	11.1	7/16"	83.50
S25-386	-	1/4"	3/8"	310.0	233.0	12.205	9.173	9.9	0.390	9.5	3/8"	76.22
S25-06	-	1/4"	7/16"	317.0	231.0	12.480	9.094	11.5	0.453	11.1	7/16"	83.50
S25-126	-	1/4"	1/2"	354.0	256.0	13.937	10.079	13.1	0.516	12.7	1/2"	104.14
S24-7167	7 MM	9/32"	7/16"	321.0	235.0	12.638	9.252	11.5	0.453	11.1	7/16"	85.21
S24-07	7 MM	9/32"	1/2"	356.0	258.0	14.016	10.157	13.1	0.516	12.7	1/2"	107.49
S24-08	8 MM	5/16"	1/2"	356.0	258.0	14.016	10.157	13.1	0.516	12.7	1/2"	110.07
S24-588	8 MM	5/16"	5/8"	413.0	305.0	16.260	12.008	16.3	0.642	16.0	5/8"	171.65
S24-10	10 MM	-	5/8"	421.0	313.0	16.575	12.323	16.3	0.642	16.0	5/8"	172.77
S25-10	-	3/8"	5/8"	421.0	313.0	16.575	12.323	16.3	0.642	16.0	5/8"	172.77
S24-12	12 MM	-	3/4"	517.0	393.0	20.354	15.472	19.1	0.752	18.5	3/4"	315.65
S25-11	-	7/16"	3/4"	517.0	393.0	20.354	15.472	19.1	0.752	18.5	3/4"	315.65
S25-12	-	1/2"	3/4"	517.0	393.0	20.354	15.472	19.1	0.752	18.5	3/4"	315.65



Did you know?

Sta-Lok stock and supply industry-leading KOS 1x19 wire.
Available in 100, 200 & 300 metre reels.

Call one of our sales representatives to order yours.

Supajust Eye Toggle & Swage

- Threaded Bronze Inserts ensure superb adjustment without seizing or galling
- Swivel toggle action allows full articulation in two planes
- Supplied with a Threaded Eye Toggle (ET18) at one end and Swage Stud (051) at the other end



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
S25 ET-11-16	-	7/16"	3/4"	571.0	451.0	22.480	17.756	20.0	0.787	16.0	0.630	377.81
S25 ET-11	-	7/16"	3/4"	571.0	451.0	22.480	17.756	20.0	0.787	18.5	3/4"	377.81
S24 ET-12-16	12 MM	-	3/4"	571.0	451.0	22.480	17.756	20.0	0.787	16.0	0.630	377.81
S24 ET-12	12 MM	-	3/4"	571.0	451.0	22.480	17.756	20.0	0.787	18.5	3/4"	377.81
S25 ET-12-16	-	1/2"	3/4"	571.0	451.0	22.480	17.756	20.0	0.787	16.0	0.630	377.81
S25 ET-12	-	1/2"	3/4"	571.0	451.0	22.480	17.756	20.0	0.787	18.5	3/4"	377.81
S24 ET-14-20	14 MM	9/16"	7/8"	646.0	500.0	25.433	19.685	25.0	0.984	20.0	0.787	546.34
S24 ET-14	14 MM	9/16"	7/8"	646.0	500.0	25.433	19.685	25.0	0.984	21.5	7/8"	546.34
S24 ET-16-22	16 MM	5/8"	1"	728.0	553.0	28.661	19.685	28.0	1.102	22.0	0.866	773.81
S24 ET-16	16 MM	5/8"	1"	728.0	553.0	28.661	21.772	28.0	1.102	25.0	1"	773.81
S24 ET-19	19 MM	3/4"	1 1/8"	835.0	620.0	32.874	24.409	31.5	1.240	28.2	1 1/8"	1,287.96
S24 ET-22	22 MM	7/8"	1 1/4"	968.0	708.0	38.110	27.874	35.0	1.378	31.5	1 1/4"	1,906.77
S24 ET-26	26 MM	1"	1 3/8"	1030.0	770.0	40.551	30.315	38.0	1.496	34.6	1 3/8"	2,427.24




New Products Added

Sta-Lok now supply downsized pin variations on our 3/4", 7/8" and 1" Supajust Eye Toggle variations.

Supajust Toggle & Sta-Lok


- High Specification stainless steel open body turnbuckle with threaded bronze inserts
- Supplied with a Threaded Strap Toggle (B18) at one end and a Sta-Lok Self-Fit Stud (036) at the other
- Toggle action gives full articulation in two planes



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
S22-05	5 MM	-	3/8"	299.0	222.0	11.772	8.740	9.9	0.390	9.5	3/8"	102.65
S23-05	-	3/16"	3/8"	299.0	222.0	11.772	8.740	9.9	0.390	9.5	3/8"	102.65
S23-55	-	7/32"	3/8"	299.0	222.0	11.772	8.740	9.9	0.390	9.5	3/8"	112.54
S22-386	6 MM	-	3/8"	299.0	222.0	11.772	8.740	9.9	0.390	9.5	3/8"	112.55
S22-06	6 MM	-	7/16"	310.0	224.0	12.205	8.819	11.5	0.453	11.1	7/16"	119.29
S23-386	-	1/4"	3/8"	299.0	222.0	11.772	8.740	9.9	0.390	9.5	3/8"	112.55
S23-06	-	1/4"	7/16"	310.0	224.0	12.205	8.819	11.5	0.453	11.1	7/16"	119.29
S23-126	-	1/4"	1/2"	346.0	248.0	13.622	9.764	13.1	0.516	12.7	1/2"	131.31
S22-7167	7 MM	9/32"	7/16"	314.0	228.0	12.362	8.976	11.5	0.453	11.1	7/16"	129.20
S22-07	7 MM	9/32"	1/2"	346.0	248.0	13.622	9.764	13.1	0.516	12.7	1/2"	141.22
S22-08	8 MM	5/16"	1/2"	347.0	249.0	13.661	9.803	13.1	0.516	12.7	1/2"	151.26
S22-588	8 MM	5/16"	5/8"	399.0	291.0	15.709	11.457	16.3	0.642	16.0	5/8"	220.59
S22-10	10 MM	-	5/8"	400.0	292.0	15.748	11.496	16.3	0.642	16.0	5/8"	246.98
S23-10	-	3/8"	5/8"	400.0	292.0	15.748	11.496	16.3	0.642	16.0	5/8"	246.98
S22-12	12 MM	-	3/4"	499.0	375.0	19.646	14.764	19.1	0.752	18.5	3/4"	490.67
S23-11	-	7/16"	3/4"	499.0	375.0	19.646	14.764	19.1	0.752	18.5	3/4"	490.67
S23-12	-	1/2"	3/4"	499.0	375.0	19.646	14.764	19.1	0.752	18.5	3/4"	490.67

Supajust Eye Toggle & Sta-Lok

- Threaded Bronze Inserts ensure superb adjustment without seizing or galling
- Swivel toggle action allows full articulation in two planes
- Supplied with a Threaded Eye Toggle (ET18) at one end and Sta-Lok Self-Fit Stud (036) at the other end




Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
S23 ET-11	-	7/16"	3/4"	554.0	430.0	21.811	16.929	20.0	0.787	18.5	3/4"	556.92
S22 ET-12	12 MM	-	3/4"	554.0	430.0	21.811	16.929	20.0	0.787	18.5	3/4"	556.92
S23 ET-12	-	1/2"	3/4"	554.0	430.0	21.811	16.929	20.0	0.787	18.5	3/4"	556.92
S22 ET-14	14 MM	9/16"	7/8"	623.0	479.0	24.528	18.858	25.0	0.984	21.5	7/8"	697.80
S22 ET-16	16 MM	5/8"	1"	683.0	507.0	26.890	19.961	28.0	1.102	25.0	1"	952.11
S22 ET-19	19 MM	3/4"	1 1/8"	815.0	599.0	32.087	23.583	31.5	1.240	28.2	1 1/8"	1,727.32
S22 ET-22	22 MM	7/8"	1 1/4"	975.0	717.0	38.386	28.228	35.0	1.378	31.5	1 1/4"	2,475.52
S22 ET-26	26 MM	1"	1 3/8"	992.0	732.0	39.055	28.819	38.0	1.496	34.6	1 3/8"	3,134.62



Supajust Toggle & Toggle


- Premium Sta-Lok turnbuckle arrangement, supplied with a Threaded Strap Toggle (B18/B15) at each end



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
S41-38	3/8"	328.0	251.0	12.913	9.882	9.9	0.390	9.5	3/8"	88.74
S41-716	7/16"	352.0	266.0	13.858	10.472	11.5	0.453	11.1	7/16"	98.05
S41-12	1/2"	384.0	286.0	15.118	11.260	13.1	0.516	12.7	1/2"	116.12
S41-58	5/8"	456.0	348.0	17.953	13.701	16.3	0.642	16.0	5/8"	206.69
S41-34	3/4"	568.0	442.0	22.362	17.402	19.1	0.752	18.5	3/4"	396.08

Supajust Toggle & Fork


- Premium open body turnbuckle arrangement, supplied with a Threaded Strap Toggle (B18) at one end and a Threaded Fork End (B17) at the other



Ref	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
S21-38	3/8"	318.0	241.0	12.520	9.488	9.9	0.390	9.5	3/8"	9.5	0.374	9.3	3/8"	105.98
S21-716	7/16"	340.0	254.0	13.386	10.000	11.5	0.453	11.1	7/16"	11.1	0.437	10.9	7/16"	118.65
S21-12	1/2"	379.0	281.0	14.921	11.063	13.1	0.516	12.7	1/2"	12.7	0.500	12.6	1/2"	142.64
S21-58	5/8"	435.0	327.0	17.126	12.874	16.3	0.642	16.0	5/8"	15.9	0.625	15.6	5/8"	282.90
S21-34	3/4"	544.0	422.0	21.417	16.614	19.1	0.752	18.5	3/4"	19.1	0.752	18.5	3/4"	487.46

Supajust Eye Toggle & Eye Toggle


- High Specification stainless steel open body turnbuckle arrangement, supplied with a Threaded Eye Toggle (ET18/ET15) at each end



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
S41 ET-34	3/4"	673.0	549.0	26.496	21.614	20.0	0.787	18.5	3/4"	528.57
S41 ET-78	7/8"	747.0	603.0	29.409	23.740	25.0	0.984	21.5	7/8"	688.19
S41 ET-100	1"	850.0	675.0	33.465	26.575	28.0	1.102	25.0	1"	984.53
S41 ET-118	1 1/8"	980.0	766.0	38.583	30.157	31.5	1.240	28.2	1 1/8"	1,665.99
S41 ET-114	1 1/4"	1131.0	874.0	44.528	34.409	35.0	1.378	31.5	1 1/4"	2,368.55
S41 ET-138	1 3/8"	1210.0	950.0	47.638	37.402	38.0	1.496	34.6	1 3/8"	3,114.13

Supajust Eye Toggle & Fork

- High Specification stainless steel open body turnbuckle arrangement, supplied with a Threaded Eye Toggle at one end (ET18) and a Threaded Machined Fork (B17) at the other end



Ref	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
S21 ET-34	3/4"	595.0	475.0	23.425	18.701	20.0	0.787	18.5	3/4"	19.1	0.752	18.5	3/4"	553.70
S21 ET-78	7/8"	680.0	536.0	26.772	21.102	25.0	0.984	21.5	7/8"	22.2	0.874	21.5	7/8"	674.51
S21 ET-100	1"	766.0	592.0	30.157	23.307	28.0	1.102	25.0	1"	25.4	1.000	25.0	1"	1,015.04
S21 ET-118	1 1/8"	891.0	677.0	35.079	26.654	31.5	1.240	28.2	1 1/8"	28.6	1.125	28.2	1 1/8"	1,556.23
S21 ET-114	1 1/4"	1044.0	786.0	41.102	30.945	35.0	1.378	31.5	1 1/4"	31.8	1.252	31.5	1 1/4"	2,247.52
S21 ET-138	1 3/8"	1133.0	873.0	44.606	34.370	38.0	1.496	34.6	1 3/8"	35.0	1.378	34.6	1 3/8"	2,920.42

Supajust Fork & Blank

- High Specification stainless steel open body turnbuckle, supplied with a Threaded Machined Fork at one end




Reference	Thread (UNF)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
S30-38	3/8"	9.5	0.374	9.3	3/8"	77.0	3.032	97.57
S30-716	7/16"	11.1	0.437	10.9	7/16"	86.0	3.386	108.78
S30-12	1/2"	12.7	0.500	12.6	1/2"	98.0	3.858	130.66
S30-58	5/8"	15.9	0.625	15.6	5/8"	108.0	4.252	255.40
S30-34	3/4"	19.1	0.752	18.5	3/4"	124.0	4.882	387.35
S30-78	7/8"	22.2	0.874	21.5	7/8"	144.0	5.669	499.22
S30-100	1"	25.4	1.000	25.0	1"	174.0	6.850	770.71
S30-118	1 1/8"	28.6	1.125	28.2	1 1/8"	214.0	8.425	1,154.98
S30-114	1 1/4"	31.8	1.252	31.5	1 1/4"	260.0	10.236	1,628.45
S30-138	1 3/8"	35.0	1.378	34.6	1 3/8"	260.0	10.236	2,102.97



Supajust Fork & Swage


- High Specification stainless steel open body turnbuckle with threaded bronze inserts
- Supplied with a fully machined Threaded Fork End (B16) at one end and a Swage Stud (051) at the other



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
S28-05	5 MM	3/16"	3/8"	294.0	217.0	11.575	8.543	9.5	0.374	9.3	3/8"	108.90
S29-55	-	7/32"	3/8"	294.0	217.0	11.575	8.543	9.5	0.374	9.3	3/8"	114.17
S28-386	6 MM	-	3/8"	294.0	217.0	11.575	8.543	9.5	0.374	9.3	3/8"	114.17
S28-06	6 MM	-	7/16"	308.0	222.0	12.126	8.740	11.1	0.437	10.9	7/16"	125.38
S29-386	-	1/4"	3/8"	299.0	222.0	11.772	8.740	9.5	0.374	9.3	3/8"	114.17
S29-06	-	1/4"	7/16"	308.0	222.0	12.126	8.740	11.1	0.437	10.9	7/16"	125.38
S29-126	-	1/4"	1/2"	351.0	253.0	13.819	9.961	12.7	0.500	12.6	1/2"	147.26
S28-7167	7 MM	9/32"	7/16"	317.0	231.0	12.480	9.094	11.1	0.437	10.9	7/16"	134.66
S28-07	7 MM	9/32"	1/2"	353.0	255.0	13.898	10.039	12.7	0.500	12.6	1/2"	156.54
S28-08	8 MM	5/16"	1/2"	354.0	256.0	13.937	10.079	12.7	0.500	12.6	1/2"	159.88
S28-588	8 MM	5/16"	5/8"	399.0	291.0	15.709	11.457	15.9	0.625	15.6	5/8"	286.55
S28-10	10 MM	-	5/8"	406.0	298.0	15.984	11.732	15.9	0.625	15.6	5/8"	297.24
S29-10	-	3/8"	5/8"	406.0	298.0	15.984	11.732	15.9	0.625	15.6	5/8"	297.24
S29-11	-	7/16"	3/4"	502.0	377.0	19.764	14.843	19.1	0.752	18.5	3/4"	451.71
S28-12	12 MM	-	3/4"	502.0	377.0	19.764	14.843	19.1	0.752	18.5	3/4"	451.71
S29-12	-	1/2"	3/4"	502.0	377.0	19.764	14.843	19.1	0.752	18.5	3/4"	451.71
S28-14	14 MM	9/16"	7/8"	576.0	432.0	22.677	17.008	22.2	0.874	21.5	7/8"	618.56
S28-16	16 MM	5/8"	1"	645.0	471.0	25.394	18.543	25.4	1.000	25.0	1"	913.99
S28-19	19 MM	3/4"	1 1/8"	762.0	547.0	30.000	21.535	28.6	1.125	28.2	1 1/8"	1,412.44
S28-22	22 MM	7/8"	1 1/4"	882.0	627.0	34.724	24.685	31.8	1.252	31.5	1 1/4"	2,023.02
S28-26	26 MM	1"	1 3/8"	953.0	693.0	37.520	27.283	35.0	1.378	34.6	1 3/8"	2,559.18

Supajust Fork & Sta-Lok


- Supajust body, supplied with a fully machined Threaded Fork End (B16) at one end and a reusable Sta-Lok Self-Fit Stud (036) at the other
- Threaded Bronze Inserts ensure superb adjustment without seizing or galling



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
S26-05	5 MM	-	3/8"	291.0	214.0	11.457	8.425	9.5	0.374	9.3	3/8"	131.43
S27-05	-	3/16"	3/8"	291.0	214.0	11.457	8.425	9.5	0.374	9.3	3/8"	131.43
S27-55	-	7/32"	3/8"	292.0	215.0	11.496	8.465	9.5	0.374	9.3	3/8"	141.33
S26-386	6 MM	-	3/8"	292.0	215.0	11.496	8.465	9.5	0.374	9.3	3/8"	141.33
S26-06	6 MM	-	7/16"	302.0	216.0	11.890	8.504	11.1	0.437	10.9	7/16"	152.55
S27-386	-	1/4"	3/8"	292.0	215.0	11.496	8.465	9.5	0.374	9.3	3/8"	141.33
S27-06	-	1/4"	7/16"	302.0	216.0	11.890	8.504	11.1	0.437	10.9	7/16"	152.55
S27-126	-	1/4"	1/2"	349.0	251.0	13.740	9.882	12.7	0.500	12.6	1/2"	174.43
S26-7167	7 MM	9/32"	7/16"	306.0	220.0	12.047	8.661	11.1	0.437	10.9	7/16"	162.46
S26-07	7 MM	9/32"	1/2"	349.0	251.0	13.740	9.882	12.7	0.500	12.6	1/2"	184.34
S26-08	8 MM	5/16"	1/2"	346.0	248.0	13.622	9.764	12.7	0.500	12.6	1/2"	194.39
S26-588	8 MM	5/16"	5/8"	383.0	276.0	15.079	10.866	15.9	0.625	15.6	5/8"	319.12
S26-10	10 MM	-	5/8"	384.0	277.0	15.118	10.906	15.9	0.625	15.6	5/8"	345.51
S27-10	-	3/8"	5/8"	384.0	277.0	15.118	10.906	15.9	0.625	15.6	5/8"	345.51
S26-12	12 MM	-	3/4"	486.0	361.0	19.134	14.213	19.1	0.752	18.5	3/4"	608.77
S27-11	-	7/16"	3/4"	486.0	361.0	19.134	14.213	19.1	0.752	18.5	3/4"	608.77
S27-12	-	1/2"	3/4"	486.0	361.0	19.134	14.213	19.1	0.752	18.5	3/4"	608.77
S26-14	14 MM	9/16"	7/8"	559.0	415.0	22.008	16.339	22.2	0.874	21.5	7/8"	756.44
S26-16	16 MM	5/8"	1"	613.0	437.0	24.134	17.205	25.4	1.000	25.0	1"	1,092.29
S26-19	19 MM	3/4"	1 1/8"	742.0	526.0	29.213	20.709	28.6	1.125	28.2	1 1/8"	1,851.81
S26-22	22 MM	7/8"	1 1/4"	891.0	631.0	35.079	24.843	31.8	1.252	31.5	1 1/4"	2,591.75
S26-26	26 MM	1"	1 3/8"	915.0	655.0	36.024	25.787	35.0	1.378	34.6	1 3/8"	3,266.57

Supajust Fork & Fork

- Supajust Turnbuckle assembly, supplied with a fully machined Threaded Fork End (B16/B17) at each end



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
S31-38	3/8"	307.0	242.0	12.087	9.528	9.5	0.374	9.3	3/8"	134.77
S31-716	7/16"	333.0	247.0	13.110	9.724	11.1	0.437	10.9	7/16"	151.91
S31-12	1/2"	383.0	285.0	15.079	11.220	12.7	0.500	12.6	1/2"	185.76
S31-58	5/8"	427.0	319.0	16.811	12.559	15.9	0.625	15.6	5/8"	381.42
S31-34	3/4"	535.0	411.0	21.063	16.181	19.1	0.752	18.5	3/4"	605.55
S31-78	7/8"	605.0	461.0	23.819	18.150	22.2	0.874	21.5	7/8"	733.26
S31-100	1"	686.0	512.0	27.008	20.157	25.4	1.000	25.0	1"	1,155.24
S31-118	1 1/8"	814.0	602.0	32.047	23.701	28.6	1.125	28.2	1 1/8"	1,680.71
S31-114	1 1/4"	952.0	692.0	37.480	27.244	31.8	1.252	31.5	1 1/4"	2,363.77
S31-138	1 3/8"	1056.0	796.0	41.575	31.339	35.0	1.378	34.6	1 3/8"	3,052.36

Sta-Lok Threaded End Fittings



Need that perfect replacement part or can't quite find a turnbuckle arrangement that matches your requirements?

Sta-Lok threaded ends are machined to the highest standard from high specification 316 stainless steel alloys and are perfectly suited for use with our Stainless Steel, Bronze and Supajust turnbuckle bodies.

Our wide range of threaded ends span from 1/4" to 1 3/8" UNF, providing options to suit all yacht rigging layouts.

Generally speaking, the end fittings are supplied as a Left Hand UNF thread where used as a turnbuckle assembly. Where available, the right hand variants are provided.


Please note:

- 1. All Threaded End Fittings are supplied with split pins to ensure positive locking with all open body turnbuckle assemblies
- 2. Should you require any further dimensional details, please make contact with our sales team

**Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly.*

Threaded Strap Toggle End


- Full Articulation in two planes
- Manufactured from high specification 316 stainless steel
- Suitable for all Sta-Lok turnbuckles
- Supplied with split pin



Left Hand Reference	Right Hand Reference	Thread (UNF)	B (MM)	B (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
B18-14	B15-14	1/4"	14.4	0.567	6.4	0.252	57.0	2.244	6.4	1/4"	0.040	0.088	17.08
B18-516	B15-516	5/16"	19.0	0.750	8.4	0.331	60.0	2.362	7.9	5/16"	0.060	0.132	18.10
B18-38	B15-38	3/8"	20.0	0.787	9.9	0.390	70.0	2.756	9.5	3/8"	0.100	0.220	19.96
B18-716	B15-716	7/16"	25.0	0.984	11.5	0.453	75.0	2.953	11.1	7/16"	0.160	0.353	22.52
B18-12	B15-12	1/2"	28.0	1.102	13.1	0.516	81.0	3.189	12.7	1/2"	0.260	0.573	28.58
B18-58	B15-58	5/8"	33.0	1.299	16.3	0.642	89.0	3.504	16.0	5/8"	0.480	1.058	49.82
B18-34	B15-34	3/4"	34.0	1.339	19.1	0.752	125.0	4.921	18.5	3/4"	0.700	1.543	126.83

Threaded U Strap & Toggle End


- Full Articulation in two planes
- Manufactured from high specification 316 stainless steel
- Supplied with split pin
- Forged T Design
- Ideal for longer chain plates



Left Hand Reference	Right Hand Reference	Thread (UNF)	B (MM)	B (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
U18-14	U15-14	1/4"	20.0	0.787	7.6	0.299	60.0	2.362	6.4	1/4"	0.040	0.088	24.54
U18-516	U15-516	5/16"	25.0	0.984	9.2	0.362	66.0	2.598	7.9	5/16"	0.060	0.132	25.19
U18-38	U15-38	3/8"	28.0	1.102	10.8	0.425	70.0	2.756	9.5	3/8"	0.100	0.220	34.48
U18-716	U15-716	7/16"	32.0	1.260	12.3	0.484	77.0	3.031	11.1	7/16"	0.160	0.352	38.45
U18-12	U15-12	1/2"	34.0	1.339	13.0	0.512	81.0	3.189	12.7	1/2"	0.260	0.572	39.47
U18-58	U15-58	5/8"	43.0	1.693	18.0	0.709	99.0	3.898	16.0	5/8"	0.460	1.012	65.90

Threaded Eye Toggle End

- Elegant design
- Manufactured from high specification 316 stainless steel
- Toggle action allows full articulation in two planes
- Ideal for longer chain plates
- Stronger than the wire ropes



Left Hand Reference	Right Hand Reference	Thread (UNF)	B (MM)	B (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	F (MM)	F (Inch)	P (MM)	P (Inch)	Price (£)
ET18-34-16	ET15-34-16	3/4"	57.4	2.260	20.0	0.787	128.0	5.039	66.0	2.598	16.0	0.630	193.06
ET18-34	ET15-34	3/4"	56.0	2.205	20.0	0.787	128.0	5.039	66.0	2.598	18.5	3/4"	193.06
ET18-78-20	ET15-78-20	7/8"	64.0	2.520	25.0	0.984	140.0	5.512	78.0	3.071	20.0	0.787	247.73
ET18-78	ET15-78	7/8"	63.0	2.480	25.0	0.984	140.0	5.512	78.0	3.071	21.5	7/8"	247.73
ET18-100-22	ET15-100-22	1"	69.4	2.732	28.0	1.102	156.0	6.142	82.0	3.228	22.0	0.866	354.00
ET18-100	ET15-100	1"	67.5	2.657	28.0	1.102	156.0	6.142	82.0	3.228	25.0	1"	354.00
ET18-118	ET15-118	1 1/8"	70.0	2.756	31.5	1.240	180.0	7.087	89.0	3.504	28.2	1 1/8"	635.49
ET18-114	ET15-114	1 1/4"	79.0	3.110	35.0	1.378	215.0	8.464	98.0	3.858	31.5	1 1/4"	856.34
ET18-138	ET15-138	1 3/8"	98.0	3.858	38.0	1.496	220.0	8.661	110.0	4.331	34.6	1 3/8"	1,143.11





New Products Added

Sta-Lok now supply downsized pin variations on our 3/4", 7/8" and 1" Threaded Eye Toggles.

Threaded Fork End



- Elegant design
- Fully machined from 316 stainless steel
- Stronger than the wire rope
- Suitable for all turnbuckles
- Supplied with split pin



Left Hand Reference	Right Hand Reference	Thread (UNF)	B (MM)	B (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
B16-14	B17-14	1/4"	10.0	0.394	6.4	0.252	54.0	2.126	6.2	1/4"	0.020	0.044	28.58
B16-516	B17-516	5/16"	14.7	0.579	7.9	0.311	59.0	2.323	7.7	5/16"	0.060	0.132	30.51
B16-38	B17-38	3/8"	17.5	0.689	9.5	0.374	67.0	2.638	9.3	3/8"	0.120	0.265	37.20
B16-716	B17-716	7/16"	22.2	0.874	11.1	0.437	76.0	2.992	10.9	7/16"	0.180	0.397	43.12
B16-12	B17-12	1/2"	27.4	1.080	12.7	0.500	83.0	3.268	12.6	1/2"	0.300	0.661	55.09
B16-58	B17-58	5/8"	29.4	1.157	15.9	0.625	95.0	3.750	15.6	5/8"	0.500	1.102	126.02
B16-34	B17-34	3/4"	33.3	1.313	19.1	0.752	124.0	4.875	18.5	3/4"	0.860	1.896	218.21
B16-78	B17-78	7/8"	38.1	1.500	22.2	0.874	148.0	5.813	21.5	7/8"	1.200	2.646	234.04
B16-100	B17-100	1"	40.0	1.575	25.4	1.000	162.0	6.375	25.0	1"	1.700	3.748	384.52
B16-118	B17-118	1 1/8"	50.0	1.970	28.6	1.125	190.0	7.480	28.2	1 1/8"	2.400	5.291	525.73
B16-114	B17-114	1 1/4"	60.0	2.362	31.8	1.252	224.0	8.812	31.5	1 1/4"	3.660	8.069	735.31
B16-138	B17-138	1 3/8"	70.0	2.756	35.0	1.378	232.0	9.134	34.6	1 3/8"	4.200	9.259	949.40

Threaded Eye End

- Suitable for all Sta-Lok turnbuckles
- Left hand thread only
- Supplied with split pin



Forged Eye




Machined Eye

Reference	Thread (UNF)	C (MM)	C (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	H (MM)	H (Inch)	Weight (KG)	Weight (LB)	Price (£)
Forged												
C770-14	1/4"	8.4	0.331	6.0	0.236	47.0	1.850	6.4	1/4"	0.014	0.031	11.29
C770-516	5/16"	9.5	0.374	6.5	0.256	57.0	2.244	8.0	5/16"	0.020	0.044	12.17
C770-38	3/8"	11.0	0.433	7.8	0.307	68.0	2.677	9.5	3/8"	0.040	0.088	15.72
C770-716	7/16"	12.0	0.472	9.3	0.366	75.0	2.953	11.1	7/16"	0.080	0.176	20.50
C770-12	1/2"	13.5	0.531	11.5	0.453	90.0	3.543	12.7	1/2"	0.120	0.264	26.44
C770-58	5/8"	18.3	0.720	13.6	0.535	100.0	3.937	16.0	5/8"	0.240	0.528	42.16
Machined												
C770-34	3/4"	22.5	0.886	18.0	0.709	128.0	5.039	19.5	3/4"	0.520	1.144	73.64
C770-78	7/8"	25.5	1.004	21.0	0.827	140.0	5.512	22.5	7/8"	0.800	1.760	118.04
C770-100	1"	31.9	1.256	24.4	0.961	156.0	6.142	25.4	1"	1.180	2.596	158.48
C770-118	1 1/8"	36.5	1.437	27.5	1.083	180.0	7.087	28.6	1 1/8"	1.720	3.784	215.49
C770-114	1 1/4"	38.1	1.500	30.5	1.201	215.0	8.465	31.8	1 1/4"	2.480	5.456	340.11
C770-138	1 3/8"	42.9	1.689	33.3	1.311	220.0	8.661	35.0	1 3/8"	2.930	6.446	389.16

Threaded Shroud

- Manufactured from high specification 316 stainless steel
- Designed to be used with turnbuckle systems
- Fits N840 backing plates
- Left hand thread only
- Supplied with split pin




Reference	Thread (UNF)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	Weight (KG)	Weight (LB)	Price (£)
188-12	1/2"	14.4	0.566	90.0	3.625	27.0	1.062	0.220	0.484	94.04
188-858	5/8"	16.0	0.628	90.0	3.625	30.0	1.181	0.280	0.616	129.17
188-1058	5/8"	17.5	0.689	100.0	4.000	32.0	1.259	0.400	0.880	148.23
188-34	3/4"	21.4	0.843	120.0	4.750	38.0	1.496	0.720	1.584	213.94

Notes:


Threaded T

- Manufactured from high specification 316 stainless steel
- Design to be used with turnbuckle systems
- Universal fitting – works with a broad selection of backing plates
- Left hand thread only
- Supplied with split pin




Reference	Thread (UNF)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	Weight (KG)	Weight (LB)	Price (£)
187-14	1/4"	6.3	0.248	48.0	1.889	13.5	0.532	0.020	0.044	33.97
187-516	5/16"	9.0	0.354	57.0	2.244	18.5	0.728	0.060	0.132	38.63
187-38	3/8"	12.6	0.496	62.0	2.440	27.5	1.083	0.120	0.264	41.98
187-716	7/16"	12.6	0.496	67.0	2.638	27.5	1.083	0.140	0.308	45.21
187-12	1/2"	14.2	0.559	80.0	3.150	29.4	1.155	0.180	0.396	45.99
187-58	5/8"	17.8	0.701	100.0	4.000	35.5	1.398	0.400	0.880	111.11

Threaded Stemball




- Suitable for all Sta-Lok turnbuckles
- Manufactured from high specification 316 stainless steel
- If Stemball Cups are required please see Product Reference – 042C, page 118
- Left hand thread only



Reference	Thread (UNF)	C (MM)	C (Inch)	E (MM)	E (Inch)	Weight (KG)	Weight (LB)	Price (£)
186-14	1/4"	14.6	0.575	57.0	2.244	0.020	0.044	10.69
186-516	5/16"	18.0	0.709	63.0	2.480	0.040	0.088	12.62
186-516Z	5/16"	13.2	0.520	63.0	2.480	0.040	0.088	12.62
186-38	3/8"	20.3	0.799	69.0	2.717	0.060	0.132	16.61
186-716	7/16"	20.3	0.799	75.0	2.953	0.100	0.220	20.60
186-12	1/2"	26.0	1.024	80.0	3.150	0.140	0.308	26.53
186-58	5/8"	27.0	1.063	98.0	3.858	0.220	0.484	43.77
186-34	3/4"	28.0	1.102	128.0	5.039	0.380	0.836	67.08
186-78	7/8"	34.0	1.339	140.0	5.512	0.640	1.408	106.07
186-100	1"	39.5	1.556	156.0	6.141	0.980	2.156	129.89
186-118	1 1/8"	54.8	2.156	182.0	7.165	1.540	3.388	278.45

Turnbuckle Extension Bar



- Maximise the adjustment on backstays and cap shrouds by joining two turnbuckles
- Manufactured from high specification 316 stainless steel
- Will assemble with standard open and closed body turnbuckles
- UNF Threads – left hand one end and right hand the other
- Supplied with split pins

Reference	Thread (UNF)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
C280-716	7/16"	75.0	2.953	0.140	0.309	65.66
C280-12	1/2"	81.0	3.189	0.220	0.485	76.34
C280-58	5/8"	100.0	3.937	0.340	0.750	116.12
C280-34	3/4"	135.0	5.315	0.640	1.411	152.55
C280-78	7/8"	140.0	5.512	0.860	1.896	173.15
C280-100	1"	156.0	6.142	1.260	2.778	202.88






Tip Cup




- Sta-Lok Terminals Spreader End Tip Cups are precision engineered from marine grade stainless steel
- The three part design works to prevent thread galling increasing both the reliability and longevity of the tip cup
- Each Spreader End Tip Cup is supplied with two Stemball Swages (042) and a Stemball and Swage Forged Bronze Turnbuckle to ensure that all you need is available and easy to order
- Standard diagonal angles for Sta-Lok Spreader End Tip Cups are 75°/80° but the product can be custom finished to meet your specifications
- Utilising a fully machined system allows for easy installation and the supplied Stemball heads give perfect wire alignment
- To be used with wire rope rigging only
- Please Note: Mast manufacturer must be specified prior to order to ensure correct specification



Reference	Lower Wire Diameter (MM)	Upper Wire Diameter (MM)	Diagonal Wire Diameter (MM)	Diagonal Angle	A (MM)	A (Inch)	B (MM)	B (Inch)	Price (£)
MTC-141210 75	14 MM	12 MM	10 MM	75	36.0	1.417	90.0	3.543	1,516.46
MTC-141210 80	14 MM	12 MM	10 MM	80	36.0	1.417	90.0	3.543	1,516.46
MTC-161410 75	16 MM	14 MM	10 MM	75	36.0	1.417	90.0	3.543	1,744.31
MTC-161410 80	16 MM	14 MM	10 MM	80	36.0	1.417	90.0	3.543	1,744.31
MTC-161412 75	16 MM	14 MM	12 MM	75	36.0	1.417	90.0	3.543	2,243.79
MTC-161412 80	16 MM	14 MM	12 MM	80	36.0	1.417	90.0	3.543	2,243.79
MTC-161610 75	16 MM	16 MM	10 MM	75	36.0	1.417	90.0	3.543	2,170.42
MTC-161610 80	16 MM	16 MM	10 MM	80	36.0	1.417	90.0	3.543	2,170.42
MTC-161612 75	16 MM	16 MM	12 MM	75	36.0	1.417	90.0	3.543	2,250.23
MTC-161612 80	16 MM	16 MM	12 MM	80	36.0	1.417	90.0	3.543	2,250.23
MTC-191612 75	19 MM	16 MM	12 MM	75	36.0	1.417	90.0	3.543	2,458.77
MTC-191612 80	19 MM	16 MM	12 MM	80	36.0	1.417	90.0	3.543	2,458.77

Double Jaw Toggle

- Manufactured from high specification 316 stainless steel
- Designed to overcome small additional length requirements on existing cable assemblies
- Use with turnbuckle forks to provide full articulation



Ref	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
DJT-14	16.0	0.630	20.0	0.787	7.6	0.299	6.7	0.264	6.4	1/4"	0.020	0.044	23.95
DJT-516	19.0	0.748	25.0	0.984	9.2	0.362	8.3	0.327	7.9	5/16"	0.060	0.132	25.24
DJT-38	22.2	0.875	28.0	1.102	10.8	0.425	9.9	0.390	9.5	3/8"	0.080	0.176	25.88
DJT-716	28.6	1.126	32.0	1.260	12.3	0.484	11.5	0.453	11.1	7/16"	0.120	0.264	34.25
DJT-12	32.0	1.260	34.0	1.339	13.0	0.512	13.0	0.512	12.7	1/2"	0.180	0.396	39.77
DJT-58	38.1	1.500	52.0	2.047	18.0	0.709	16.3	0.642	16.0	5/8"	0.360	0.792	57.67
DJT-34	48.0	1.890	81.0	3.189	20.0	0.790	19.5	0.768	18.5	3/4"	0.900	1.980	157.83
DJT-78	60.0	2.362	92.0	3.622	25.0	1.000	23.0	0.906	21.5	7/8"	1.420	3.124	238.02
DJT-100	64.0	2.520	99.0	3.898	28.0	1.130	26.0	1.024	25.0	1"	1.860	4.092	317.58
DJT-118	70.0	2.756	105.0	4.134	31.5	1.250	29.0	1.142	28.2	1 1/8"	2.850	6.270	507.20
DJT-114	80.0	3.150	119.0	4.685	35.0	1.375	34.0	1.339	31.5	1 1/4"	4.020	8.844	727.72
DJT-138	90.0	3.543	140.0	5.512	38.0	1.500	35.0	1.378	34.6	1 3/8"	5.430	11.946	878.34

Eye & Jaw Bar Toggle

- Manufactured from high specification 316 stainless steel
- Designed to overcome small additional length requirements on existing cable assemblies
- Use with turnbuckle forks to provide full articulation



Ref	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
S-14BT	29.1	1.146	13.2	0.520	6.0	0.236	6.4	0.252	6.4	1/4"	6.2	1/4"	0.020	0.044	19.31
S-516BT	38.6	1.520	14.7	0.580	7.4	0.290	7.9	0.311	7.9	5/16"	7.7	5/16"	0.060	0.132	20.60
S-38BT	49.1	1.933	17.5	0.687	8.9	0.349	9.5	0.375	10.0	3/8"	9.3	3/8"	0.080	0.176	25.88
S-716BT	60.4	2.378	21.9	0.861	10.4	0.409	11.1	0.437	11.4	7/16"	10.9	7/16"	0.120	0.265	38.49
S-12BT	74.1	2.917	27.4	1.080	12.0	0.500	12.7	0.500	13.0	1/2"	12.6	1/2"	0.180	0.397	67.08
S-58BT	81.6	3.213	29.2	1.150	13.5	0.531	15.9	0.626	16.0	5/8"	15.6	5/8"	0.360	0.794	84.83
S-34BT	92.2	3.630	33.3	1.311	18.4	0.724	19.1	0.752	19.1	3/4"	18.5	3/4"	0.900	1.984	201.60
S-78BT	110.6	4.354	38.1	1.500	20.0	0.788	22.2	0.874	22.2	7/8"	21.5	7/8"	1.420	3.131	217.42
S-100BT	121.3	4.776	40.0	1.576	23.5	0.925	25.4	1.000	25.4	1"	25.0	1"	1.860	4.101	291.07
S-118BT	148.4	5.843	50.0	1.970	27.0	1.062	28.6	1.125	28.6	1 1/8"	28.2	1 1/8"	2.850	6.283	479.39
S-114BT	174.6	6.875	60.0	2.362	30.7	1.210	32.0	1.260	31.8	1 1/4"	31.5	1 1/4"	4.020	8.863	600.02
S-138BT	185.0	7.282	70.0	2.756	33.3	1.311	35.0	1.378	35.0	1 3/8"	34.6	1 3/8"	5.430	11.971	733.26

Sta-Lok Guard Rail & Life Line Fittings



For your safety and peace of mind. Sta-Lok have designed an extensive range of guard rail and lifeline hardware.

Our wide range of 316 stainless steel hardware is designed to fit 3mm (1/8") to 6mm (1/4") stainless steel wire.

Sta-Lok Guard Rail & Life Line Fittings are designed to fit most pushpit / pulpit designs on both sailing yachts and powerboats alike.

This range of fittings is also perfect for commercial or architectural balustrading infill projects.


Please note:

- 1. Guard Rail and Life Line Fittings should not be used for yacht standing rigging
- 2. All fittings are designed for machine swaging

**Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly.*

Swage Welded Fork


- Marine grade stainless steel fittings
- For use with guard rails
- Wide jaw fits most stanchions and pushpit/pulpits



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Price (£)
WSF-03	3 MM	-	6.3	0.250	13.0	0.512	9.5	0.374	6.0	1/4"	14.08
WSF-04	4 MM	5/32"	7.5	0.295	15.0	0.591	11.0	0.433	8.0	5/16"	17.95
WSF-05	5 MM	3/16"	9.0	0.354	19.0	0.748	12.0	0.472	9.5	3/8"	19.38
WSF-06	6 MM	-	12.6	0.495	25.0	0.984	14.0	0.551	12.0	1/2"	29.97
WSF-07	7 MM	9/32"	14.2	0.559	25.0	0.984	14.0	0.551	12.0	1/2"	36.53
WSF-08	8 MM	5/16"	16.0	0.630	25.0	0.984	14.0	0.551	12.0	1/2"	45.58

Swage Guard Rail Fork


- Marine grade stainless steel fittings
- For use with guard rails
- Manufactured as a two part weld free assembly
- Supplied with split ring



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
G035-04	4 MM	5/32"	7.4	0.292	15.0	0.591	11.1	0.433	7.7	5/16"	0.044	0.097	14.67
G035-05	5 MM	3/16"	9.0	0.354	15.0	0.591	11.1	0.433	7.7	5/16"	0.052	0.115	15.95

Guard Rail Adjuster Fork & Swage


- Marine grade stainless steel fittings
- Provides weight and length reduction on conventional turnbuckles
- Swivel action - adjust one end only
- Adjustment +/- 16mm (5/8")
- Nuts not supplied
- Supplied with split ring
- Supplied with standard swage stud



Ref	Wire Size (MM)	Thread (UNF)	Thread (Metric)	A (MM)	A (Inch)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
G28-04	4 MM	5/16"	-	7.4	0.292	15.0	0.591	11.1	0.437	7.7	5/16"	0.110	0.243	28.85
G28-04-M8	4 MM	-	M8	7.4	0.292	15.0	0.591	11.1	0.437	7.7	5/16"	0.110	0.243	28.85
G28-05	5 MM	5/16"	-	9.0	0.354	15.0	0.591	11.1	0.437	7.7	5/16"	0.120	0.265	33.84
G28-05-M8	5 MM	-	M8	9.0	0.354	15.0	0.591	11.1	0.437	7.7	5/16"	0.120	0.265	33.84

Guard Rail Adjuster Fork & Blank


- Marine grade stainless steel fittings
- Provides weight and length reduction on conventional turnbuckles
- Designed to fit most chain plates and fixing point
- Supplied with split ring
- Nuts not supplied



Reference	Thread (UNF)	Thread (Metric)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Price (£)
G30-516	5/16"	-	15.0	0.591	11.1	0.437	7.7	5/16"	21.71
G30-M8	-	M8	15.0	0.591	11.1	0.437	7.7	5/16"	21.71

Guard Rail Adjuster Fork & Sta-Lok


- Marine grade stainless steel fittings
- Provides weight and length reduction on conventional turnbuckles
- Swivel action - adjust one end only
- Adjustment +/- 16mm (5/8")
- Supplied with Sta-Lok stud (Reusable, self-fit wire rope terminal)
- Supplied with split ring



Reference	Wire Size (MM)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Weight (KG)	Weight (LB)	Price (£)
G26-04	4 MM	15.0	0.591	11.1	0.437	7.7	5/16"	0.110	0.243	50.46
G26-05	5 MM	15.0	0.591	11.1	0.437	7.7	5/16"	0.120	0.265	55.74

Guard Rail Adjuster Fork & Fork



- Marine grade stainless steel fittings
- Provides weight and length reduction on conventional turnbuckles
- Swivel action - adjust one end only
- Adjustment +/- 16mm (5/8")
- Supplied with Fork at either end
- Supplied with split ring



Reference	Thread (UNF)	Thread (Metric)	B (MM)	B (Inch)	D (MM)	D (Inch)	P (MM)	P (Inch)	Price (£)
G31-516	5/16"	-	15.0	0.591	11.1	0.437	7.7	5/16"	35.81

Guard Rail Single Eye


- Marine grade stainless steel
- Available with UNF & metric right hand threads



Reference	Thread (UNF)	Thread (Metric)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
GE1 - 516	5/16"	-	16.0	0.625	19.4	0.764	0.020	0.044	10.69
GE1 - M8	-	M8	16.0	0.625	19.4	0.764	0.020	0.044	10.69

Guard Rail Interlocking Eye


- Marine grade stainless steel
- Available with UNF & metric right hand threads



Reference	Thread (UNF)	Thread (Metric)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
GE2 - 516	5/16"	-	38.8	1.528	0.040	0.088	21.24
GE2 - M8	-	M8	38.8	1.528	0.040	0.088	21.24

Short Swage Stud

- Designed specifically for guard rail eyes (GE1 & GE2)
- Marine grade stainless steel
- Available with UNF & metric right hand threads
- Should be machine swaged



A = DIAMETER
BEFORE SWAGING



Reference	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Thread (Metric)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
051-04-SH	4 MM	5/32"	5/16"	-	7.4	0.292	11.1	0.437	0.020	0.044	5.36
051-04M8-SH	4 MM	5/32"	-	M8	7.4	0.292	11.1	0.437	0.020	0.044	5.36
051-05-SH	5 MM	3/16"	5/16"	-	9.0	0.354	11.1	0.437	0.030	0.066	9.36
051-05M8-SH	5 MM	3/16"	-	M8	9.0	0.354	11.1	0.437	0.030	0.066	9.36
051-06-SH	6 MM	-	5/16"	-	12.4	0.489	11.1	0.437	0.050	0.110	10.63
051-06M8-SH	6 MM	-	-	M8	12.4	0.489	11.1	0.437	0.050	0.110	10.63

Pelican Hook

- Designed specifically for guard rails and life lines
- Manufactured from Stainless Steel Grade 316
- UNF & Metric right hand threads
- Nut not supplied



Reference	Wire Size (MM)	Thread (UNF)	Thread (Metric)	Weight (KG)	Weight (LB)	Price (£)
PH-516	4 MM - 5 MM	5/16"	-	0.140	0.309	23.30
PH-M8	4 MM - 5 MM	-	M8	0.140	0.309	23.30

Pelican Hook with Sta-Lok Stud

- Designed specifically for guard rails
- Manufactured from Stainless Steel Grade 316
- Provided with a reusable, self-fit Sta-Lok Stud
- Supplied with right hand nut



Reference	Wire Size (MM)	Thread (UNF)	Price (£)
PH-0364 516	4 MM	5/16"	51.88
PH-0365 516	5 MM	5/16"	57.16

Pelican Hook with Swage Stud

- Designed specifically for guard rails
- Manufactured from Stainless Steel Grade 316
- UNF & Metric right hand threads
- Supplied with right hand nut
- Supplied with standard swage stud (051 or 061)



Reference	Wire Size (MM)	Thread (UNF)	Thread (Metric)	Weight (KG)	Weight (LB)	Price (£)
PH-0514 516	4 MM	5/16"	-	0.180	0.397	30.64
PH-0514 M8	4 MM	-	M8	0.180	0.397	30.64
PH-0515 516	5 MM	5/16"	-	0.180	0.397	34.64
PH-0515 M8	5 MM	-	M8	0.180	0.397	34.64

Stainless Steel Turnbuckle Body

- These classic standard stainless steel turnbuckles are manufactured from 316 stainless steel tube
- Available in Metric and UNF Threads



Reference	Thread (UNF)	Thread (Metric)	A (MM)	A (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
TB-M6	-	M6	90.0	3.543	62.0	2.441	8.07
TB-14	1/4"	-	90.0	3.543	62.0	2.441	8.07
TB-M8	-	M8	105.0	4.134	68.0	2.677	13.90
TB-516	5/16"	-	112.0	4.409	68.0	2.677	13.90
TB-M10	-	M10	125.0	4.921	80.0	3.150	15.48
TB-38	3/8"	-	125.0	4.921	80.0	3.150	15.48
TB-M12	-	M12	150.0	5.906	96.0	3.779	27.35
TB-12	1/2"	-	150.0	5.906	96.0	3.779	27.35
TB-M16	-	M16	192.0	7.559	123.0	4.843	35.42
TB-58	5/8"	-	192.0	7.559	123.0	4.843	35.42

Stainless Steel Toggle & Blank

- Manufactured from polished stainless steel seamless tube
- Supplied with a Threaded Strap Toggle at one end
- Swivel toggle action allows full articulation in two planes
- Designed to fit most chain plates and fixing points
- Supplied with nut



Reference	Thread (UNF)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
ST20-14	1/4"	6.4	0.252	6.4	1/4"	62.0	2.441	22.75
ST20-516	5/16"	8.4	0.331	7.9	5/16"	68.0	2.677	31.95
ST20-38	3/8"	9.9	0.390	9.5	3/8"	80.0	3.150	36.56
ST20-12	1/2"	13.1	0.516	12.7	1/2"	96.0	3.779	57.66
ST20-58	5/8"	16.3	0.642	16.0	5/8"	123.0	4.843	88.78

Stainless Steel U-Strap Toggle & Blank


- Manufactured from polished stainless steel seamless tube
- Provided with Forged T U-Strap toggle design for longer chain plates
- Swivel toggle action allows full articulation in two planes
- Supplied with nut



Reference	Thread (UNF)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
UST20-14	1/4"	7.6	0.299	6.4	1/4"	62.0	2.441	33.37
UST20-516	5/16"	9.2	0.362	7.9	5/16"	68.0	2.677	39.89
UST20-38	3/8"	10.8	0.425	9.5	3/8"	80.0	3.150	51.09

Stainless Steel Toggle & Swage

- Manufactured from polished stainless steel seamless tube
- Supplied with a Threaded toggle at one end and Swage Stud (051) at the other end
- Swivel toggle action allows full articulation in two planes
- Designed to fit most chain plates and fixing points



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
ST24-03	3 MM	1/8"	1/4"	213.0	151.0	8.386	5.945	6.4	0.252	6.4	1/4"	30.85
ST24-144	4 MM	5/32"	1/4"	220.0	158.0	8.661	6.220	6.4	0.252	6.5	1/4"	30.85
ST24-04	4 MM	5/32"	5/16"	239.0	171.0	9.409	6.732	8.4	0.331	7.9	5/16"	40.09
ST24-5165	5 MM	3/16"	5/16"	240.0	172.0	9.449	6.772	8.4	0.331	7.9	5/16"	44.08
ST24-05	5 MM	3/16"	3/8"	275.0	195.0	10.827	7.677	9.9	0.390	9.5	3/8"	49.03
ST24-386	6 MM	-	3/8"	271.0	191.0	10.669	7.520	9.9	0.390	9.5	3/8"	54.30
ST24-07	7 MM	9/32"	1/2"	333.0	237.0	13.110	9.331	13.1	0.516	12.7	1/2"	85.29
ST24-08	8 MM	5/16"	1/2"	333.0	237.0	13.110	9.331	13.1	0.516	12.7	1/2"	88.63
ST24-588	8 MM	5/16"	5/8"	408.0	285.0	16.063	11.220	16.3	0.642	16.0	5/8"	123.46
ST24-10-5/8	10 MM	-	5/8"	412.0	290.0	16.220	11.417	16.3	0.642	16.0	5/8"	134.15




Don't see your perfect arrangement or require a different size for Inch Wire?

Refer to Stainless Steel Toggle & Blank (page 102) and choose your Swage Stud (051) to match from page 37.

Stainless Steel Toggle & Sta-Lok


- Manufactured from polished stainless steel seamless tube
- Supplied with a Threaded Strap Toggle at one end and Sta-Lok Self-Fit Stud (036) at the other end
- Swivel toggle action allows full articulation in two planes
- Designed to fit most chain plates and fixing points



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
ST22-03	3 MM	1/8"	1/4"	207.0	145.0	8.150	5.709	6.4	0.252	6.4	1/4"	60.71
ST22-144	4 MM	5/32"	1/4"	208.0	146.0	8.189	5.748	6.4	0.252	6.5	1/4"	52.09
ST22-04	4 MM	5/32"	5/16"	230.0	162.0	9.055	6.378	8.4	0.331	7.9	5/16"	61.33
ST22-5165	5 MM	-	5/16"	234.0	166.0	9.213	6.535	8.4	0.331	7.9	5/16"	66.61
ST22-05	5 MM	-	3/8"	268.0	188.0	10.551	7.402	9.9	0.390	9.5	3/8"	71.55
ST22-386	6 MM	-	3/8"	264.0	184.0	10.394	7.244	9.9	0.390	9.5	3/8"	81.47
ST22-07	7 MM	9/32"	1/2"	319.0	223.0	12.559	8.780	13.1	0.516	12.7	1/2"	113.09
ST22-08	8 MM	5/16"	1/2"	320.0	224.0	12.598	8.819	13.1	0.516	12.7	1/2"	123.14
ST22-588	8 MM	5/16"	5/8"	398.0	275.0	15.669	10.827	16.3	0.642	16.0	5/8"	156.03
ST22-10-5/8	10 MM	-	5/8"	398.0	275.0	15.669	10.827	16.3	0.642	16.0	5/8"	182.42

Stainless Steel Toggle & Toggle


- Manufactured from polished stainless steel seamless tube
- Supplied with a Threaded Strap Toggle at either end
- Swivel toggle action allows full articulation in two planes
- Designed to fit most chain plates and fixing points



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Price (£)
ST41-14	1/4"	233.0	171.0	9.173	6.732	6.4	0.252	6.4	1/4"	37.42
ST41-516	5/16"	261.0	193.0	10.276	7.598	8.4	0.331	7.9	5/16"	50.00
ST41-38	3/8"	296.0	216.0	11.654	8.504	9.9	0.390	9.5	3/8"	57.65
ST41-12	1/2"	365.0	269.0	14.370	10.591	13.1	0.516	12.7	1/2"	87.99
ST41-58	5/8"	443.0	321.0	17.441	12.638	16.3	0.642	16.0	5/8"	142.13

Stainless Steel Toggle & Fork

- Manufactured from polished stainless steel seamless tube
- Supplied with a Threaded Strap Toggle (B15 / B18) at one end with a Threaded Machined Fork (B16 / B17) at the other
- Swivel toggle action allows full articulation in two planes
- Designed to fit most chain plates and fixing points



Ref	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Toggle Width (MM)	Toggle Width (Inch)	Toggle Pin (MM)	Toggle Pin (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
ST21-14	1/4"	216.0	154.0	8.504	6.063	6.4	0.252	6.4	1/4"	6.4	0.252	6.2	1/4"	52.09
ST21-516	5/16"	250.0	182.0	9.843	7.165	8.4	0.331	7.9	5/16"	7.9	0.311	7.7	5/16"	63.26
ST21-38	3/8"	286.0	206.0	11.260	8.110	9.9	0.390	9.5	3/8"	9.5	0.374	9.3	3/8"	74.90
ST21-12	1/2"	354.0	258.0	13.937	10.157	13.1	0.516	12.7	1/2"	12.7	0.500	12.6	1/2"	114.51
ST21-58	5/8"	434.0	310.0	17.087	12.205	16.3	0.642	16.0	5/8"	15.9	0.625	15.6	5/8"	218.45

Stainless Steel Fork & Blank


- Manufactured from polished stainless steel seamless tube
- Threaded Machined Fork (B16) provided at one end
- Designed to fit most chain plates and fixing points
- Supplied with right hand nut



Reference	Thread (UNF)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
ST30-14	1/4"	6.4	0.252	6.2	1/4"	62.0	2.441	37.42
ST30-516	5/16"	7.9	0.311	7.7	5/16"	68.0	2.677	45.22
ST30-38	3/8"	9.5	0.374	9.3	3/8"	80.0	3.150	53.81
ST30-12	1/2"	12.7	0.500	12.6	1/2"	96.0	3.779	84.19
ST30-58	5/8"	15.9	0.625	15.6	5/8"	123.0	4.843	164.98

Stainless Steel Fork & Swage


- Manufactured from polished stainless steel seamless tube
- Supplied with a Threaded Machined Fork (B16) at one end and a Swage Stud (051) at the other
- Designed to fit most chain plates and fixing points



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
ST28-03	3 MM	1/8"	1/4"	201.0	139.0	7.913	5.472	6.4	0.252	6.2	1/4"	45.52
ST28-144	4 MM	5/32"	1/4"	209.0	147.0	8.228	5.787	6.4	0.252	6.2	1/4"	45.52
ST28-04	4 MM	5/32"	5/16"	230.0	162.0	9.055	6.378	7.9	0.311	7.7	5/16"	53.35
ST28-5165	5 MM	3/16"	5/16"	232.0	164.0	9.134	6.457	7.9	0.311	7.7	5/16"	57.34
ST28-05	5 MM	3/16"	3/8"	263.0	183.0	10.354	7.205	9.5	0.374	9.3	3/8"	66.28
ST28-386	6 MM	-	3/8"	263.0	183.0	10.354	7.205	9.5	0.374	9.3	3/8"	71.54
ST28-07	7 MM	9/32"	1/2"	328.0	232.0	12.913	9.134	12.7	0.500	12.6	1/2"	111.82
ST28-08	8 MM	5/16"	1/2"	328.0	232.0	12.913	9.134	12.7	0.500	12.6	1/2"	115.15
ST28-588	8 MM	5/16"	5/8"	390.0	267.0	15.354	10.512	15.9	0.625	15.6	5/8"	199.79
ST28-10	10 MM	-	5/8"	402.0	279.0	15.827	10.984	15.9	0.625	15.6	5/8"	210.35

Stainless Steel Fork & Sta-Lok


- Manufactured from polished stainless steel seamless tube
- Designed to fit most chain plates and fixing points
- Supplied with Threaded Machined Fork at one end and a reusable Sta-Lok Self-Fit Stud at the other



Ref	Wire Size (MM)	Wire Size (Inch)	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
ST26-03	3 MM	1/8"	1/4"	196.0	134.0	7.717	5.276	6.4	0.252	6.2	1/4"	75.38
ST26-144	4 MM	5/32"	1/4"	196.0	134.0	7.717	5.276	6.4	0.252	6.2	1/4"	66.76
ST26-04	4 MM	5/32"	5/16"	228.0	160.0	8.976	6.299	7.9	0.311	7.7	5/16"	74.59
ST26-5165	5 MM	-	5/16"	229.0	161.0	9.016	6.339	7.9	0.311	7.7	5/16"	79.88
ST26-05	5 MM	-	3/8"	256.0	176.0	10.079	6.929	9.5	0.374	9.3	3/8"	88.80
ST26-386	6 MM	-	3/8"	256.0	176.0	10.079	6.929	9.5	0.374	9.3	3/8"	98.71
ST26-07	7 MM	9/32"	1/2"	317.0	221.0	12.480	8.701	12.7	0.500	12.6	1/2"	139.61
ST26-08	8 MM	5/16"	1/2"	317.0	221.0	12.480	8.701	12.7	0.500	12.6	1/2"	149.66
ST26-588	8 MM	5/16"	5/8"	378.0	255.0	14.882	10.039	15.9	0.625	15.6	5/8"	232.24
ST26-10	10 MM	-	5/8"	378.0	255.0	14.882	10.039	15.9	0.625	15.6	5/8"	258.63

Stainless Steel Fork & Fork

- Manufactured from polished stainless steel seamless tube
- Threaded Machined Fork (B16 / B17) provided at both ends



Reference	Thread (UNF)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
ST31-14	1/4"	203.0	141.0	7.992	5.551	6.4	0.252	6.2	1/4"	66.76
ST31-516	5/16"	242.0	174.0	9.528	6.850	7.9	0.311	7.7	5/16"	76.53
ST31-38	3/8"	276.0	196.0	10.866	7.717	9.5	0.374	9.3	3/8"	92.14
ST31-12	1/2"	353.0	257.0	13.898	10.118	12.7	0.500	12.6	1/2"	141.04
ST31-58	5/8"	419.0	296.0	16.496	11.654	15.9	0.625	15.6	5/8"	286.45

Stainless Steel Welded Fork & Blank


- Manufactured from polished stainless steel seamless tube
- Supplied with a Welded Fork at one end
- Supplied with right hand nut



Reference	Thread (Metric)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Adjustment (MM)	Adjustment (Inch)	Price (£)
WT30-M6	M6	9.5	0.374	6.0	0.236	70.0	2.756	18.82
WT30-M8	M8	11.0	0.433	8.0	0.314	78.0	3.071	29.56
WT30-M10	M10	12.0	0.472	10.0	0.393	80.0	3.150	36.23
WT30-M12	M12	14.0	0.551	12.0	0.472	118.0	4.646	55.09

Stainless Steel Welded Fork & Swage


- Manufactured from polished stainless steel seamless tube
- Supplied with a Welded Fork at one end and Swage Stud (061) at the other
- Supplied with nuts
- Designed for machine swaging



Reference	Wire Size (MM)	Wire Size (Inch)	Thread (Metric)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
WT28-03-M6	3 MM	1/8"	M6	207.0	137.0	8.150	5.394	9.5	0.374	6.0	0.236	36.14
WT28-04-M6	4 MM	5/32"	M6	211.0	141.0	8.307	5.551	9.5	0.374	6.0	0.236	36.14
WT28-04-M8	4 MM	5/32"	M8	245.0	167.0	9.646	6.575	11.0	0.433	8.0	0.314	50.17
WT28-05-M8	5 MM	3/16"	M8	245.0	167.0	9.646	6.575	11.0	0.433	8.0	0.314	54.16
WT28-05-M10	5 MM	3/16"	M10	260.0	180.0	10.236	7.087	12.0	0.472	10.0	0.393	66.04
WT28-06-M10	6 MM	-	M10	260.0	180.0	10.236	7.087	12.0	0.472	10.0	0.393	71.32

Stainless Steel Welded Fork & Welded Fork

- Manufactured from polished stainless steel seamless tube
- Supplied with a Welded Fork at each end
- Supplied with nuts and split rings



Reference	Thread (Metric)	Fully Open (MM)	Fully Closed (MM)	Fully Open (Inch)	Fully Closed (Inch)	Fork Width (MM)	Fork Width (Inch)	Fork Pin (MM)	Fork Pin (Inch)	Price (£)
WT31-M6	M6	204.0	134.0	8.031	5.276	9.5	0.374	6.0	0.236	28.80
WT31-M8	M8	260.0	182.0	10.236	7.165	11.0	0.433	8.0	0.314	42.83
WT31-M10	M10	278.0	198.0	10.945	7.795	12.0	0.472	10.0	0.393	54.71
WT31-M12	M12	358.0	240.0	14.094	9.449	14.0	0.551	12.0	0.472	79.35



Other Products & Accessories



From Backing plates to ferrules and thimbles.
Find all your additional products and spare components.

Sta-Lok stock a large range of rigging hardware and replacement parts.

We carry a complementary range of British & Din Standard Copper Ferrules & Stainless Steel Thimbles, perfect for making hard eyes and loops.


Please note:

- 1. All products are supplied as singles unless a packet quantity is listed.

**Many elements, including usage, environment and standard of maintenance can affect the lifetime of your rigging. All fittings should be inspected, checked and maintained regularly.*

Eye Nut



- Manufactured from 316 Stainless Steel
- Right hand thread only



Reference	Thread (Metric)	C (MM)	C (Inch)	D (MM)	D (Inch)	H (MM)	H (Inch)	Price (£)
EN-M6	M6	26.5	1.043	5.5	0.216	15.0	0.590	3.65
EN-M8	M8	35.5	1.397	8.0	0.314	20.0	0.787	4.91
EN-M10	M10	44.5	1.751	10.0	0.393	25.0	0.984	7.45
EN-M12	M12	52.2	2.055	12.0	0.472	30.0	1.181	10.33

Eye Bolt


- Manufactured from 316 stainless steel
- Right hand thread only
- Perfect for marine and architectural applications



Reference	Thread (Metric)	C (MM)	C (Inch)	D (MM)	D (Inch)	E (MM)	E (Inch)	H (MM)	H (Inch)	Price (£)
EB-M6	M6	111.0	4.370	5.0	0.196	80.0	3.149	16.0	0.629	5.89
EB-M8	M8	142.0	5.590	7.0	0.275	100.0	3.937	20.0	0.787	7.73
EB-M10	M10	170.0	6.692	8.0	0.314	120.0	4.724	25.0	0.984	11.36
EB-M12	M12	200.0	7.874	9.5	0.374	140.0	5.511	30.0	1.181	15.63

Stemball Cup

- Manufactured from high specification 316 stainless steel
- Used to fit Stemball fittings into spreader bracket
- One or two Stemball cups may be required to bring the head size up to fit the mast/spreader brackets




Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
042C-4	4 MM	5/32"	9.0	0.354	26.0	1.024	0.016	0.035	10.05
042C-5	5 MM	3/16"	11.2	0.441	26.0	1.024	0.014	0.031	10.05
042C-6/7	6 MM & 7 MM	7/32", 1/4", 9/32"	16.0	0.630	26.0	1.024	0.016	0.035	10.05
042C-8/10	8 MM & 10 MM	5/16" & 3/8"	20.0	0.787	34.0	1.339	0.017	0.037	11.33

Notes:

Shroud Backing Plate


- Manufactured from high specification 316 stainless steel
- Design to be used only with Shroud Terminals



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	Weight (KG)	Weight (LB)	Price (£)
BP 145-08	8 MM	5/16"	120.0	4.750	39.4	1.550	39.8	1.567	0.180	0.397	54.93
BP 145-10	10 MM	3/8"	150.0	5.900	43.8	1.720	44.5	1.750	0.320	0.705	78.11
BP 145-12	12 MM	7/16" & 1/2"	177.8	7.000	50.8	2.000	51.6	2.030	0.460	1.014	88.13

T Terminal Backing Plate


- Manufactured from high specification 316 stainless steel
- Design to be used only with T Terminals



Reference	Wire Size (MM)	Wire Size (Inch)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	Weight (KG)	Weight (LB)	Price (£)
BP 144-6/7	6 MM & 7 MM	1/4" & 9/32"	123.0	4.840	40.0	1.570	15.0	0.591	0.100	0.220	20.66
BP 144-8/10	8 MM & 10 MM	5/16" & 3/8"	151.0	5.940	38.0	1.496	19.0	0.748	0.240	0.529	79.83

Hexagonal Lock Nuts


- Manufactured from 316 Stainless Steel
- Left and Right Hand, Metric and UNF Threads are available
- Supplied as singles



Left Hand Reference	Right Hand Reference	Thread (UNF)	Thread (Metric)	A (MM)	A (Inch)	B (MM)	B (Inch)	Weight (KG)	Weight (LB)	Price (£)
HN-M6 L	HN-M6 R	-	M6	8.0	0.315	4.0	0.157	0.001	0.002	0.77
HN-14 L	HN-14 R	1/4"	-	8.0	0.315	4.0	0.157	0.001	0.002	0.77
HN-M8 L	HN-M8 R	-	M8	10.0	0.394	5.0	0.197	0.001	0.002	0.80
HN-516 L	HN-516 R	5/16"	-	10.0	0.394	5.0	0.197	0.001	0.002	0.80
HN-M10 L	HN-M10 R	-	M10	13.0	0.512	7.0	0.276	0.001	0.002	1.12
HN-38 L	HN-38 R	3/8"	-	13.0	0.512	6.5	0.256	0.001	0.002	1.12
HN-716 L	HN-716 R	7/16"	-	14.0	0.551	8.4	0.331	0.009	0.020	1.75
HN-M12 L	HN-M12 R	-	M12	17.0	0.669	8.0	0.315	0.009	0.020	1.75
HN-12 L	HN-12 R	1/2"	-	17.0	0.669	8.0	0.315	0.010	0.022	1.75
HN-M16 L	HN-M16 R	-	M16	22.0	0.866	11.0	0.433	0.020	0.044	3.53
HN-58 L	HN-58 R	5/8"	-	22.0	0.866	11.0	0.433	0.020	0.044	3.53
HN-M20 L	HN-M20 R	-	M20	24.0	0.945	13.0	0.512	0.020	0.044	4.92
HN-34 L	HN-34 R	3/4"	-	24.0	0.945	13.0	0.512	0.020	0.044	4.92
HN-M22 L	HN-M22 R	-	M22	30.0	1.181	17.0	0.669	0.040	0.088	20.07
HN-78 L	HN-78 R	7/8"	-	30.0	1.181	16.5	0.650	0.040	0.088	20.07
HN-M24 L	HN-M24 R	-	M24	36.0	1.417	18.0	0.799	0.088	0.194	22.90
HN-100 L	HN-100 R	1"	-	36.0	1.417	17.5	0.689	0.088	0.194	22.90

Stainless Steel Thimble

- Suitable for forming hard eyes in wire ropes
- Thimbles reinforce and support looped wire rope eyes and create a lasting surface



Reference	Wire Size (MM)	A (MM)	A (Inch)	B (MM)	B (Inch)	C (MM)	C (Inch)	D (MM)	D (Inch)	Weight (KG)	Weight (LB)	Price (£)
T-02	2 MM	10.3	0.406	22.0	0.866	2.3	0.091	0.8	0.033	0.003	0.007	0.33
T-03	3 MM	12.8	0.504	25.0	0.984	3.2	0.134	1.0	0.039	0.003	0.007	0.40
T-03S	3 MM	10.4	0.409	18.0	0.709	3.6	0.142	1.0	0.039	0.003	0.007	0.46
T-04	4 MM	13.6	0.535	28.5	1.122	4.3	0.169	1.0	0.039	0.007	0.015	0.59
T-05	5 MM	16.3	0.642	32.0	1.260	5.8	0.228	1.0	0.039	0.007	0.015	0.63
T-05S	5 MM	13.4	0.528	24.0	0.945	5.8	0.228	1.0	0.039	0.006	0.013	0.63
T-06	6 MM	17.3	0.681	33.0	1.299	6.4	0.252	1.3	0.051	0.014	0.031	0.76
T-07	7 MM	19.3	0.760	36.0	1.417	8.4	0.331	1.5	0.059	0.014	0.031	1.52
T-08	8 MM	22.7	0.894	41.0	1.614	8.6	0.339	1.5	0.059	0.022	0.049	2.11
T-10	10 MM	26.0	1.024	46.0	1.811	12.0	0.472	1.5	0.059	0.028	0.062	3.92
T-12	12 MM	29.6	1.165	55.0	2.165	14.5	0.571	2.6	0.102	0.040	0.088	4.55

Copper Ferrules

- Copper Ferrule for crimping wire rope
- Suitable for forming eyes and stops in wire rope
- Swaging press or crimping tool required
- Supplied as singles



Reference	Wire Size (MM)	Wire Rope Limits - Wire Core (MM)	Weight (KG)	Weight (LB)	Price (£)
British Standard					
BF-CU 01.5	1 MM	0.95 - 1.05	0.002	0.004	0.26
BF-CU 02	1.5 MM	1.45 - 1.60	0.002	0.004	0.39
BF-CU 02.5	2 MM	1.95 - 2.15	0.002	0.004	0.49
BF-CU 03	2.5 MM	2.40 - 2.65	0.004	0.009	0.74
BF-CU 03.5	3 MM	2.90 - 3.20	0.006	0.013	0.91
BF-CU 04	3.5 MM	3.40 - 3.70	0.010	0.022	1.26
BF-CU 04.5	4 MM	3.90 - 4.30	0.014	0.031	1.62
BF-CU 05	5 MM	4.60 - 5.40	0.016	0.035	1.87
BF-CU 06	6 MM	6.30	0.024	0.053	2.11
BF-CU 08	8 MM	8.50	0.068	0.150	6.00
Din Standard 3093					
F-CU 01.5	1 MM	1.1 - 1.4	0.001	0.002	0.24
F-CU 02	1.5 MM	1.5 - 1.9	0.002	0.004	0.26
F-CU 02.5	2 MM	2.0 - 2.4	0.002	0.004	0.29
F-CU 03	2.5 MM	2.5 - 2.9	0.002	0.004	0.40
F-CU 03.5	3 MM	3.0 - 3.4	0.004	0.009	0.56
F-CU 04	3.5 MM	3.5 - 3.8	0.006	0.013	0.74
F-CU 04.5	4 MM	3.9 - 4.3	0.010	0.022	1.08
F-CU 05	4.5 MM	4.4 - 4.8	0.012	0.026	1.29
F-CU 06	5 MM	4.9 - 5.8	0.020	0.044	2.11
F-CU 06.5	6 MM	5.9 - 6.2	0.026	0.057	2.36
F-CU 07	6.5 MM	6.3 - 6.7	0.034	0.075	3.10
F-CU 08	7 MM	6.8 - 7.7	0.044	0.097	4.18
F-CU 09	8 MM	7.8 - 8.6	0.064	0.141	6.09
F-CU 10	9 MM	8.7 - 9.6	0.092	0.203	7.66
F-CU 11	10 MM	9.7 - 10.5	0.116	0.256	10.46
F-CU 12	11 MM	10.6 - 11.5	0.160	0.353	13.28

Split Pins

- Manufactured from 316 Stainless Steel
- Used to retain fork and clevis pins, studs etc.



Reference	DIA	Length (MM)	Length (Inch)	Pack (Quantity)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
779-00 PKT-10	1.5 X 12	12.0	0.468	10	0.010	0.022	1.26
779-01 PKT-10	2.3 X 12	12.0	0.468	10	0.010	0.022	1.39
779-02 PKT-10	2.3 X 16	16.0	0.624	10	0.010	0.022	1.41
779-03 PKT-10	2.3 X 19	19.0	0.741	10	0.020	0.044	1.46
779-04 PKT-10	3 X 19	19.0	0.741	10	0.020	0.044	1.67
779-05 PKT-10	3 X 24	24.0	0.936	10	0.060	0.132	2.75
779-06 PKT-10	5 X 40	40.0	1.560	10	0.070	0.154	5.42
779-07 PKT-10	5 X 52	52.0	2.028	10	0.080	0.176	7.49

Split Rings


- Manufactured from 316 Stainless Steel
- Used to restrain fork and clevis pins, studs etc.



Reference	DIA (MM)	DIA (Inch)	Pack (Quantity)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
C775-01 PKT-10	16.0	0.630	10	0.010	0.022	2.66
C775-02 PKT-10	24.0	0.945	10	0.020	0.044	3.72

Strap Toggle Pin


- Manufactured from 316 Stainless Steel
- Replacement pin for Strap Toggles, product reference (038, B15, B18)



Reference	A (MM)	A (Inch)	P (MM)	P (Inch)	Pack (Quantity)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
057-03	12.7	0.500	6.4	1/4"	5	0.125	0.276	21.88
057-04	15.5	0.610	7.9	5/16"	5	0.225	0.496	19.31
057-05	17.5	0.689	9.5	3/8"	5	0.400	0.882	20.60
057-06	20.2	0.795	11.1	7/16"	5	0.550	1.213	26.53
057-08	23.8	0.937	12.7	1/2"	2	0.128	0.282	10.69
057-10	31.0	1.220	16.0	5/8"	2	0.240	0.529	14.67
057-12	38.1	1.500	18.5	3/4"	1	0.101	0.223	11.97
057-14	42.0	1.654	21.5	7/8"	1	0.160	0.353	16.61

Sta-Lok Fork Pin


- Manufactured from 316 Stainless Steel
- Replacement pin for Sta-Lok Fork, product reference (034)



Reference	A (MM)	A (Inch)	P (MM)	P (Inch)	Pack (Quantity)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
037-03	15.5	0.610	5.0	3/16"	5	0.100	0.220	25.88
037-04	17.5	0.689	6.4	1/4"	5	0.200	0.441	25.88
037-05	20.6	0.811	8.0	5/16"	5	0.300	0.661	33.21
037-06	27.0	1.063	10.9	7/16"	5	0.600	1.323	47.76
037-07	27.0	1.063	10.9	7/16"	5	0.600	1.323	47.76
037-08	34.1	1.343	12.6	1/2"	2	0.128	0.282	21.24
037-10	37.3	1.469	15.6	5/8"	2	0.280	0.617	25.88
037-12	47.6	1.874	18.5	3/4"	1	0.120	0.265	25.24
037-14	50.8	2.000	21.5	7/8"	1	0.160	0.353	65.66
037-16	54.0	2.126	21.5	7/8"	1	0.180	0.397	75.87
037-19	66.7	2.626	27.0	11/16"	1	0.392	0.864	88.96
037-22	80.1	3.187	31.5	11/4"	1	0.680	1.500	112.78
037-26	96.0	3.781	34.6	13/8"	1	0.890	1.962	127.95

Turnbuckle Fork Pins


- Replacement pin for Turnbuckle Fork, product references: B16 and B17
- For UNF Thread turnbuckles only



Reference	Turnbuckle (UNF)	A (MM)	A (Inch)	P (MM)	P (Inch)	Pack (Quantity)	Weight per pack (KG)	Weight per pack (LB)	Price (£)
047-03	1/4"	14.5	0.571	6.2	1/4"	5	0.020	0.044	19.31
047-04	5/16"	19.0	0.748	7.7	5/16"	5	0.040	0.088	21.88
047-05	3/8"	23.8	0.937	9.3	3/8"	5	0.085	0.187	31.93
047-06	7/16"	27.0	1.063	10.9	7/16"	5	0.140	0.309	37.85
047-08	1/2"	34.1	1.343	12.6	1/2"	2	0.080	0.176	14.03
047-10	5/8"	40.5	1.594	15.6	5/8"	2	0.140	0.309	17.89
047-12	3/4"	47.6	1.874	18.5	3/4"	1	0.120	0.265	24.59
047-14	7/8"	54.0	2.126	21.5	7/8"	1	0.180	0.397	29.86
047-16	1"	60.3	2.374	25.0	1"	1	0.280	0.617	43.77
047-19	1 1/8"	69.8	2.748	28.2	1 1/8"	1	0.392	0.864	88.82
047-22	1 1/4"	74.6	2.937	31.5	1 1/4"	1	0.680	1.500	112.78
047-26	1 3/8"	87.3	3.437	34.6	1 3/8"	1	0.890	1.962	127.95

Wire Rope Grip

- To be used with stainless steel wire rope
- Suitable for forming eyes in wire rope
- Adjustable and reusable



Reference	Wire Size (MM)	A (MM)	A (Inch)	C (MM)	C (Inch)	Price (£)
WG-02	2 MM	14.0	0.550	18.0	0.707	1.86
WG-03	3 MM	16.0	0.629	21.0	0.825	2.08
WG-04	4 MM	18.0	0.707	24.0	0.943	2.26
WG-05	5 MM	22.0	0.865	28.0	1.100	2.56
WG-06	6 MM	27.0	1.061	33.0	1.297	3.09
WG-08	8 MM	34.0	1.336	40.0	1.572	3.88
WG-10	10 MM	44.0	1.729	50.0	1.965	5.66
WG-12	12 MM	50.0	1.965	63.0	2.476	10.60

Terms & Conditions

1. DEFINITIONS

In these Terms & Conditions, unless the context otherwise requires:

“The Company” means Sta-Lok Terminals Ltd of The Forge, Mistley Heath, Manningtree, Essex CO11 2QH.

“The Customer” means the person, firm or company to whom the Company supplies Goods under the Contract.

“The Contract” means the contract entered into between the Company and the Customer in relation to the Goods supplied, and

“The Goods” means the goods which the company is to supply to the Customer under the Contract.

2. GENERAL

2.1 The Company supplies the Goods on these Terms & Conditions only. Accordingly these Terms and Conditions shall apply to all orders for the Goods which are received from the Customer and (save as shall have been expressly agreed in writing by a director of the Company) shall prevail over any conditions of contract which the Customer may seek to impose. No variation of, or addition to, these Terms & Conditions and no representations about the Goods will be binding on the Company unless made in writing and signed by a director of the Company.

2.2 Any reference in these Terms & Conditions to any provision of an Act of Parliament or statutory instrument shall be construed as a reference to that provision as amended, re-enacted or extended from time to time.

2.3 The headings in these Terms & Conditions are set out for convenience only and shall have no effect on the interpretation of the individual clauses.

3. THE SCOPE OF CONTRACT

3.1 The Contract does not become binding upon the Company until the Company has issued a written acceptance of the Customer's order.

3.2 The Company's obligations under the Contract shall be limited to supplying the Goods contemplated by the Customer's order together with any variations thereof and additions thereto, which may subsequently be agreed. The Customer must give the Company reasonable notice of any variations and additions that are required.

4. PRICE

4.1 Subject as hereinafter provided, the price payable by the Customer for the Goods shall reflect the Company's price list from time to time in force in relation to the Customer except where the Company has issued a written quotation to the Customer, in which case the price or prices referred to in that quotation shall prevail,

4.2 The Company does however reserve the right to increase the price payable in order to reflect any agreed variations or additions to the Customer's requirements and any increases in production costs, which may be incurred by the Company between the date of the Customer's order and the date of despatch. In no circumstances shall any increase in the Contract price entitle the Customer to cancel its order or to repudiate the Contract but the Customer shall be entitled to receive notification of any such increases as soon as possible after their occurrence.

4.3 Unless expressly included in any quote given to the Customer, the Company shall be entitled to recover from the Customer as an additional item at cost all transportation, insurance, storage and other associated costs and charges which are incurred by the Company in delivering the Goods in accordance with the Customer's order, including any additional costs and charges which may be incurred by the Company in the event of the Customer for any reason failing or being unable to accept delivery of the Goods when tendered or causing despatch or delivery to be withheld through the non-payment of any sum due to the Company.

4.4 Unless otherwise indicated, all prices listed or quoted are exclusive of any applicable Value Added or other relevant sales taxes, which the Company reserves the right to levy at the prevailing rate on all amounts actually charged to the Customer.

5. PAYMENT

5.1 Payment of sums due under the Contract shall be made by the Customer nett within 30 days of invoice, unless the Company has requested alternative terms of payment in which case payment should be made on the terms then requested. The Company shall be entitled to invoice the Customer for each consignment despatched at any time on or after the date of despatch.

5.2 In the event that payment is not made by the due date, the Company shall be entitled to charge the Customer interest on any overdue amounts at the rate of 2% per month (or at such other rate as maybe advised by the Company from time to time) for each month or part month during which the said amounts are to remain overdue (both before and after any judgement).

5.3 Payment on or before the due date is of the essence of the Contract. Accordingly the Company shall upon notice to the Customer be entitled to withhold delivery and/or suspend the performance of the Contract generally if at the time of the notice payment of any amount stated on any of the Company's invoices (whether related to the Contract or not) is then overdue. If the Customer fails within 14 days of notice to settle the amount outstanding under the said invoices, then the Company shall be entitled to terminate the Contract without further notice.

5.4 The Customer shall not be entitled to retain, deduct or defer any sums whatsoever due to the Company under the Contract on account of any dispute cross claim or set off which it might have with the Company or with any company in the same group of companies as the Company.

6. DELIVERY

6.1 The performance of the Contract is subject to availability, and therefore in the event that it is unable to supply any specific Goods or any specific quantities of Goods, the Company reserves the right to provide suitable alternatives or suitable alternative quantities, and to make such reasonable adjustments (upwards or downwards) to the Contract price as are necessary to reflect the change. Such alterations shall not entitle the Customer to repudiate the Contract.

6.2 Unless otherwise indicated, and subject to the provisions of clause 4.3, the Company shall be responsible for arranging delivery of Goods to the Customer's premises.

Accordingly the Customer undertakes to provide a safe and convenient access for the Company's delivery vehicles (or those of its agents) at each delivery point together with safe facilities for the loading and unloading of the Goods (including any assistance in loading and unloading that may be required). The placing of an order by the Customer shall be deemed to constitute authority for the Company's delivery vehicles (or those of its agents) to enter the Customer's premises where necessary and it shall be the responsibility of the Customer to supervise the safe discharge of each load.

6.3 Any time estimates or delivery dates given by the Company shall be by way of guidance only and shall not be of the essence of the Contract. Accordingly any delay in delivery shall not entitle the Customer to repudiate the Contract and the Company shall not be liable to the Customer (either in contract or tort) for any loss or damage whatsoever (including consequential losses, loss of profit and other losses of a similar nature) which may be suffered or sustained by it as a result of any failure by the Company to adhere to any time estimate or delivery date given.

6.4 If for any reason the Company still fails to deliver the Goods within any reasonable time limit specified by the Customer at any time after the Customer has purported to make time of the essence of the Contract, and a Court or any other arbiter subsequently finds the Company to be responsible for any loss or damage suffered by the Customer as a result thereof, the Company's liability therefore (both in contract and tort) shall be strictly limited to the excess (if any) of the cost to the Customer (over and above the Contract price) of obtaining similar goods (in the cheapest available market) to replace those not delivered.

6.5 Without prejudice to any of the above the Company shall be entitled to deliver the Goods by single delivery or instalment at its option and, whenever the Goods are delivered, or are to be delivered, by instalments, the Company shall be entitled to treat each delivery as a separate contract. Accordingly any failure by the Company to make one delivery (in whole or in part) shall not entitle the Customer to terminate any other contract or refuse any other deliveries.

7. OWNERSHIP AND RISK

7.1 Unless otherwise indicated, the risk of damage to the Goods shall pass to the Customer upon delivery to the Customer or its agents

7.2 However, title to the goods shall not pass to the Customer until the Company has received payment in full of all sums due from the Customer under the Contract together with any interest accrued thereon and other charges. In the meantime, the Company shall retain full legal and beneficial title to the Goods and the Customer shall (a) hold the goods in a fiduciary capacity as the Company's bailee free from any charge, lien or other encumbrance, (b) shall keep the Goods fully insured with a reputable insurer, and (c) shall store the Goods separately in such a way that they can be clearly identified as the Company's property. In this period the Company shall be entitled to recover possession of the Goods (or any of them) at any time and for any reason whatsoever and shall be entitled without restriction to lawfully enter upon the premises to the customer for the purposes of removing the Goods. The customer shall pay all costs and expenses incurred by the Company in exercising this right.

7.3 If, pending the passing title in the Goods, the Customer sells or otherwise disposes of the Goods in such manner as to pass valid title to a third party, the Customer shall hold the full proceeds of such a sale (and pending payment the right to receive the proceeds of such a sale) on trust for the Company in a separate and identifiable bank account.

During the same period, the Customer will pay the said proceeds to the Company on demand notwithstanding that any period of credit extended to the Customer may not have expired. In addition the Customer agrees that it will assign to the Company upon the Company's request all of its rights (under such a contract of sale) against any subsequent purchaser of the Goods.

7.4 Notwithstanding that title may not have passed to the Customer, the Company may maintain an action for the price of the Goods supplied. The Customer acknowledges that nothing in clauses 7.2 and 7.3 above confers any right upon the Customer to return or reject the Goods supplied or to refuse, defer or delay payment for them.

8. LIEN

8.1 The Company shall (without prejudice to any other remedy available to it) have in respect of all unpaid debts and other sums due from the Customer under the Contract a general lien on any goods and property whatsoever in is possession (whether in relation to the contract or otherwise) which are or intended to become the property of the Customer.

8.2 Pursuant to that lien, the Company shall be entitled upon fourteen days written notice to the Customer to sell any goods or property so held upon such items as it thinks fit, and to keep the proceeds of the sale thereof in diminution of the debts, the other sums due and all costs and expenses incurred in or about effecting the sale.

9. CANCELLATION OF ORDERS

Orders for Goods which have been accepted by the Company may not be cancelled or suspended without the Company's prior written consent which consent the Company may give or withhold in its absolute discretion.

10. INVALIDITY OF ANY CONTRACTUAL TERM

If any clause or sub-clause or part thereof contained in these Terms and Conditions is held by any court or other competent authority to be invalid or unenforceable in whole or in part, the validity of the remainder of the clause or sub-clause and of the remaining clauses and sub-clauses of these Terms and Conditions shall not be affected thereby.

11. WAIVER

No waiver by the Company of any particular default or breach of Contract by the Customer shall be considered as a waiver of any subsequent default or breach of the same or of any other provision of the Contract.

12. ASSIGNMENT

The Customer may not assign the benefit or burden of the Contract without the written consent of the Company which the Company may give or withhold in its absolute discretion.

13. FORCE MAJEURE

In the event that the normal course of the Contract is frustrated, prevented, interrupted, hindered, delayed or rendered unduly expensive in any way whatsoever through war, rebellion, civil commotion, strike, lock-out or industrial dispute, fire, explosion, earthquake, act of God, flood, drought or bad weather, the unavailability or late delivery of supplies, the inability to secure labour or by any other cause whatsoever beyond the Company's control, the Company shall promptly give notice thereof to the Customer and shall have the right to cancel the Contract or defer its performance for as long as such force majeure shall continue.

14. PROPER LAW

The construction validity and performance of the Contract shall be governed by English Law and all disputes or questions which may arise out of, or in connection with, or in relation to the Contract shall be decided by the English Courts.

15. WARRANTIES AND LIMITATION OF LIABILITY

15.1 All Goods are sold on the basis that the Customer is neither a consumer nor deals as a consumer within the meaning of the Unfair Contract Terms Act 1977. Where the Goods are supplied under a consumer transaction, the statutory rights of the Customer shall be unaffected by anything set out in these Terms and Conditions.

15.2 The Company hereby warrants that the Goods are at the date of delivery free from any material defect in workmanship and will remain free from any material defect in workmanship and materials for a period of 2 years from the date of delivery to the Customer and correspond with any agreed written specification but the Company's liabilities under this warranty shall be limited to making available free of charge the labour and materials required to make good any such defects or (at the Company's option) replacing any defective Goods. The Company's liability under this warranty is also subject to the following conditions and limitations:

a. The Company will not accept any liability for any defective or faulty Goods supplied, unless the Customer gives the Company written notice of the defect or defects in question within 90 days of delivery (save where the defect or defects are of a nature which would not normally be apparent upon a reasonable inspection, in which case the notice of defect or defects must be given within 14 days of discovering the same);

b. The Company will not accept any liability for goods damaged in transit unless the Customer gives it written notice of the damage within 5 working days of delivery;

c. The Goods having been properly stored and used by the Customer prior to the defect occurring;

d. The Company will not accept any liability whatsoever in relation to any goods which have been fitted incorrectly or subjected to any incorrect, abnormal or improper load use accident or unauthorised modification, repair or application, whether by the Customer or any third party;

e. The goods having been used in accordance with the Company's instructions whether written or oral;

f. The Goods having been subjected to proper and adequate inspection after installation and properly maintained in accordance with the Company's guidelines;

g. The Goods having been returned at the Company's request but at the Customer's expense for inspection; and

h. The Company having received the total price for the Goods by the due date for payment. Without

prejudice to the provisions of clause 7.1 above, all goods which are returned to or replaced by the Company, shall become the property of the Company.

15.3 The warranty contained in clause 15.2 is given in lieu of and shall be deemed to exclude all other warranties and conditions whether express or implied whether arising by common law, statute or otherwise to the fullest extent permitted by law, other than that relating to title to the Goods. The warranty contained in clause 15.2 does not extend to parts, materials or equipment not manufactured by the Company, in respect of which the Customer shall only be entitled to the benefit of any such warranty or guarantee as is given by the manufacturer to the Company.

The warranty contained in clause 15.2 does not extend to cosmetic defects occurring after supply. In corrosive atmospheres stainless steel parts may show discolouration.

15.4 Save as provided under the Unfair Contract Terms Act 1977 and as mentioned in this clause 15, all

liability (both in contract and in tort) of the Company for any consequential losses, loss of profit and other losses of a similar nature which may be suffered or sustained by the Customer in connection with the contract and/or the quality or performance of the goods supplied there under is excluded to the fullest extent permitted by law.

15.5 All Goods are sold on the basis that the Customer has satisfied itself as to the suitability of the Goods for use or resale in accordance with its own specialised knowledge and skill and the Customer acknowledges that it has not placed any reliance upon the skill or judgement of the Company or of any of the Company's servants or agents. In the case of export orders, it is also the Customer's responsibility to ensure that the Goods comply with any legislation or regulations relating to their use in the country in question and the Company shall not therefore incur any liability whatever in respect thereof. The Company shall not be under any liability in respect of any defect arising from fair wear and tear, wilful damage or arising from any drawing, design or specification supplied by the Customer.

15.6 The Customer agrees to indemnify the Company against all claims relating to Goods sold to the Customer in respect of any loss damage or expense, whether direct or consequential, sustained by any third party save only in respect of death or personal injury caused by the negligence of the Company or any of its employees, agents or sub-contractors.

15.7 Notwithstanding the above provisions, the Company does not exclude or restrict its liability for death or personal injury caused by its negligence or that of its employees, agents or subcontractors.

15.8 Some states do not permit some of the limitations or exclusions noted above, so some of them may not apply to the Customer.


16. RETURNS

16.1 Rigging hardware manufactured by Sta-Lok is guaranteed at the time of shipment, to be free of defects in material and craftsmanship and only when used for the purpose intended.

16.2 Returned goods will not be accepted without notification and prior approval by Sta-Lok Terminals Ltd.

16.3 All returns must be prepaid and in a re-saleable condition before a credit can be issued. We reserve the right to make a re-stocking charge of 25%.

16.4 Items that have been manufactured to specific requirements, including but not limited too, Wire Rope Assemblies and Tie Rod Assemblies cannot be refunded.



STA-LOK®

The Forge, Mistley Heath,
Manningtree, Essex CO11 2QH
England

Contact us:

+44 (0) 1206 390773
enquiries@stalok.com

USA Office:

+1 910 259 3394
usa@stalok.com

Follow us on:



STA-LOK[®]