

The logo for Axis, featuring the word "axis" in a green, lowercase, serif font.

**Automatic Entrance Systems**

**STANLEY**

# ProCare 8300BP

**THE SPACE OPTIMIZING ICU DOOR SOLUTION  
DELIBERATELY DESIGNED WITH RESPECT FOR PATIENTS  
AND CAREGIVERS IN HEALTHCARE ENVIRONMENTS**



## **THE PROCARE DIFFERENCE**

The space-optimizing ICU door solution, this compact 4-panel bi-part is the newest alternative to the standard ICU door. With a smaller breakaway arc, you can meet NFPA corridor codes and never have to give up a square inch of your patient room design. Effortless one-handed operation slides both center panels simultaneously. Our exclusive soft open/close prevents loud slamming and extends the life of the door.



### **Protect the patient**

Wide clear door opening\* at 1044mm on an 2438mm door and 1196mm on 2743mm. Eliminate dangerous snagging of IV lines and equipment with our catch-free contoured handle and retractable positive latch hook shield.



### **Promote healing**

Easy and more controlled breakaway and return with our new intuitive swing-out button. Quiet and flawless operation with swing out guidance system.

## RATINGS\*

### Smoke & Draft

Leakage rated under ANSI/UL1784 and labeled as a smoke barrier. Learn More

- Smoke and Draft Seals
- Positive Latching With Retractable Positive Latch Hook Shield
- Identifiable Sticker For Rapid Commissioning

### Infection Control

Leakage rated, tested to ASTM E283-04 standards and in compliance with the 2014 FGI guidelines for pressurized Airborne Isolation Infection Rooms.

- Concealed Bottom Sweeps
- Perimeter Seals
- Self Closing

\* Restrictions may apply such as overall frame height, sliding/breakaway panel width and glazing.

All door packages are custom manufactured to fit your job requirements up to 6mm increments. For sizes greater or smaller than typical, contact Axis.

## STANDARD FEATURES

Catch-free Contoured Handle  
Swing Out Button  
Swing Out Guidance System  
Soft Open/Close

## OPTIONS

Integral Blinds  
Positive Latching With Hook Shield  
Self-Closing

## WATCH PROCARE 8300BP IN ACTION

<https://youtu.be/tWfi84fXMT8>

## TECHNICAL SPECIFICATIONS

<b>CONFIGURATIONS</b>	4-Panel Bi-Part, Smoke & Draft, Trackless, Manual
<b>TYPICAL HEIGHT</b>	2235mm; Taller Available
<b>TYPICAL WIDTH</b>	2438mm, Range 2134mm to 3656mm
<b>HEADER SIZE</b>	101mm Nominal Height
<b>BREAKAWAY TYPE</b>	Breakaway From Full Slide Open Position
<b>JAMB DIMENSION</b>	114mm x 22mm
<b>CLEAR DOOR OPENING WIDTH†</b>	Range: 892mm to 1654mm; 1044mm at 2438mm (Std) Width
<b>SUPPORTED GLAZING</b>	114mm (Std); 22mm, 13mm, 25mm Insulated
<b>STILES</b>	Narrow
<b>BOTTOM RAILS</b>	101mm (Std), 152mm, 203mm, 254mm, 305mm, other custom
<b>FINISHES</b>	Anodized, PVDF Paint, Anti-Microbial (Touch Points or All)
<b>HARDWARE</b>	Catch-free Contoured Handle Option: Positive Latch with Hook Shield, Single-Point Locking, Concealed Self Closing
<b>LISTINGS</b>	UL1784
<b>RATINGS</b>	Leakage (Smoke & Draft), +/- Pressure, ASTM E283-04
<b>Leakage (Smoke &amp; Draft), +/- Pressure, STC</b>	
<b>CODES AND STANDARDS</b>	NFPA 101, NFPA 105, IBC
<b>NFPA 101, NFPA 105, IBC</b>	

† Without Positive Latch

Specifications subject to change. Please contact us to ensure accuracy.



### Axis Automatic Entrance Systems Ltd

Unit 6, Queens Park Industrial Estate, Studland Road,  
Northampton, NN2 6NA.  
Tel: 01604 212500 · Fax 01604 212495  
Email: sales@axisautomatic.com  
www.axisautomatic.com



\* DT3/DP3 \*\*DP1/DP3

Specifications are subject to change without prior notice.  
All values measured in specific conditions.

