

# ProCare 8300

## 2-PANEL TRACKLESS MANUAL SLIDING ICU DOOR WITH FULL BREAKOUT



ProCare, is the new name to represent the next generation of the Stanley Dura-Care product family. The ProCare 8300 is the industry's only human-centric ICU door deliberately designed with respect for patients and caregivers in sensitive healthcare environments and featuring many new, patent pending components.

- Breakout is Now Swing Out
- Patent Pending Catch-Less Handle
- Patent Pending Magnetic SO Detent to allow smooth swing out with reduced force, no longer requiring to "break" the door open
- Patent pending Swing Interlock to prevent accidental swing out unless the door is fully open
- Instant swing out with button push release system instead of latches
- No panel sag during break out because the interlock system locks the hangar in place
- 22mm deep rectangular jambs providing industry's largest clear door opening

## OPTIONAL FEATURES

- Patent pending positive latch hook shield for positive latch applications, covering the exposed hook to eliminate dangerous snagging of IV lines
- Smoke and draft package
- STC rated package for reduced sound transmission
- Isolation room package (+/- pressure rated)
- Pocket jambs in both 22mm depth and 44mm depth
- Self-closers for heavier panels with thicker glass and wider packages
- The widest clear door opening in the industry, at 1120mm on a 2440mm package and 1275mm on a 2745mm package.
- Quiet and flawless operation every time with our swing out guidance system. No panel sag during swing out.

## APPLICATIONS

- ICU/CCUs
- Pressurized Isolation Rooms
- Smoke Rated Rooms
- Emergency Department Treatment Rooms
- Pre/Post Surgery Rooms
- Same Day Surgery Rooms
- Trauma Rooms



*Instant swing out with button push release system*

## CONFIGURATIONS:

### 2-PANEL TRACKLESS:

Smoke & Draft, Isolation, STC Rated

### TYPICAL HEIGHT:

Available in 2160mm -2745mm | 2235mm Typical

### TYPICAL WIDTH:

Available 2135mm to 2745 | 2440mm Typical

### HEADER SIZE:

100mm Nominal Height

### SWING OUT:

2 Panels Swing Out from Fully Open Position

### JAMB DIMENSION:

Standard: 22mm x 114mm Rectangular | Option: 44mm x 114mm Rectangular, 22mm x 114mm Pocket, 44mm x 114mm Pocket

### CLEAR DOOR OPENING WIDTH:

Available from 972mm to 1276mm | 1122mm at 2438mm (Typical) package

### SWING OUT OPENING WIDTH:

Available from 1980mm to 2590mm | 2286mm at 2438mm Typical Width

### SUPPORTED GLAZING:

Standard: 6mm | Optional: 15mm, 13mm, 25mm Integral Blinds, STC Rated Glass

### STILES:

Narrow

### BOTTOM RAILS:

100mm (Std), 150mm, 200mm, 250mm, 300mm, other custom

### MUNTINS:

0, 1 (Std) or 2

### FINISHES:

Anodized, PVDF Paint, Anti-Microbial (Touch Points or All)

### HARDWARE OPTIONS:

Standard: Catch-less Handle available in clear or black.

### OPTIONAL:

Positive Latch With Catch-Less Hook Shield, Single-Point Locking, Concealed Self Closing



### Axis Automatic Entrance Systems Ltd

Unit 6, Queens Park Industrial Estate, Studland Road,  
Northampton, NN2 6NA.

Tel: 01604 212500 · Fax 01604 212495

Email: sales@axisautomatic.com

www.axisautomatic.com

