



High pressure
cleaning equipment
for professionals



TD/SD352

SPECIFICATIONS

Pressure:	34-350 bar*
Water flow:	20 l/min*
Pump:	Cat Industrialpump
Max. temperature:	99°C* / 150°C**
Engine model:	Kubota D905
Engine type:	Diesel 3 cyl.
Engine power:	18 kw
Fuel tank:	80 litres
Water tank:	700 litres
Trailer dimensions LxWxH:	351x179x169 cm
Van mount dimensions LxWxH:	200x120x128 cm
Weight:	840 kg / 700 kg
Hot water driven:	Yes
Heat exchanger:	Yes

*Step less regulation of pressure and water flow

** Higher temperature can be reached by reduced flow

SAFETY SYSTEM WITH ERROR INDICATION

Open engine lid compartment
Low water level
Wash water temperature
Oil pressure
Engine temperature
Chimney lid
Engine overheat protection
Flame surveillance

STANDARD EQUIPMENT

Heat exchanger
Spray gun and lance
50 m water supply hose on reel
50 m high pressure hose on reel

EXTRA EQUIPMENT – FACTORY MOUNTED

BKX unloader
Hazard lights
Descale system
Anti freeze system
Chemical injection system
Automatic throttle control – ATC system
Remote control
Electric hose reels
150° C thermostat
Steam pack - low pressure steam operation

ACCESSORIES

Floor tools
Turbo nozzles
Water sandblasting kit
Extension hose and reels
Spray guns and lances
Tank cleaning head



www.aquila.dk

High pressure cleaning equipment for professionals

TD/SD352

ADVANTAGES

- Heat exchange system – saves diesel
- PLC touch screen
- Extensive safety program
- Large accessory program
- Large amount of know-how and experience as back-up
- Extensive service

ACCESSORIES


Floor tools:



Wall tools:




Turbo nozzles:




Spray guns and lances:



Chewing gum cleaners:



Chute cleaners:



Pipe cleaning nozzles:



Wet sandblasting kit:



tensid® uk ltd



technology | environment | partnership