PRODUCT DATA

tensid[®]uk Itd

Cladex AC

Cleaning for corrosion and limescale

Description and use

Cladex AC is an acidic cleaner formulated to remove corrosion stains and limescale deposits from anodised aluminium, stainless steel and some painted surfaces while at the same time providing a deep clean preparation

TECHNICAL DATA

Appearance: Colourless liquid

pH Value: 1

Boiling Point: N/A

Advantages

- Fast acting
- Economical

Preparation

Protect surrounding areas and be aware of wind drift

Equipment

Apply with a brush such as the tensid restoration brush or similar, low compression sprayer or a sponge.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures

Application Instructions

Agitate the product and then apply with the chosen method. Allow up to 1 minute dwell time before rinsing thoroughly with water.

Dilutions

Dilute the product to the appropriate strength, normally 3 parts water to 1 part Cladex AC. This product can be used neat if required however try first to make sure no damage occurs.

Coverage Rates

Approximately 10m² per litre

Safety Information

Wear suitable PPE - goggles and gloves to avoid splash to bare skin or eyes (Always refer to MSDS before use)

Shelf Life

Cladex AC may be stored for up to one year in a tightly sealed, unopened container and in a frost free environment

Packing

1 X 5 litre plastic container

This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit: **www.tensid.com**

Share your project photos and news on the Tensid UK social media professional community pages:









REVISION: 01 July 2015, Nº-2