PRODUCT DATA

tensid® uk ltd

AGS Graffi Ghost Poultice ®

For deep seated and stubborn ghosting

Description and use

AGS Graffi Ghost Poultice is a paste product ghosting remover. It works by oxidising away traces of pigments and by breaking down grease and oil residues in the substrate.
The poultice is specially formulated for the removal of difficult ghosting and is suitable for most surfaces.

TECHNICAL DATA

Appearance:	When mixed, yellow/brown paste
pH Value:	13 - 14
Boiling Point:	N/A

Advantages

- Fast acting and effective on most masonry surfaces Limitations
- Not effective if initial graffiti removal procedures have not been followed

Recommended as follows. Always test.

Substrate	Type		m^2 per litre
Concrete		Yes	0.2 - 1
Marble Travertine Limestone	Polished*	Yes	0.2 - 1
	Unpolished	Yes	0.2 - 1
Granite	Polished*	Yes	0.2 – 1
	Unpolished	Yes	0.2 – 1
Sandstone	Unpolished	Yes	0.2 – 1
Slate	Unpolished	Yes	0.2 – 1
Fired Clay	Brick Tile Terracotta Pavers	Yes Yes Yes Yes	0.2 – 1 0.2 – 1 0.2 – 1 0.2 - 1
Wood		No	

* *Test first.*

* *This product has a bleaching effect on fabric and some other non masonry surfaces.*

Preparation

Protect surrounding surfaces.

Equipment

Apply with a brush or trowel.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Mix powder with liquid to make up a creamy consistency.
2. With a brush or trowel, apply the poultice on affected areas.
3. Cover with black polythene and leave for up to 24 hours.
4. Remove poultice with a plastic spatula or trowel.
5. Rinse off with hot water pressure washing.
6. On non polished masonry surfaces, use Graffi Ghost Rinse or PROSOCO Limestone Afterwash.
7. Repeat the process if ghosting remains.

Coverage Rates

Coverage rates will vary according to the character of the surface.

Tensid UK Ltd., Unit 1 Craven Court, Canada Road, Byfleet. KT14 7JL
T: +44(0) 1932 564133 | E: info@tensid.com | Web: www.tensid.com

Packing

10 litre plastic container + 10kg powder

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.
Always rinse substrate clean of any other chemicals prior to application of Graffi Ghost Poultice. Never mix liquid component with other substances.

Shelf Life

Graffi Ghost Poultice may be stored for up to 1 year in a tightly sealed, unopened container.

This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:
www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:

tensid® uk ltd

AGS Graffi Ghost Poultice

REVISION: 01 July 2015, Nº·2

Tensid UK Ltd., Unit 1 Craven Court, Canada Road, Byfleet. KT14 7JL
T: +44(0) 1932 564133 | E: info@tensid.com | Web: www.tensid.com