### **Product Overview** Hydronic Underfloor Heating





#### **Wired** Room Controls

#### **Wireless** Room Controls

















		<b>Danfoss Icon™</b> Dial 230V	<b>Danfoss Icon™</b> Display 230V	<b>Danfoss Icon™</b> Programmable 230V	<b>Danfoss Icon™</b> Display 24V	<b>Danfoss Icon™</b> Wireless Dial	<b>Danfoss Icon™</b> Wireless Display Infrared available
Features	Energy saving	00	000	0000	00000	00000	00000
	Comfort level	Floor sensor not supported	Floor sensor not supported	Floor sensor supported	COC Sensor supported	Floor sensor not supported	<b>♦ • • • • • • • • • • • • • • • • • • •</b>
	Advanced features				App Auto Supply C° control	App Auto Supply C° control	App Auto Supply C° control balancing control
	Cooling option			**	***	***	**
	Adaptive learning			<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>
	Switchable frames	Available for in-wall	Available for in-wall	Available for in-wall	Available for in-wall		
	Installation	On-wall In-wall	On-wall In-wall	On-wall In-wall	On-wall in-wall	On-wall	On-wall
	Master Controller fit	230V	230V	230V	24V	24V	24V

# **Product Overview**Hydronic Underfloor Heating





## Supply Temperature Controls Mechanical systems





		<b>FHM-C1</b> Best with 230V system	<b>Midi Shunt</b> Danfoss Icon™ 230V included	
	Energy saving	000	000	
ures	Prefabrication (ready to go)	Incl. pump, temp. sensor and fittings	Incl. pump, temp. sensor, fittings and backplate. Needs only pipe connection. One circuit only	
Features	Plug and play installation	✓	<b>✓</b>	
	Control	Controlled by FTC temp. sensor	Controlled by FTC temp. sensor + Danfoss Icon™ 230V	

**Basic** Manifold







**Advanced** 

		<b>SSM</b> (without flowmeter)	<b>SSM-F</b> (with flowmeter)
	Comfort level	<del>aa</del>	444
ures	Hydronic balancing	w w w	
Features	Pre-setting	+	++
	Integrated end section	<b>✓</b>	<b>✓</b>