

**DIMENSIONS (mm)**

Standard Max Position Glass Height: 1700

Standard Counter Height: 1100

Standard Max Floor to Top of Bulkhead:  
2800

Standard Max Position Width: 1200

Counter Depth: Subject to project  
requirement

**WEIGHT**

Bespoke to project requirement

**RESISTANCE**

BS 5051 G2/S86

**CONSTRUCTION**

Armour plating is integral within  
construction of the systems  
and is concealed or unobtrusive.

The systems are self-supporting, with  
fixings to the floor, wall and bulkhead.

# DATASHEET

## BULLET RESISTANT MKII FRAMEWORK AND COUNTER

Bullet Resistant MKII Framework and Counter solutions offer protection against physical attack and BS 5051 G2/S86 ballistic resistance.

Typical applications are banks, building societies, government offices, cash office or any application where there is a serious risk of firearm attack or robbery.

### MAIN FEATURES

- These systems are typically installed with, or into, adjoining bullet resistant walls and doors to form a bullet resistant enclosure, which Safetell can supply as required
- Screens and counters are available in single, double and three tier versions for compliance with DDA regulations
- Can be manufactured to include a very wide range of sizes, materials and finishes to obtain the required corporate appearance
- A bespoke design process that allows for you to specify your counter and glazing every step of the way

### OPTIONAL

- Typically includes electronic speech transfer, also available with natural speech transfer
- A wide range of bullet resistant Cash Scoops are available
- Can be designed to incorporate Meridian Bulk Item Transfer Units



SERVICE &  
MAINTENANCE  
AVAILABLE

+44 (0) 1322 223 233

sales@safetell.co.uk safetell.co.uk